POOR LEGIBILITY

PORTIONS OF THIS DOCUMENT MAY BE UNREADABLE, DUE TO THE QUALITY OF THE ORIGINAL

NUS CORPORATION
1927 LAKESIDE PARKWAY
SUITE 614
TUCKER, GEORGIA 30084
404-938-7710

C-586-2-1-90

February 19, 1991

Mr. A.R. Hanke
Waste Programs Branch
Waste Management Division
Environmental Protection Agency
345 Courtland Street, N. E.
Atlanta, Georgia 30365

Date: 3-13-91
Site Disposition: NFRAP
EPA Project Manager: BENEDIKT (CB)

Subject: Screening Site Inspection, Phase I
Kentucky Petroleum Products
Louisville, Jefferson County, Kentucky
EPA ID No. KYD061564001
TDD No. F4-9001-115
Revision 0

Dear Mr. Hanke:

FIT 4 conducted a Screening Site Inspection, Phase I at Kentucky Petroleum Products in Louisville, Jefferson County, Kentucky. This assessment included a review of EPA and state file material, completion of a target survey and an offsite reconnaissance of the facility and surrounding area.

Kentucky Petroleum Products is located at 6911 Grade Lane at the intersection of Knopp Avenue in the city of Louisville, Jefferson County, Kentucky (Refs. 1, 2). The fenced facility occupies a 1 acre tract and is owned by Leo J. Shircliff (Refs. 2, 3). The facility is now known as Kentucky Petroleum Waste, Inc. (Ref. 2).

Kentucky Petroleum Products is a waste oil recycler that operates several tank trucks which collect waste oil and deliver it to a small storage facility (Ref. 1). The facility has been involved in petroleum products reclamation since 1962 and is currently active (Ref. 4). The storage facility consists of approximately 15 aboveground storage tanks. The waste oil is stored and later sold to various companies that either refine it into petroleum products, place it in a waste oil fuel program, or burn it as a waste oil fuel (Ref. 1).

Kentucky Petroleum Products did not file a RCRA Part A application for a hazardous waste permit in 1980 (Ref. 5). Kentucky Petroleum Products filed applications for transporting and handling of hazardous waste on June 22, 1977 and November 21, 1977 (Refs. 6, 7). On January 29, 1986, the facility filed a Notification of Hazardous Waste Activity stating that they were a Transporter and Treatment, Storage and/or Disposal facility; however, inspections conducted by the state have determined that the facility was not a hazardous waste TSD facility (Ref. 8) They were issued a Certificate of Registration as a Hazardous Waste Fuel Marketer and Off-specification Used Oil Marketer on May 9, 1986 (Ref. 9). The facility is currently registered as an off-specification used oil fuel marketer, off-specification used oil fuel burner, and specification used-oil fuel marketer (Refs. 10, 11).

In March 1978, Kentucky Petroleum Products deposited approximately 1,000 gallons of waste oil from a tank truck onto the working face of Mobile Waste landfill (Ref. 12). In February 1984, the state of Kentucky, Division of Waste Management collected samples from 13 onsite storage tanks. Analytical results identified solvents in all samples. The solvents identified were 1,1,1-trichloroethane with a concentration of 15 to 640 mg/kg, trichloroethene with a concentration of 1.1 to 1,600 mg/kg, and tetrachloroethene with a concentration of 16 to 4,700 mg/kg (Ref. 13). In October of 1988, the Kentucky Natural Resources and Environmental Protection Cabinet filed an Agreed Order with the Division of Hearings stating that the facility was in violation of several standards applicable to used oil fuel marketers and burners (Ref. 14).

Jefferson County lies within the Ohio River Valley and the Bluegrass regions of north-central Kentucky (Ref.15). This area is located on the western flank of the Cincinnati Arch, within the Interior Low Plateaus Physiographic Province and the nonglaciated central region hydrogeologic setting (Refs.15, 16,p.228). The net annual rainfall for the area is 9 inches and the 1-year, 24-hour rainfall is 2.8 inches (Refs. 17,pp.43,63; 18,p.93).

The majority of the county is drained by small tributaries of the Ohio River (Ref. 19,p. C5). The present valley of the Ohio River was cut into the shale and limestone bedrock during glacial times. The rock valley was filled with Quaternary alluvium which underlies the Ohio River flood plain to a maximum depth of 130 feet (Ref. 19, pp. C5, C7).

The alluvium in the Ohio River flood plain is the principal aquifer and second most important source of water in the area. The aquifer is made up of outwash sand and gravel of Pleistocene age ranging from 0 to 130 feet in thickness, depending on the altitude of the erosional surface of the underlying bedrock formations (Ref. 19, p. C7). The upper portion of the unconsolidated deposits consist of 5 to 40 feet of relatively impermeable clay, silt, and fine sand (Ref. 20, p. 49). Laboratory analysis of sediments similar to these have been shown to have hydraulic conductivities ranging between 1.0×10^{-5} cm/s and 1.0×10^{-7} cm/s (Ref. 21, p. 29). Beneath this layer are thick deposits of permeable sand and gravel (Ref. 20, p. 49).

The alluvial aquifer is hydraulically connected with the Ohio River in this area. Infiltration from the Ohio River and flow through the limestone valley wall are major contributors of recharge to the aquifer. Groundwater flow is generally toward the Ohio River (Refs. 20, 21). The depth of groundwater at the facility ranges between 5 and 10 feet below land surface (bls). The depth to groundwater is variable and is very dependent upon topographic elevation and position as well as the seasonal availability of water (Ref. 20).

The Louisville Limestone of Silurian age and the Jefferson and Sellersburg limestones of Devonian age underlie the alluvium. These bedrocks are considered to be a single aquifer. Water in this aquifer is contained in and moves along interconnected cracks and solution channels (Ref. 19, p. C18). The limestone beneath the flood plain is hydraulically connected with the alluvial deposits of sand and gravel, from which a continuing source of recharge is available. In the Bluegrass region, the limestone supplies small quantities of water to domestic wells, but beneath the Ohio River alluvium it is capable of yielding large quantities of water, mostly for industrial use (Ref. 15).

The Louisville Water Company (LWC) serves the city of Louisville, Kentucky. The LWC obtains potable water from two surface water intakes on the Ohio River. One intake is located at river mile 600.6 (Zorn Avenue). A second surface water intake is located above Herrods Creek at Mayfair Avenue and

Jacobs School Road. Both surface water intakes are located upstream from the facility (Refs. 22, 24). The LWC serves 208,500 residential, industrial, and commercial customers. The LWC also wholesales water to other systems, including Jeffersontown and the Indiana Water and Sewer Commission. These systems serve an additional 40,000 persons (Ref. 24).

There are private wells located within the LWC service area. These wells obtain water from the flood plain alluvium at depths ranging from 60-90 feet bls (Ref. 24). No private wells were located within 4 miles of the Kentucky Petroleum Waste, Inc. facility (Ref. 25). There are 3,758 residences within Jefferson County that are not connected to the municipal water system, 485 of which have access but have not obtained water connections (Ref. 26). The residents within 4 miles of Kentucky Petroleum Waste, Inc. obtain drinking water from the Louisville Water Company (Ref. 25).

Surface water drains from the northwestern corner of the Kentucky Petroleum Waste, Inc. facility and flows approximately 1500 feet in a northeastward direction in a roadside drainage ditch and enters Northern ditch. Water flows approximately 2.6 miles southwest along Northern ditch and enters Southern ditch. Water then flows approximately 1.9 miles along Southern ditch and enters Pond Creek. Water then flows another 10.2 miles southwest along Pond Creek. Northern ditch and Southern ditch are man-made drainage ditches for the area surrounding the Kentucky Petroleum Waste, Inc. facility (Ref. 21).

The ranges of several endangered species include Jefferson County. The endangered species are the gray bat (Myotis grisescens), Indiana bat (Myotis sodalis), eastern cougar (Felis concolor cougar), bald eagle (Haliaeetus leucocephalus), least tern (Sterna antillarum), Bachman's warbler (Vermivora bachmann), ivory-billed woodpecker (Campephilus principalis). The area is also a critical habitat for the Indiana bat (Myotis sodalis) (Ref. 27).

The Kentucky Petroleum Waste, Inc. facility is located in a commercial/industrial area of Louisville, Kentucky. During an offsite reconnaissance on April 19, 1990, the facility was active. The facility is completely fenced and access is controlled by locked gates on the south and west sides of the facility (Ref. 3). The nearest residence is approximately 1,300 feet east of the facility. There are no schools or day-care centers within 1 mile of the facility (Ref. 21). A house count, using a topographic map of the facility area, provided an estimate of population in the 0- to 1-mile radius. The population within 1 mile of the facility is 467 (123 houses X 3.8) (Refs. 21, 28). The population within 3 miles of the facility is 63,410 and the population within 4 miles of the facility is 122,977 (Ref. 29).

Based on the above results of this evaluation and the attached reference material, FIT 4 recommends no further remedial action be planned for the Kentucky Petroleum Waste, Inc. facility. If you have any comments or questions about this assessment, please contact me at NUS Corporation.

Very truly yours,

Wendell C. McLendon
Project Manager

Approved:

Greg Schank

WCM/jec

cc: Craig Benedikt

REFERENCES

1. Potential Hazardous Waste Site Preliminary Assessment (EPA Form 2070-12) and attachments for Kentucky Petroleum Products, filed by Jim Jarman, Kentucky Natural Resources and Environmental Protection Cabinet, Division of Waste Management, March 27, 1984.

2. NUS Corporation Field Logbook No. F4-2169 for Kentucky Petroleum Products, TDD No. F4-9001-115. Documentation of facility reconnaissance, April 19, 1990.

3. Wendell C. McLendon, NUS Corporation, memo to file for Kentucky Petroleum Products, November 1, 1990. Subject: Property ownership of facility and surrounding property.

4. Best Management Practices Plan for Kentucky Petroleum Waste, Inc., Petroleum Recycling Plant, Louisville, Kentucky, approved by C.R. Shircliff, plant manager.

5. Interim Status Hazardous Waste Facility Report, filed by K.L. Asher for Kentucky Natural Resources and Environmental Protection Cabinet, Division of Waste Management, July 7, 1986.

6. Permit application for transporting and handling of hazardous wastes, Commomwealth of Kentucky, Department of Natural Resources and Environmental Protection, Division of Hazardous Materials and Waste Management, filed by Leo Shircliff for Kentucky Petroleum Products, June 22, 1977.

7. Permit application for transporting and handling of hazardous wastes, Commomwealth of Kentucky, Department of Natural Resources and Environmental Protection, Division of Hazardous Materials and Waste Management, filed by Leo Shircliff for Kentucky Petroleum Products, November 21, 1977.

8. Notification of Hazardous Waste Activity (EPA Form 8700-12) for Kentucky Petroleum Waste, Inc., filed by James L. Shircliff, owner, January 29, 1986.

9. Certificate of Registration for hazardous waste activity for Kentucky Petroleum Waste, Inc., issued May 9, 1986, by Kentucky Division of Waste Management.

10. Certificate of Registration for hazardous waste management activity, Kentucky Natural Resources and Environmental Protection Cabinet, Department for Environmental Protection, Division of Waste Management, for Kentucky Petroleum Waste, Inc., expiration date January 31, 1991.

11. Christie Harrington, Kentucky Department of Hazardous Waste Permitting, telephone conversation with Wendell C. McLendon, NUS Corporation, December 17, 1990. Subject: Permit type and status for Kentucky Petroleum Waste, Inc.

12. Robert L. Sholar, Environmental Specialist I, Kentucky Department for Natural Resource and Environmental Protection, Division of Hazardous Materials and Waste Management, letter to Leo Shircliff, Kentucky Petroleum Products, March 27, 1987. Subject: Deposition of approximately 1,000 gallons of waste oil at Mobile Waste landfill.

13. William E. Davis, Director, Environmental Services, memorandum to Carl Horneman, Division of Waste Management, Frankfort, Kentucky, March 13, 1984. Subject: Report of analysis for samples from storage tanks at Kentucky Petroleum Waste, Inc., Louisville, Kentucky.

14. Commonwealth of Kentucky, Natural Resource and Environmental Protection Cabinet, Agreed Order WM87-059C for Kentucky Petroleum Waste, Inc., Louisville, Kentucky, KYD06-156-4001, filed October 3, 1988 by Division of Hearings.

15. L.M. MacCary, Availability of Groundwater for Domestic Use in Jefferson County, Kentucky, U.S. Geological Survey Hydrologic Investigations Atlas, HA-8 (Washington, D.C.: GPO 1966).

16. Linda Aller, et al., DRASTIC: A Standardized System for Evaluating Ground Water Pollution Potential Using Hydrogeologic Settings, EPA-600/2-87-035 (Ada,Oklahoma: EPA, April 1987).

17. U.S. Department of Commerce, Climatic Atlas of the United States, (Washington, D.C.: G.P.O., June, 1968) Reprint: 1983, National Oceanic and Atmospheric Administration, pp. 43,63.

18. U.S. Department of Commerce, Rainfall Frequency Atlas of the United States, Technical Paper No. 40, (Washington, D.C.: G.P.O., 1961), p. 93.

19. E.A. Bell, Summary of Hydrologic Conditions of the Louisville Area, Kentucky, U.S. Geological Survey Water Supply Paper 1819-C (Washington, D.C.: GPO 1966), pp.C4 - C18.

20. J.T.Gallaher and W.E. Price, Jr., Hydrology of the Alluvial Deposits in the Ohio River Valley in Kentucky, U.S. Geological Survey Water Supply Paper 1818 (Washington, D.C.: GPO 1966), p. 49.

21. R.A. Freeze, and J.A. Cherry, Groundwater, Englewood Cliffs, N.J.: Prentice-Hall, Inc. 1979, p.29.

22. U.S. Geological Survey, 7.5 minute series Topographic Quadrangle Maps of Kentucky : Brooks 1981 (Photorevised 1987), Louisville East 1982 (PR 1987), Louisville West 1983 (PR 1987), Valley Station 1982 (PR 1987). scale 1:24,000.

23. Mark Lyverse, U.S. Geological Survey, Louisville, Kentucky, telephone conversation with Carol Northern, NUS Corporation, May 2, 1988. Subject: Direction of groundwater flow.

24. John Huber, Louisville Water Company, telephone conversation with Carol Northern, NUS Corporation, July 13, 1988. Subject: Information on the Louisville Water Company.

25. Louisville Water Company, Distribution System Map; obtained from Jerry R. Ford, Louisville Water Company, July 26, 1990.

26. Charles Schott, Louisville Water Company, telephone conversation with Wendell C. McLendon, NUS Corporation, April 26, 1990. Subject: information on the number of customers served by the Louisville Water Company.

27. U.S. Fish and Wildlife Service, Endangered and Threatened Species of the Southeastern United States, (Atlanta, Georgia, 1988).

28. U.S. Bureau of the Census, Estimates of Households for Counties: July 1, 1985, Current Population Reports, Series P-23, No. 156 (Washington, D.C.: GPO, 1988).

29. U.S. EPA, Graphical Exposure Modeling System (GEMS) Data Base, compiled from U.S.Bureau of the Census (1980).

Site Inspection Report

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 1 - SITE LOCATION AND INSPECTION INFORMATION

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D061564001

II. SITE NAME AND LOCATION

01 SITE NAME (Legal, common or descriptive name of site)	02 STREET, ROUTE NO., OR SPECIFIC LOCATION IDENTIFIER
KENTUCKY PETROLEUM WASTE, INC.	6911 GRADE LANE

03 CITY	04 STATE	05 ZIP CODE	06 COUNTY	07 COUNTY CODE	08 CONG DIST
			JEFFERSON		

09 COORDINATES LATITUDE	LONGITUDE	10 TYPE OF OWNERSHIP (Check one)
38 08 52.0	085 44 08.0	☒ A. PRIVATE ☐ B. FEDERAL _____ ☐ C. STATE ☐ D. COUNTY ☐ E. MUNICIPAL ☐ F. OTHER _____ ☐ G. UNKNOWN

III. INSPECTION INFORMATION

01 DATE OF INSPECTION	02 SITE STATUS	03 YEARS OF OPERATION
04 18 90 (MONTH DAY YEAR)	☒ ACTIVE ☐ INACTIVE	1962 (BEGINNING YEAR) / PRESENT (ENDING YEAR) ___ UNKNOWN

04 AGENCY PERFORMING INSPECTION (Check all that apply)

☐ A. EPA ☒ B. EPA CONTRACTOR NUS CORPORATION (Name of firm) ☐ C. MUNICIPAL ☐ D. MUNICIPAL CONTRACTOR _____ (Name of firm)
☐ E. STATE ☐ F. STATE CONTRACTOR _____ (Name of firm) ☐ G. OTHER _____ (Specify)

05 CHIEF INSPECTOR	06 TITLE	07 ORGANIZATION	08 TELEPHONE NO
WENDELL C. MCKENDON	FIELD TECHNICIAN	NUS CORP	(404) 938-7710
09 OTHER INSPECTORS	10 TITLE	11 ORGANIZATION	12 TELEPHONE NO
STEPHANY FINE	GEOLOGIST	NUS CORP	(404) 938-7710
			( )
			( )
			( )
			( )

13 SITE REPRESENTATIVES INTERVIEWED	14 TITLE	15 ADDRESS	16 TELEPHONE NO
			( )
			( )
			( )
			( )
			( )
			( )

17 ACCESS GAINED BY (Check one)	18 TIME OF INSPECTION	19 WEATHER CONDITIONS
☐ PERMISSION ☐ WARRANT	1010	CLEAR AND COOL

IV. INFORMATION AVAILABLE FROM

01 CONTACT	02 OF (Agency/Organization)	03 TELEPHONE NO
CRAIG BENEDICT	EPA - REGION IV	(404) 347-5065

04 PERSON RESPONSIBLE FOR SITE INSPECTION FORM	05 AGENCY	06 ORGANIZATION	07 TELEPHONE NO.	08 DATE
WENDELL C. MCKENDON		NUS CORPORATION	(404) 938-7710	02/19/90 (MONTH DAY YEAR)

EPA FORM 2070-13 (7-81)

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 2 - WASTE INFORMATION

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156401

II. WASTE STATES, QUANTITIES, AND CHARACTERISTICS

01 PHYSICAL STATES (Check all that apply)

- A SOLID
- B POWDER, FINES
- C SLUDGE
- D OTHER _____ (Specify)
- E SLURRY
- ✓F LIQUID
- G GAS

02 WASTE QUANTITY AT SITE
(Measures of waste quantities must be independent)

- TONS _____
- CUBIC YARDS _____
- NO. OF DRUMS _____

03 WASTE CHARACTERISTICS (Check all that apply)

- A TOXIC
- B CORROSIVE
- C RADIOACTIVE
- ✓D PERSISTENT
- E SOLUBLE
- F INFECTIOUS
- ✓G FLAMMABLE
- H IGNITABLE
- I HIGHLY VOLATILE
- J EXPLOSIVE
- K REACTIVE
- L INCOMPATIBLE
- M NOT APPLICABLE

III. WASTE TYPE

CATEGORY	SUBSTANCE NAME	01 GROSS AMOUNT	02 UNIT OF MEASURE	03 COMMENTS
SLU	SLUDGE			
OLW	OILY WASTE	197,500	GALLONS	TOTAL CAPACITY OF TANKS AT FACILITY
SOL	SOLVENTS			
PSD	PESTICIDES			
OCC	OTHER ORGANIC CHEMICALS			
IOC	INORGANIC CHEMICALS			
ACD	ACIDS			
BAS	BASES			
MES	HEAVY METALS			

IV. HAZARDOUS SUBSTANCES (See Appendix for most frequently cited CAS Numbers)

01 CATEGORY	02 SUBSTANCE NAME	03 CAS NUMBER	04 STORAGE/DISPOSAL METHOD	05 CONCENTRATION	06 MEASURE OF CONCENTRATION

V. FEEDSTOCKS (See Appendix for CAS Numbers)

CATEGORY	01 FEEDSTOCK NAME	02 CAS NUMBER	CATEGORY	01 FEEDSTOCK NAME	02 CAS NUMBER
FDS			FDS		
FDS			FDS		
FDS			FDS		
FDS			FDS		

VI. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis, reports)

BEST MANAGEMENT PRACTICES PLAN FOR KENTUCKY PETROLEUM WASTE, INC.

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

I. IDENTIFICATION	
01 STATE	02 SITE NUMBER
KY	0061564001

II. HAZARDOUS CONDITIONS AND INCIDENTS

01 ☒ A. GROUNDWATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) — ☒ POTENTIAL — ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

SPILLS OF WASTE OILS COULD CONTAMINATE GROUNDWATER.

01 ☒ B. SURFACE WATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) — ☒ POTENTIAL — ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

SPILLS OF WASTE OILS AND FUELS COULD POSSIBLY CONTAMINATE SURFACE WATER DRAINAGE DITCHES.

01 ☒ C. CONTAMINATION OF AIR — 02 ☐ OBSERVED (DATE: _____) — ☐ POTENTIAL — ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

REMOTE POTENTIAL

01 ☒ D. FIRE/EXPLOSIVE CONDITIONS — 02 ☐ OBSERVED (DATE: _____) — ☒ POTENTIAL — ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

WASTE OILS AND FUELS ARE FLAMMABLE.

01 ☒ E. DIRECT CONTACT — 02 ☐ OBSERVED (DATE: _____) — ☒ POTENTIAL — ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

SPILLS OF WASTE OILS AND FUELS COULD COME IN DIRECT CONTACT WITH EMPLOYEES.

01 ☒ F. CONTAMINATION OF SOIL — 02 ☐ OBSERVED (DATE: _____) — ☒ POTENTIAL — ☐ ALLEGED
03 AREA POTENTIALLY AFFECTED: ≈ 1 (Acres) — 04 NARRATIVE DESCRIPTION

SPILLS OF WASTE OILS AND FUELS COULD CONTAMINATE SOILS

01 ☒ G. DRINKING WATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) — ☐ POTENTIAL — ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

THERE ARE NO SURFACE WATER INTAKES ALONG DRAINAGE PATHWAY.

01 ☒ H. WORKER EXPOSURE/INJURY — 02 ☐ OBSERVED (DATE: _____) — ☒ POTENTIAL — ☐ ALLEGED
03 WORKERS POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

SPILLS COULD CAUSE EMPLOYEES TO COME IN DIRECT CONTACT WITH WASTE OIL AND FUEL.

01 ☐ I. POPULATION EXPOSURE/INJURY — 02 ☐ OBSERVED (DATE: _____) — ☐ POTENTIAL — ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ — 04 NARRATIVE DESCRIPTION

REMOTE POTENTIAL. EMPLOYEES COULD COME IN DIRECT CONTACT WITH WASTE OILS AND FUELS.

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156601

II. HAZARDOUS CONDITIONS AND INCIDENTS (Continued)

01 ☐ J. DAMAGE TO FLORA — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION
NONE NOTED

01 ☐ K. DAMAGE TO FAUNA — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION (Include names of species)
NONE REPORTED

01 ☐ L. CONTAMINATION OF FOOD CHAIN — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION
NONE REPORTED

01 ☐ M. UNSTABLE CONTAINMENT OF WASTES (Spills, Runoff, Standing liquids, Leaking drums) — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION
TANKS HAVE CONTAINMENT DIKES.

01 ☐ N. DAMAGE TO OFFSITE PROPERTY — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION
THE SITE IS BORDERED BY STREETS AND VACANT LOTS.

01 ☒ O. CONTAMINATION OF SEWERS, STORM DRAINS, WWTPs — 02 ☐ OBSERVED (DATE: _____) ☒ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION
SPILLS OF USED OILS AND FUELS COULD CONTAMINATE DRAINAGE DITCHES.

01 ☒ P. ILLEGAL/UNAUTHORIZED DUMPING — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION
NONE REPORTED

05 DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL, OR ALLEGED HAZARDS
NONE REPORTED.

III. TOTAL POPULATION POTENTIALLY AFFECTED: _____

IV. COMMENTS

V. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis, reports)
STATE AND EPA FILE MATERIAL

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION
PART 4 - PERMIT AND DESCRIPTIVE INFORMATION

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156401

II. PERMIT INFORMATION

01 TYPE OF PERMIT ISSUED (Check all that apply)	02 PERMIT NUMBER	03 DATE ISSUED	04 EXPIRATION DATE	05 COMMENTS
☐ A. NPDES				
☐ B. UIC				
☐ C. AIR				
☐ D. RCRA				
☐ E. RCRA INTERIM STATUS				
☐ F. SPCC PLAN				
☐ G. STATE (Specify)				
☐ H. LOCAL (Specify)				
☐ I. OTHER (Specify)				
☐ J. NONE				

III. SITE DESCRIPTION

01 STORAGE/DISPOSAL (Check all that apply)	02 AMOUNT	03 UNIT OF MEASURE
☐ A. SURFACE IMPOUNDMENT		
☐ B. PILES		
☐ C. DRUMS, ABOVE GROUND		
☒ D. TANK, ABOVE GROUND	197,500	GALLONS
☐ E. TANK, BELOW GROUND		
☐ F. LANDFILL		
☐ G. LANDFARM		
☐ H. OPEN DUMP		
☐ I. OTHER (Specify)		

04 TREATMENT (Check all that apply)

- ☐ A. INCENERATION
- ☐ B. UNDERGROUND INJECTION
- ☐ C. CHEMICAL/PHYSICAL
- ☐ D. BIOLOGICAL
- ☐ E. WASTE OIL PROCESSING
- ☐ F. SOLVENT RECOVERY
- ☐ G. OTHER RECYCLING/RECOVERY
- ☐ H. OTHER _____ (Specify)

05 OTHER

☒ A. BUILDINGS ON SITE

1

06 AREA OF SITE

≈ 1 Acres

07 COMMENTS

IV. CONTAINMENT

01 CONTAINMENT OF WASTES (Check one)

☒ A. ADEQUATE, SECURE ☐ B. MODERATE ☐ C. INADEQUATE, POOR ☐ D. INSECURE, UNSOUND, DANGEROUS

02 DESCRIPTION OF DRUMS, DIKING, LINERS, BARRIERS, ETC.

TANKS HAVE CONTAINMENT DIKES.

V. ACCESSIBILITY

01 WASTE EASILY ACCESSIBLE ☐ YES ☒ NO

02 COMMENTS

FACILITY IS FENCED.

VI. SOURCES OF INFORMATION (Cite specific references, e.g. state files, sample analysis, reports.)

STATE, EPA FILE MATERIAL

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 5 - WATER, DEMOGRAPHIC, AND ENVIRONMENTAL DATA

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	KD061564001

II. DRINKING WATER SUPPLY

01 TYPE OF DRINKING SUPPLY (Check as applicable)	SURFACE	WELL	02 STATUS	ENDANGERED	AFFECTED	MONITORED	03 DISTANCE TO SITE
COMMUNITY	A. ☒	B. ☐		A. ☐	B. ☐	C. ☐	A. UPGRADIENT (mi)
NON-COMMUNITY	C. ☒	D. ☐		D. ☐	E. ☐	F. ☐	B. UPGRADIENT (mi)

III. GROUNDWATER

01 GROUNDWATER USE IN VICINITY (Check one)

☐ A. ONLY SOURCE FOR DRINKING ☐ B. DRINKING (Other sources available) COMMERCIAL, INDUSTRIAL, IRRIGATION (No other water sources available) ☐ C. COMMERCIAL, INDUSTRIAL, IRRIGATION (Limited other sources available) ☒ D. NOT USED, UNUSEABLE

02 POPULATION SERVED BY GROUND WATER	03 DISTANCE TO NEAREST DRINKING WATER WELL
NONE	(mi)

04 DEPTH TO GROUNDWATER	05 DIRECTION OF GROUNDWATER FLOW	06 DEPTH TO AQUIFER OF CONCERN	07 POTENTIAL YIELD OF AQUIFER	08 SOLE SOURCE AQUIFER
5-10 (ft)	SW	X (ft)	(gpd)	☐ YES ☒ NO

09 DESCRIPTION OF WELLS (Including useage, depth, and location relative to population and buildings)

THERE ARE NO WELLS WITHIN 4 MILES OF THE FACILITY.

10 RECHARGE AREA		11 DISCHARGE AREA	
☐ YES ☐ NO	COMMENTS	☐ YES ☐ NO	COMMENTS

IV. SURFACE WATER

01 SURFACE WATER USE (Check one)

☐ A. RESERVOIR, RECREATION DRINKING WATER SOURCE ☐ B. IRRIGATION, ECONOMICALLY IMPORTANT RESOURCES ☐ C. COMMERCIAL, INDUSTRIAL ☒ D. NOT CURRENTLY USED

02 AFFECTED/POTENTIALLY AFFECTED BODIES OF WATER

NAME:	AFFECTED	DISTANCE TO SITE
POND CREEK	☐	4.9 (mi)
	☐	(mi)
	☐	(mi)

V. DEMOGRAPHIC AND PROPERTY INFORMATION

01 TOTAL POPULATION WITHIN			02 DISTANCE TO NEAREST POPULATION
ONE (1) MILE OF SITE	TWO (2) MILES OF SITE	THREE (3) MILES OF SITE	
A. 462 NO. OF PERSONS	B. 20,326 NO. OF PERSONS	C. 63,410 NO. OF PERSONS	0.2 (mi)

03 NUMBER OF BUILDINGS WITHIN TWO (2) MILES OF SITE	04 DISTANCE TO NEAREST OFF-SITE BUILDING
	<0.1 (mi)

05 POPULATION WITHIN VICINITY OF SITE (Provide narrative description of nature of population within vicinity of site, e.g., rural, village, densely populated urban area)

THE FACILITY IS IN A COMMERCIAL/INDUSTRIAL AREA IN LOUISVILLE, KY. POPULATION INCREASES RAPIDLY BETWEEN 1 & 2 MILES AND BETWEEN 2 & 3 MILES OF THE FACILITY

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 5 - WATER, DEMOGRAPHIC, AND ENVIRONMENTAL DATA

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	0061564001

VI. ENVIRONMENTAL INFORMATION

01 PERMEABILITY OF UNSATURATED ZONE (Check one)

☒ A. 10^{-6} – 10^{-8} cm/sec ☐ B. 10^{-4} – 10^{-6} cm/sec ☐ C. 10^{-4} – 10^{-3} cm/sec ☐ D. GREATER THAN 10^{-3} cm/sec

02 PERMEABILITY OF BEDROCK (Check one)

☐ A. IMPERMEABLE (Less than 10^{-6} cm/sec) ☒ B. RELATIVELY IMPERMEABLE (10^{-4} – 10^{-6} cm/sec) ☐ C. RELATIVELY PERMEABLE (10^{-2} – 10^{-4} cm/sec) ☐ D. VERY PERMEABLE (Greater than 10^{-2} cm/sec)

03 DEPTH TO BEDROCK	04 DEPTH OF CONTAMINATED SOIL ZONE	05 SOIL pH	
up to 130 (ft)	6? (ft)		

06 NET PRECIPITATION	07 ONE YEAR 24 HOUR RAINFALL	08 SLOPE		
		SITE SLOPE	DIRECTION OF SITE SLOPE	TERRAIN AVERAGE SLOPE
9 (in)	2.8 (in)	1 %	NW	1 %

09 FLOOD POTENTIAL

SITE IS IN _____ YEAR FLOODPLAIN

10

☐ SITE IS ON BARRIER ISLAND, COASTAL HIGH HAZARD AREA, RIVERINE FLOODWAY

11 DISTANCE TO WETLANDS (5 acre minimum)

ESTUARINE	OTHER
A. X (mi)	B. X (mi)

12 DISTANCE TO CRITICAL HABITAT (of endangered species)

_____ (mi)

ENDANGERED SPECIES: _____

13 LAND USE IN VICINITY

DISTANCE TO:

COMMERCIAL/INDUSTRIAL	RESIDENTIAL AREAS; NATIONAL/STATE PARKS, FORESTS, OR WILDLIFE RESERVES	AGRICULTURAL LANDS	
		PRIME AG LAND	AG LAND
A. < 0.1 (mi)	B. > 1 (mi)	C. _____ (mi)	D. _____ (mi)

14 DESCRIPTION OF SITE IN RELATION TO SURROUNDING TOPOGRAPHY

THE FACILITY IS IN A COMMERCIAL/INDUSTRIAL AREA OF LOUISVILLE, KY.

VII. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis, reports)

STATE, EPA, NUS FILES

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 6 - SAMPLE AND FIELD INFORMATION

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156401

II. SAMPLES TAKEN

SAMPLE TYPE	01 NUMBER OF SAMPLES TAKEN	02 SAMPLES SENT TO	03 ESTIMATED DATE RESULTS AVAILABLE
GROUNDWATER			
SURFACE WATER			
WASTE OIL	13	ENVIRONMENTAL SERVICES, FRANKFORT, Ky	3/13/84
AIR			
RUNOFF			
SPILL			
SOIL			
VEGETATION			
OTHER			

III. FIELD MEASUREMENTS TAKEN

01 TYPE	02 COMMENTS
NOT DOCUMENTED	

IV. PHOTOGRAPHS AND MAPS

01 TYPE ☒ GROUND ☐ AERIAL

02 IN CUSTODY OF NUS CORPORATION FILES
(Name of organization or individual)

03 MAPS ☒ YES ☐ NO

04 LOCATION OF MAPS NUS CORPORATION FILES.

V. OTHER FIELD DATA COLLECTED (Provide narrative description)

VI. SOURCES OF INFORMATION (Cite specific references, e.g. State files, sample analysis, reports)

EPA AND STATE FILE MATERIAL

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 7 - OWNER INFORMATION

I. IDENTIFICATION	
01 STATE	02 SITE NUMBER
KY	D061564001

II. CURRENT OWNER(S)

01 NAME	02 D+B NUMBER	08 NAME (PARENT COMPANY (If applicable))	09 D+B NUMBER
LEO J. SHIRCLIFF		N/A	

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	10 STREET ADDRESS (P.O. Box, RFD #, etc.)	11 SIC CODE
4019 BLANTON LANE (?)			

05 CITY	06 STATE	07 ZIP CODE	12 CITY	13 STATE	14 ZIP CODE
LOUISVILLE	KY				

01 NAME	02 D+B NUMBER	08 NAME	09 D+B NUMBER

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	10 STREET ADDRESS (P.O. Box, RFD #, etc.)	11 SIC CODE

05 CITY	06 STATE	07 ZIP CODE	12 CITY	13 STATE	14 ZIP CODE

01 NAME	02 D+B NUMBER	08 NAME	09 D+B NUMBER

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	10 STREET ADDRESS (P.O. Box, RFD #, etc.)	11 SIC CODE

05 CITY	06 STATE	07 ZIP CODE	12 CITY	13 STATE	14 ZIP CODE

01 NAME	02 D+B NUMBER	08 NAME	09 D+B NUMBER

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	10 STREET ADDRESS (P.O. Box, RFD #, etc.)	11 SIC CODE

05 CITY	06 STATE	07 ZIP CODE	12 CITY	13 STATE	14 ZIP CODE

III. PREVIOUS OWNER(S) (List most recent first) / IV. REALTY OWNER(S) (If applicable; list most recent first)

01 NAME	02 D+B NUMBER	01 NAME	02 D+B NUMBER
N/A		N/A	

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE

05 CITY	06 STATE	07 ZIP CODE	05 CITY	06 STATE	07 ZIP CODE

01 NAME	02 D+B NUMBER	01 NAME	02 D+B NUMBER

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE

05 CITY	06 STATE	07 ZIP CODE	05 CITY	06 STATE	07 ZIP CODE

01 NAME	02 D+B NUMBER	01 NAME	02 D+B NUMBER

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE

05 CITY	06 STATE	07 ZIP CODE	05 CITY	06 STATE	07 ZIP CODE

V. SOURCES OF INFORMATION (Cite specific references, e.g. state files, sample analysis, reports)

STATE & EPA FILE MATERIAL

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 8 - OPERATOR INFORMATION

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156401

II. CURRENT OPERATOR (Provide if different from owner)

01 NAME	02 D+B NUMBER
LEO J. SHARCLIFF	

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE

05 CITY	06 STATE	07 ZIP CODE
LOUISVILLE	KY	40216

08 YEARS OF OPERATION	09 NAME OF OWNER

OPERATOR'S PARENT COMPANY (If applicable)

10 NAME	11 D+B NUMBER
N/A	

12 STREET ADDRESS (P.O. Box, RFD #, etc.)	13 SIC CODE

14 CITY	15 STATE	16 ZIP CODE

III. PREVIOUS OPERATOR(S) (List most recent first; provide only if different from owner)

01 NAME	02 D+B NUMBER
N/A	

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE

05 CITY	06 STATE	07 ZIP CODE

08 YEARS OF OPERATION	09 NAME OF OWNER DURING THIS PERIOD

PREVIOUS OPERATORS' PARENT COMPANIES (If applicable)

10 NAME	11 D+B NUMBER
N/A	

12 STREET ADDRESS (P.O. Box, RFD #, etc.)	13 SIC CODE

14 CITY	15 STATE	16 ZIP CODE

01 NAME	02 D+B NUMBER

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE

05 CITY	06 STATE	07 ZIP CODE

08 YEARS OF OPERATION	09 NAME OF OWNER DURING THIS PERIOD

10 NAME	11 D+B NUMBER

12 STREET ADDRESS (P.O. Box, RFD #, etc.)	13 SIC CODE

14 CITY	15 STATE	16 ZIP CODE

01 NAME	02 D+B NUMBER

03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE

05 CITY	06 STATE	07 ZIP CODE

08 YEARS OF OPERATION	09 NAME OF OWNER DURING THIS PERIOD

10 NAME	11 D+B NUMBER

12 STREET ADDRESS (P.O. Box, RFD #, etc.)	13 SIC CODE

14 CITY	15 STATE	16 ZIP CODE

IV. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis, reports)

STATE & EPA FILE MATERIAL

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 9 - GENERATOR/TRANSPORTER INFORMATION

I. IDENTIFICATION	
01 STATE	02 SITE NUMBER
KY	D061564001

II. ON-SITE GENERATOR

01 NAME	02 D+B NUMBER
N/A	
03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE
05 CITY	06 STATE / 07 ZIP CODE

III. OFF-SITE GENERATOR(S)

01 NAME	02 D+B NUMBER	01 NAME	02 D+B NUMBER
N/A			
03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE
05 CITY	06 STATE / 07 ZIP CODE	05 CITY	06 STATE / 07 ZIP CODE
01 NAME	02 D+B NUMBER	01 NAME	02 D+B NUMBER
03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE
05 CITY	06 STATE / 07 ZIP CODE	05 CITY	06 STATE / 07 ZIP CODE

IV. TRANSPORTER(S)

01 NAME	02 D+B NUMBER	01 NAME	02 D+B NUMBER
N/A			
03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE
05 CITY	06 STATE / 07 ZIP CODE	05 CITY	06 STATE / 07 ZIP CODE
01 NAME	02 D+B NUMBER	01 NAME	02 D+B NUMBER
03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE	03 STREET ADDRESS (P.O. Box, RFD #, etc.)	04 SIC CODE
05 CITY	06 STATE / 07 ZIP CODE	05 CITY	06 STATE / 07 ZIP CODE

V. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis, reports)

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 10 - PAST RESPONSE ACTIVITIES

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156401

II. PAST RESPONSE ACTIVITIES

01 ☐ A. WATER SUPPLY CLOSED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ B. TEMPORARY WATER SUPPLY PROVIDED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ C. PERMANENT WATER SUPPLY PROVIDED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ D. SPILLED MATERIAL REMOVED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ E. CONTAMINATED SOIL REMOVED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ F. WASTE REPACKAGED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
unknown

01 ☐ G. WASTE DISPOSED ELSEWHERE — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
unknown

01 ☐ H. ON SITE BURIAL — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ I. IN SITU CHEMICAL TREATMENT — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ J. IN SITU BIOLOGICAL TREATMENT — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION

01 ☐ K. IN SITU PHYSICAL TREATMENT — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ L. ENCAPSULATION — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ M. EMERGENCY WASTE TREATMENT — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
unknown

01 ☐ N. CUTOFF WALLS — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ O. EMERGENCY DIKING SURFACE WATER DIVERSION — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ P. CUTOFF TRENCHES/SUMP — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ Q. SUBSURFACE CUTOFF WALL — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 10 - PAST RESPONSE ACTIVITIES

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D0615640 01

II PAST RESPONSE ACTIVITIES (Continued)

01 ☐ R. BARRIER WALLS CONSTRUCTED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ S. CAPPING/COVERING — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ T. BULK TANKAGE REPAIRED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
UNKNOWN

01 ☐ U. GROUT CURTAIN CONSTRUCTED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ V. BOTTOM SEALED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ W. GAS CONTROL — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ X. FIRE CONTROL — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ Y. LEACHATE TREATMENT — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ Z. AREA EVACUATED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
UNKNOWN

01 ☐ 1. ACCESS TO SITE RESTRICTED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
UNKNOWN

01 ☐ 2. POPULATION RELOCATED — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

01 ☐ 3. OTHER REMEDIAL ACTIVITIES — 02 DATE _____ — 03 AGENCY _____
04 DESCRIPTION
N/A

III. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis reports)

EPA AND STATE FILE MATERIAL

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT
PART 11 - ENFORCEMENT INFORMATION

I. IDENTIFICATION	
01 STATE	02 SITE NUMBER
KY	0061569001

II. ENFORCEMENT INFORMATION

01 PAST REGULATORY ENFORCEMENT ACTION ✓ YES NO

02 DESCRIPTION OF FEDERAL STATE ✓ LOCAL REGULATORY ENFORCEMENT ACTION

In March 1978, Kentucky Petroleum Products deposited approximately 1000 gallons of waste oil at Mobile Waste Landfill.

In October 1988, Kentucky Natural Resources and Environmental Protection Cabinet filed an Agreed Order stating that Ky. Petroleum Products was in violation of several standards applicable to used fuel oil marketers and burners.

III. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis reports)

EPA & State file material

EPA FORM 2070-13 (7-81)

HAZARD RANKING SYSTEM SCORING SUMMARY

FOR

KENTUCKY PETROLEUM PRODUCTS
EPA SITE NUMBER KYD061564001
LOUISVILLE
JEFFERSON COUNTY, KY
EPA REGION: 4

SCORE STATUS: IN PREPARATION

SCORED BY W. MCLENDON
OF NUS CORPORATION
ON 01/29/91

DATE OF THIS REPORT: 01/29/91
DATE OF LAST MODIFICATION: 01/29/91

GROUND WATER ROUTE SCORE	:	3.39
SURFACE WATER ROUTE SCORE	:	6.80
AIR ROUTE SCORE	:	0.00
MIGRATION SCORE	:	4.39

HRS GROUND WATER ROUTE SCORE

CATEGORY/FACTOR	RAW DATA	ASN. VALUE	SCORE
1. OBSERVED RELEASE	NO	0	0
2. ROUTE CHARACTERISTICS			
DEPTH TO WATER TABLE	10 FEET		
DEPTH TO BOTTOM OF WASTE	6 FEET		
DEPTH TO AQUIFER OF CONCERN	4 FEET	3	6
PRECIPITATION	44.0 INCHES		
EVAPORATION	35.0 INCHES		
NET PRECIPITATION	9.0 INCHES	2	2
PERMEABILITY	1.0X10-6 CM/SEC	1	1
PHYSICAL STATE		3	3
TOTAL ROUTE CHARACTERISTICS SCORE:			12
3. CONTAINMENT		3	3
4. WASTE CHARACTERISTICS			
TOXICITY/PERSISTENCE:TRICHLOROETHENE			12
WASTE QUANTITY CUBIC YDS	0		
DRUMS	0		
GALLONS	197500		
TONS	0		
TOTAL	988 CU. YDS	6	6
TOTAL WASTE CHARACTERISTICS SCORE:			18
5. TARGETS			
GROUND WATER USE		1	3
DISTANCE TO NEAREST WELL	> 3 MILES		
AND	MATRIX VALUE	0	0
TOTAL POPULATION SERVED	0 PERSONS		
NUMBER OF HOUSES	0		
NUMBER OF PERSONS	0		
NUMBER OF CONNECTIONS	0		
NUMBER OF IRRIGATED ACRES	0		
TOTAL TARGETS SCORE:			3

GROUND WATER ROUTE SCORE (Sgw) = 3.39

HRS SURFACE WATER ROUTE SCORE

CATEGORY/FACTOR	RAW DATA	ASN. VALUE	SCORE
1. OBSERVED RELEASE	NO	0	0
2. ROUTE CHARACTERISTICS			
SITE LOCATED IN SURFACE WATER	NO		
SITE WITHIN CLOSED BASIN	NO		
FACILITY SLOPE	1.0 %		
INTERVENING SLOPE	1.0 %	0	0
24-HOUR RAINFALL	2.8 INCHES	2	2
DISTANCE TO DOWN-SLOPE WATER	1500 FEET	2	4
PHYSICAL STATE	3		3
TOTAL ROUTE CHARACTERISTICS SCORE:			9
3. CONTAINMENT	3		3
4. WASTE CHARACTERISTICS			
TOXICITY/PERSISTENCE: TRICHLOROETHENE			12
WASTE QUANTITY CUBIC YDS	0		
DRUMS	0		
GALLONS	197500		
TONS	0		
TOTAL	988 CU. YDS	6	6
TOTAL WASTE CHARACTERISTICS SCORE:			18
5. TARGETS			
SURFACE WATER USE		3	9
DISTANCE TO SENSITIVE ENVIRONMENTS		0	0
COASTAL WETLANDS	NONE		
FRESH-WATER WETLANDS	NONE		
CRITICAL HABITAT	NONE		
DISTANCE TO STATIC WATER	> 3 MILES		
DISTANCE TO WATER SUPPLY INTAKE	> 3 MILES		
AND	MATRIX VALUE	0	0
TOTAL POPULATION SERVED	0		
NUMBER OF HOUSES	0		
NUMBER OF PERSONS	0		
NUMBER OF CONNECTIONS	0		
NUMBER OF IRRIGATED ACRES	0		
TOTAL TARGETS SCORE:			9

SURFACE WATER ROUTE SCORE (Ssw) = 6.80

HRS AIR ROUTE SCORE

CATEGORY/FACTOR	RAW DATA	ASN. VALUE	SCORE
1. OBSERVED RELEASE	NO	0	0
2. WASTE CHARACTERISTICS			
REACTIVITY:		MATRIX VALUE	
INCOMPATIBILITY			
TOXICITY			
WASTE QUANTITY CUBIC YARDS			
DRUMS			
GALLONS			
TONS			
TOTAL			
TOTAL WASTE CHARACTERISTICS SCORE:			N/A
3. TARGETS			
POPULATION WITHIN 4-MILE RADIUS			
0 to 0.25 mile			
0 to 0.50 mile			
0 to 1.0 mile			
0 to 4.0 miles			
DISTANCE TO SENSITIVE ENVIRONMENTS			
COASTAL WETLANDS			
FRESH-WATER WETLANDS			
CRITICAL HABITAT			
DISTANCE TO LAND USES			
COMMERCIAL/INDUSTRIAL			
PARK/FOREST/RESIDENTIAL			
AGRICULTURAL LAND			
PRIME FARMLAND			
HISTORIC SITE WITHIN VIEW?			
TOTAL TARGETS SCORE:			N/A

AIR ROUTE SCORE (Sa) = 0.00

HAZARD RANKING SYSTEM SCORING CALCULATIONS
FOR
SITE: KENTUCKY PETROLEUM PRODUCTS
AS OF 01/29/91

GROUND WATER ROUTE SCORE

ROUTE CHARACTERISTICS		12
CONTAINMENT	X	3
WASTE CHARACTERISTICS	X	18
TARGETS	X	3
	=	1944 /57,330 X 100 = 3.39 = S_{gw}

SURFACE WATER ROUTE SCORE

ROUTE CHARACTERISTICS		9
CONTAINMENT	X	3
WASTE CHARACTERISTICS	X	18
TARGETS	X	9
	=	4374 /64,350 X 100 = 6.80 = S_{sw}

AIR ROUTE SCORE

OBSERVED RELEASE 0 /35,100 X 100 = 0.00 = S_{air}

SUMMARY OF MIGRATION SCORE CALCULATIONS

	S	S^2
GROUND WATER ROUTE SCORE (S_{gw})	3.39	11.49
SURFACE WATER ROUTE SCORE (S_{sw})	6.80	46.24
AIR ROUTE SCORE (S_{air})	0.00	0.00
$S^2_{gw} + S^2_{sw} + S^2_{air}$		57.73
$\sqrt{(S^2_{gw} + S^2_{sw} + S^2_{air})}$		7.60
$S_M = \sqrt{(S^2_{gw} + S^2_{sw} + S^2_{air})}/1.73$		4.39

CERCLA ELIGIBILITY QUESTIONNAIRE

Site Name: KENTUCKY PETROLEUM PRODUCTS

City: LOUISVILLE State: KY

EPA ID Number: KYD061564001

I. CERCLA ELIGIBILITY	Yes	No
Did the facility cease operations prior to November 19, 1980?	___	X
If answer YES, STOP, facility is probably a CERCLA site.		
If answer NO, Continue to Part II.		

II. RCRA ELIGIBILITY	Yes	No
Did the facility file a RCRA Part A application?	___	X
If YES:		
1. Does the facility currently have interim status?	___	___
2. Did the facility withdraw its Part A application?	___	___
3. Is the facility a known or possible protective filer? (facility filed in error)	___	___
4. Type of facility: Generator_____ Transporter_____ Recycler_____ TSD (Treatment/Storage/Disposal)_____		
Does the facility have a RCRA operating or post closure permit?	___	X
Is the facility a late (after 11/19/80) or non-filer that has been identified by the EPA or the State? (facility did not know it needed to file under RCRA)	___	X
If all answers to questions in Part II are NO, STOP, the facility is a CERCLA eligible site.		
If answer to #2 or #3 is YES, STOP, the facility is a CERCLA eligible site.		
If answer #2 and #3 are NO and any OTHER answer is YES, site is RCRA, continue to Part III.		

III. RCRA SITES ELIGIBLE FOR NPL	Yes	No
Has the facility owner filed for bankruptcy under federal or state laws?	___	___
Has the facility lost RCRA authorization to operate or shown probable unwillingness to carry out corrective action?	___	___
Is the facility a TSD that converted to a generator, transporter or recycler facility after November 19, 1980?	___	___

SSI PHASE I
RECONNAISSANCE DOCUMENTATION CHECKLIST

This information is required for all SSI Phase Is. Much of it will be detailed in your letter report, logbook, or topo map. In such cases, provide only brief descriptions and reference citations on the checklist to avoid duplication. Cite the source for all information obtained for all sections. Lists of HRS-specific definitions and sensitive environment identifications are attached.

Site Name: Kentucky Petroleum Products

City, County, State: Louisville, Jefferson County, Kentucky

EPA ID No.: KYD061564001

Person responsible for form: Wendell C. McLendon

Date: 12/19/90

DESKTOP DATA COLLECTION
(Can be done before or after recon. Include attachments as necessary).

I. **Groundwater Use** (See project geologist for this information)

- Identify aquifer(s) of concern.

  The alluvium in the Ohio River Flood Plain.

- Identify any areas of karst terrain within the 4-mile site radius, and confining layers and hydraulic interconnections within 2 miles of the site.

  None.

II. **Surface Water Use**

- Identify uses along the 15-stream-mile surface water pathway (i.e. drinking water, fishing, irrigation, industrial).

  There are no surface water intakes along the 15-mile surface water pathway.

- Identify any designated recreational areas, sensitive environments, and fisheries along the surface water pathway. Specify whether fishing is recreational, subsistence, or commercial. Information for smaller water bodies can be confirmed or obtained from local sources during the recon.

  There are no designated recreational areas or sensitive environments along the surface water pathway.

III. **Sensitive Environments**

- Identify any sensitive environments within 4 radial miles of the site (See Table 4-23 of the February 15, 1990 HRS Draft Final Rule, attached). Remember, sensitive environments are not limited to critical habitats.

DRIVE-BY RECONNAISSANCE DATA COLLECTION
(This information should be recorded in logbooks with attachments).

I. **Groundwater Use** (This information can generally be obtained from local water departments, or city hall in rural areas).

- Identify on copies of topos the extent of all municipal systems and areas served by private wells within 4 miles of the site.

  Copies of the area served by the Louisville Water Company are located in files.

- Locate on copies of topos all municipal well locations in the site area, including any wells of a blended system >4 miles from site. Specify if water from these wells is partially or fully blended prior to or during distribution, and if any surface water intakes contribute to a blended system (whether or not they draw from the target sw pathway).

  No municipal wells were located.

- Note the depth, pumpage, and population served for all municipal wells within the 4-mile site radius. Complete well survey forms.

- Document other groundwater uses (e.g. irrigation, industrial).

  There are no industrial wells within 4 miles of the facility.

II. **Surface Water Use**

- Identify on topos the 15-mile surface water pathway.

- Identify and locate on topos any surface water intakes within 15 miles downstream of the site (to be obtained from local water department).

  No surface water intakes are located within 15 miles downstream of the facility.

III. **Site and Area Use Data Collection** (May be obtained before or during recon)

- Describe any barriers to travel (e.g. rivers) within 1 mile of the site (consult topo).

  There are no rivers or other barriers to travel within 1 mile of the facility.

- Describe population within the immediate site vicinity and within the 4-mile radius (e.g. sparsely populated rural areas, commercial/industrial areas, densely populated urban areas, etc.).

  The facility is in an industrial/commercial area, the population within 3 miles is 63,410 and within 4 miles is 122,977. The population within a 1-mile radius is estimated at be 467.

- Obtain aerial photos of site and immediate vicinity whenever available (from county offices).

  No aerial photos were obtained.

- Note if the facility is on sewers or septic tanks (consult water or public works department).

- Obtain current property owner information from the county tax assessor's office.

  See Project Note to Kentucky Petroleum Products.

REFERENCE # 1

MEMORANDUM

TO: Barry Burrus, Chief
Uncontrolled Sites Section

FROM: Jim Jarman, Geologist
Uncontrolled Sites Section

DATE: March 27, 1984

SUBJECT: Preliminary Assessment Report for Kentucky Petroleum Products - Jefferson County

Kentucky Petroleum Products is a waste oil recycler that operates several tank trucks which collect waste oil and delivers it to a small storage facility (about 15 tanks). The waste oil is stored and later sold to various companies that either refine it into petroleum products, place it in a waste oil fuel program, or burn it as a waste oil fuel. The firm is now known as Kentucky Petroleum Wastes, Inc.

Presently, the site is being handled by the Enforcement Branch of the Kentucky Division of Waste Management. Numerous violations have been documented by field personnel. A preliminary assessment and site inspection completed in 1980 did not designate any action to be taken. Tank waste oil samples taken in February 1984 indicate high levels of trichloroethylene to be present.

After reviewing the information within the division and talking with enforcement personnel, I am recommending this site be given a low priority ranking for a site inspection. The presence of trichloroethylene in these storage tanks could present an environmental problem if the contents are released.

JJ:da

cc: John Brooks
Millie Archer
EPA-Atlanta
File

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 1 - SITE INFORMATION AND ASSESSMENT

EPA

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D061564001

II. SITE NAME AND LOCATION

01 SITE NAME (Legal, common, or descriptive name of site)	02 STREET, ROUTE NO., OR SPECIFIC LOCATION IDENTIFIER
Kentucky Petroleum Products	4019 Blanton Lane

03 CITY	04 STATE	05 ZIP CODE	06 COUNTY	07 COUNTY CODE	08 CONG DIST
Louisville	KY	40216	Jefferson	056	

09 COORDINATES LATITUDE	LONGITUDE
38°08'50.0	085°44'15.0

10 DIRECTIONS TO SITE (Starting from nearest public road)
Facility Location is intersection Knopp avenue & Grade Lane - storage tanks

III. RESPONSIBLE PARTIES

01 OWNER (If known)	02 STREET (Business, mailing, residential)
Kentucky Petroleum Products	4019 Blanton Lane

03 CITY	04 STATE	05 ZIP CODE	06 TELEPHONE NUMBER
Louisville	KY	40216	(502) 447-1802

07 OPERATOR (If known and different from owner)	08 STREET (Business, mailing, residential)
SAME	

09 CITY	10 STATE	11 ZIP CODE	12 TELEPHONE NUMBER
			( )

13 TYPE OF OWNERSHIP (Check one)
☒ A. PRIVATE ☐ B. FEDERAL: _____ (Agency name) ☐ C. STATE ☐ D. COUNTY ☐ E. MUNICIPAL
☐ F. OTHER: _____ (Specify) ☐ G. UNKNOWN

14 OWNER/OPERATOR NOTIFICATION ON FILE (Check all that apply)
☐ A. RCRA 3001 DATE RECEIVED: ___/___/___ (MONTH DAY YEAR) ☐ B. UNCONTROLLED WASTE SITE (CERCLA 103 c) DATE RECEIVED: ___/___/___ (MONTH DAY YEAR) ☒ C. NONE

IV. CHARACTERIZATION OF POTENTIAL HAZARD

01 ON SITE INSPECTION
☒ YES ☐ NO DATE 02/29/84 (MONTH DAY YEAR)

BY (Check all that apply)
☐ A. EPA ☐ B. EPA CONTRACTOR ☐ C. STATE ☐ D. OTHER CONTRACTOR
☐ E. LOCAL HEALTH OFFICIAL ☐ F. OTHER: _____ (Specify)
CONTRACTOR NAME(S): _____

02 SITE STATUS (Check one)
☒ A. ACTIVE ☐ B. INACTIVE ☐ C. UNKNOWN

03 YEARS OF OPERATION
BEGINNING YEAR _____ ENDING YEAR _____ ☒ UNKNOWN

04 DESCRIPTION OF SUBSTANCES POSSIBLY PRESENT, KNOWN, OR ALLEGED
Waste oil & Trichloroethylene mixed with water.

05 DESCRIPTION OF POTENTIAL HAZARD TO ENVIRONMENT AND/OR POPULATION
- Spills - Floral & faunal destruction; Groundwater contamination

V. PRIORITY ASSESSMENT

01 PRIORITY FOR INSPECTION (Check one. If high or medium is checked, complete Part 2 - Waste Information and Part 3 - Description of Hazardous Conditions and Incidents)
☐ A. HIGH (Inspection required promptly) ☐ B. MEDIUM (Inspection required) ☒ C. LOW (Inspect on time available basis) ☐ D. NONE (No further action needed, complete current disposition form)

VI. INFORMATION AVAILABLE FROM

01 CONTACT	02 OF (Agency/Organization)	03 TELEPHONE NUMBER
Millie ARCHER	KyNREPC - Louisville Field Office	(502) 588 4259

04 PERSON RESPONSIBLE FOR ASSESSMENT	05 AGENCY	06 ORGANIZATION	07 TELEPHONE NUMBER	08 DATE
Jim Jarman	KyNREPC	Div. Waste Mgt.	(502) 564-6716	03/27/84 (MONTH DAY YEAR)

EPA FORM 2070-12 (7-81)

EPA

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 2 - WASTE INFORMATION

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156400 1

II. WASTE STATES, QUANTITIES, AND CHARACTERISTICS

01 PHYSICAL STATES (Check all that apply)

- ☐ A. SOLID
- ☐ B. POWDER, FINES
- ☐ C. SLUDGE
- ☐ E. SLURRY
- ☐ F. LIQUID
- ☐ G. GAS
- ☒ D. OTHER N/A (Specify)

02 WASTE QUANTITY AT SITE (Measures of waste quantities must be independent)

- TONS
- CUBIC YARDS N/A
- NO. OF DRUMS

03 WASTE CHARACTERISTICS (Check all that apply)

- ☐ A. TOXIC
- ☐ B. CORROSIVE
- ☐ C. RADIOACTIVE
- ☐ D. PERSISTENT
- ☐ E. SOLUBLE
- ☐ F. INFECTIOUS
- ☐ G. FLAMMABLE
- ☐ H. IGNITABLE
- ☐ I. HIGHLY VOLATILE
- ☐ J. EXPLOSIVE
- ☐ K. REACTIVE
- ☐ L. INCOMPATIBLE
- ☒ M. NOT APPLICABLE

III. WASTE TYPE

CATEGORY	SUBSTANCE NAME	01 GROSS AMOUNT	02 UNIT OF MEASURE	03 COMMENTS
SLU	SLUDGE			
OLW	OILY WASTE			
SOL	SOLVENTS			
PSD	PESTICIDES			
OCC	OTHER ORGANIC CHEMICALS			
IOC	INORGANIC CHEMICALS			
ACD	ACIDS			
BAS	BASES			
MES	HEAVY METALS			

IV. HAZARDOUS SUBSTANCES (See Appendix for most frequently cited CAS Numbers)

01 CATEGORY	02 SUBSTANCE NAME	03 CAS NUMBER	04 STORAGE/DISPOSAL METHOD	05 CONCENTRATION	06 MEASURE OF CONCENTRATION

V. FEEDSTOCKS (See Appendix for CAS Numbers)

CATEGORY	01 FEEDSTOCK NAME	02 CAS NUMBER	CATEGORY	01 FEEDSTOCK NAME	02 CAS NUMBER
FDS			FDS		
FDS			FDS		
FDS			FDS		
FDS			FDS		

VI. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analyses, reports)

KYNREPC Files
Enforcement Branch files

EPA

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

I. IDENTIFICATION	
01 STATE	02 SITE NUMBER
KY	D061564001

II. HAZARDOUS CONDITIONS AND INCIDENTS

01 ☐ A. GROUNDWATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ B. SURFACE WATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ C. CONTAMINATION OF AIR — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ D. FIRE/EXPLOSIVE CONDITIONS — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ E. DIRECT CONTACT — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ F. CONTAMINATION OF SOIL — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 AREA POTENTIALLY AFFECTED: _____ (Acres) 04 NARRATIVE DESCRIPTION

01 ☐ G. DRINKING WATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ H. WORKER EXPOSURE/INJURY — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 WORKERS POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ I. POPULATION EXPOSURE/INJURY — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

EPA

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

I. IDENTIFICATION
01 STATE: KY | 02 SITE NUMBER: D061564001

II. HAZARDOUS CONDITIONS AND INCIDENTS (Continued)

01 ☐ J. DAMAGE TO FLORA — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ K. DAMAGE TO FAUNA — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION (Include name(s) of species)

01 ☐ L. CONTAMINATION OF FOOD CHAIN — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ M. UNSTABLE CONTAINMENT OF WASTES (Spills/runoff/standing liquids/leaking drums) — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ N. DAMAGE TO OFFSITE PROPERTY — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ O. CONTAMINATION OF SEWERS, STORM DRAINS, WWTPs — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ P. ILLEGAL/UNAUTHORIZED DUMPING — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

05 DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL, OR ALLEGED HAZARDS

III. TOTAL POPULATION POTENTIALLY AFFECTED: _____

IV. COMMENTS

This facility is now Regulated By RCRA AND is now under Enforcement preceedings in the Division's Enfocement Branch.
Site Has 15(+) Tanks with waste in them- Tanks are rusting & spills are evident according to pictures in Division files. Sample analysis of 3/13/84 shows high concentrations of Tri-chloroethylene in tank samples. The spillage area would be good sampling locations for future inspections.

V. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis, reports)

KYNREPC FILES
Louisville field Personnel - Enforcement files.

EPA FORM 2070-12 (7-81)



(VALLEY STATION) 38085 III SE

Mapped by the Army Map Service and the Geological Survey
Edited and Published by the Geological Survey

Control by USGS, NOS/NOAA, USCE, and the City of Louisville

Topography by photogrammetric methods from aerial photographs taken 1947. Field checked 1950. Revised from aerial photographs taken 1978. Field checked 1979. Map edited 1982

Polyconic projection. 10,000-foot grid ticks based on Kentucky coordinate system, north zone
1000-meter Universal Transverse Mercator grid, zone 16
1927 North American Datum
To place on predicted North American Datum 1983 move the projection lines 4 meters south and 3 meters west as shown by dashed corner ticks

Red tint indicates areas in which only landmark buildings are shown

MN GN
1½° 27 MILS 0°49' 15 MILS

UTM GRID AND 1982 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1 1/2
1000 0 1000 2000
1 5

CONTOUR IN
DOTTED LINES REPRE
NATIONAL GEODETIC

THIS MAP COMPLIES WITH NA
FOR SALE BY U. S. GEOLOGICAL
KENTUCKY GEOLOGICAL SURV
AND KENTUCKY DEPARTMENT OF C
A FOLDER DESCRIBING TOPOGRAPHIC MAP

REFERENCE # 2

"Rite in the Rain."
WEATHERPROOF

LEVEL

NOTEBOOK NO. 311

F4-2169 TDD-F4-9001-115

KENTUCKY PETROLEUM PRODUCTS

LOUISVILLE, JEFFERSON COUNTY, KENTUCKY

PROJECT MANAGER: WENDELL C. MCKENDON

APRIL 18, 1990

LOGBOOK REQUIREMENTS
REVISED - NOVEMBER 29, 1988

NOTE: ALL LANGUAGE SHOULD BE FACTUAL AND OBJECTIVE

1. Record on front cover of the Logbook: TDD No., Site Name, Site Location, Project Manager.
2. All entries are made using ink. Draw a single line through errors. Initial and date corrections.
3. Statement of Work Plan, Study Plan, and Safety Plan discussion and distribution to field team with team members' signatures.
4. Record weather conditions and general site information.
5. Sign and date each page. Project Manager is to review and sign off on each logbook daily.
6. Document all calibration and pre-operational checks of equipment. Provide serial numbers of equipment used onsite.
7. Provide reference to Sampling Field Sheets for detailed sampling information.
8. Describe sampling locations <u>in detail</u> and document all changes from project planning documents.
9. Provide a site sketch with sample locations and photo locations.
10. Maintain photo log by completing the stamped information at the end of the logbook.
11. If no site representative is on hand to accept the receipt for samples, an entry to that effect must be placed in the logbook.
12. Record I.D. numbers of COC and receipt for sample forms used. Also record numbers of destroyed documents.
13. Complete SMO information in the space provided.

4-18-90 M1

4-18-90 M1

0[illegible]01

1010 4-18-90

WEATHER CLEAR AND COOL

ARRIVED AT KY. PETROLEUM AT 1010 WEDNESDAY APRIL ~~11~~ 18, 1990

KY PETROLEUM WASTE, INC IS LOCATED AT 6900 GRADE LANE AT [illegible] AVE INTERSECTION.

SITE SURROUNDED BY CHAIN LINK FENCE WITH LOCKED GATE ON S SIDE, LOCKED GATE ~~[illegible]~~ ON WEST (FRONT) [illegible] [illegible] METAL OFFICE BUILDING ON WEST SIDE. SITE CONSISTS OF A SERIES OF STORAGE TANKS. STEAM? (VAPORS?) BEING EMITTED BEHIND TANKS AT PUMPHOUSE.

METAL 45 FT. TRAILER USED FOR STORAGE IS PARKED AT BACK OF PROPERTY ALONG NORTH FENCE. TANKER TRAILER PARKED ALONG BACK FENCE ON EAST SIDE.

4-18-90 [illegible]

SEE SITE MAP FOR TANK LOCATIONS.

SMALL TREES GROWING ALONG THE FENCE THAT SURROUNDS SITE. GRASS AND BRUSH GROWING UNDER HORIZONTAL TANKS BEHIND METAL BUILDING.

POWER LINES ON E SIDE OF GRADE LANE, S SIDE OF [illegible] RD, AND ALONG N BORDER OF SITE.

[illegible] BUSINESS [illegible] SIGNS AND [illegible] ON TO S AT CORNER OF GRADE LANE AND [illegible] AVE.

DIXIE [illegible] + COMMERCE PARK [illegible], GRADE LANE [illegible] [illegible] WEST.

[illegible] [illegible] [illegible] LOCATED ADJACENT TO SITE ON NORTH SIDE.

4-18-90 [illegible]

KENTUCKY PETROLEUM
6911 GRADE LANE
LOU. KY. 40213



W PROCESSOR AND BOILER ROOM
X 30'X50' METAL BLDG
Y DIKED AREA (PURCHASED PRODUCT TANK)
Z PARKING

① → PICTURE NUMBER AND DIRECTION TAKEN

EXISTING STRUCTURES
A TANK YARD
B PUMPHOUSE & LOADING RAMP
C WATER SEPARATION UNIT (UNDERGROUND)
D LOADING DOCK

~~(TEMPORARY)~~

4-18-90 m

Case No. _____

Low Concentration yes/no

Media	Lab	Airbill No.
Soil		
Water		

Airbill No.

KY-9001-115
4-18-90
1010
KY Petroleum Products
Louisville, KY
TANK YARD, LOADING WEST
Above Knapp Ave
KY-9001-115
4-18-90
1010
KY Petroleum Products
Louisville, KY
TANK YARD SHOWING PUMP
HOUSE AND STEAM CLEANER
KY-9001-115
4-18-90
1010
KY Petroleum Products
Louisville, KY
FRONT OF FACILITY

W. McLeod
2

W. McLeod
3

W. McLeod
1

0000010

0000011

0010042

F4-9001-115
4-18-90
1010
KY PETROLEUM PRODUCTS
LOUISVILLE, KY
NORTH SIDE OF FACILITY AND ADJACENT PROPERTY
By Whom: W. McKENDON
Keyed to map: 4

F4-9001-115
Date: 4-18-90
Time: 1010
Location: KY PETROLEUM PRODUCTS
LOUISVILLE, KY
Picture of: TANK YARD
W. McKENDON
5

F4-9001-115
Date: 4-18-90
Time: 1010
Location: KY PETROLEUM PRODUCTS
LOUISVILLE, KY
Picture of: TANK YARD, STORAGE TANKS
W. McKENDON
6

F4-9001-115
4-18-90
1010
KY PETROLEUM PRODUCTS
LOUISVILLE, KY
TANK YARD. BACK OF OFFICE
W. McKENDON
7

F4-9001-115
4-18-90
1010
KY PETROLEUM PRODUCTS
LOUISVILLE, KY
TANK YARD
W. McKENDON
8

F4-9001-115
4-18-90
1010
KY PETROLEUM PRODUCTS
LOUISVILLE, KY
TANK YARD
W. McKENDON
9

0010043

REFERENCE # 3

NUS CORPORATION
SUPERFUND DIVISION

PROJECT NOTES

TO: File - Kentucky Petroleum Products **DATE:** November 1, 1990

FROM: Wendell C. McLendon wcm

SUBJECT: Property Ownership of Facility and Surrounding Property, From Deed Books at Jefferson County Courthouse

REFERENCE: Kentucky Petroleum Products: owned by Leo J. and Julia C. Shircuff



Property to West Owned By: Dixie Warehouse and Cartage Company

Property to East Owned By: Lester W. Inman, Sr. or
1/2 By: James L. and Martha S. Mattingly
1/2 By: Allen C. and Sylvia Mattingly

Property to the South Owned By: Larry W. Embry
J. J. Simon

REFERENCE # 4

BEST MANAGEMENT PRACTICES PLAN

KENTUCKY PETROLEUM WASTE, INC.

PETROLEUM RECYCLING PLANT

LOUISVILLE, KENTUCKY

APPROVED BY: C.R. Shircliff

C. R. SHIRCLIFF
PLANT MANAGER

INTRODUCTION

In accordance with Kentucky Pollutant Discharge Elimination System (KPDES) Permit No. KY 0073172 for Kentucky Petroleum Waste, Inc., this plan describes potential sources of pollution to surface waters through discharges, leaks or spills of petroleum products. The plan further identifies measures to control or prevent discharges of such materials to surface waters.

DESCRIPTION OF FACILITY

Name: Kentucky Petroleum Waste, Inc.
Type: Petroleum Recyling for Energy Recovery
Location: 6911 Grade Lane
Louisville, KY 40213

Kentucky Petroleum Waste, Inc. produces fuels for industrial uses, both on and off specification. Petroleum products, both new and used are recovered from service facilities, industrial processes, water reclamation, and emergency spills. These products are then processed and blended with used or new fuels to produce a uniform product for energy recovery. [redacted] Products are then shipped by tank trucks from our facility to customers who have obtained requisite permits.

An attached map shows our location in the Knopp-Melton Avenue Industrial Park. Storm water runoff from the facility discharges through a drainage ditch approximately 1/4 mile to Pond Creek and eventually into the Ohio River. (See Attachment A.)

POLICY STATEMENT

Kentucky Petroleum Waste, Inc. has been involved in petroleum reclamation since 1962. Its founder, Leo J. Shircliff, has been involved in petroleum handling and transport since 1952.

It is our goal to provide a market for reclaimable petroleum products. To do this, we must satisfy the needs of both our producing customers and fuel consumers. In essence, we provide a conduit between producers and consumers and, also, an alternative to both proper and improper disposal. Along with providing a valuable service to commerce in the Commonwealth, we conduct our business in a manner that is responsible, safe, and in compliance with all applicable laws and regulations. In doing so, we strive to have as limited an adverse impact on the environment as is practicable. To achieve these goals, we have set forth in this plan procedures which now exist and have defined procedures to minimize the environmental impact of abnormal conditions or environmental incidents.

BMP COMMITTEE

Plant personnel involved in this plan are:

		Home Phone
Plant Manager:	Charles R. Shircliff	502/245-2030
Chairman:	Leo J. Shircliff	502/448-4733
Transportation Coordinator:	James L. Shircliff	502/935-4233
Operator:	Beverly A. Coffman	812/732-4399

Plant Phone #: 502/367-7766

The BMP Committee have the following responsibilities:

1. To provide assistance in developing, implementing and maintaining a BMP plan;

2. To establish BMP incident reporting procedures;

3. To identify potential spill sources;

4. To establish plant incident response, cleanup, and notification procedures;

5. To establish monitoring and records procedure;

6. To review new construction and changes in processes and procedures; and

7. To evaluate the effectiveness of the BMP plan and institute any changes.

RISK IDENTIFICATION AND ASSESSMENT

The primary areas of risk at our plant are:

A. The loading dock and immediate area;

B. The storage tanks and containment areas; and

C. The processing vessels, pumps, valves, and pipelines.

The loading dock and immediate area are located on a concrete basin which drains directly to a three stage oil separation unit consisting of one 2,000 gallon tank and three 550 gallon tanks. Total containment capacity is 3500 gallons. The bulk storage tank area and all drainage paths are constructed

of concrete. These areas also drain to the oil separation unit. The entire area is also diked and has a total containment capacity of 30,000+ gallons.

Drivers are responsible for loading and off-loading of tankers. Storage tank levels are checked before pumping begins. When loading, tank levels are constantly monitored, and if filled to capacity, adequate space is allowed for expansion due to temperature change. The same procedure is followed in off-loading. The pump can be controlled from inside or outside of the pump room, as well as from the off-loading dock. Hoses are drained and all valves are closed after each load. Tank numbers are then noted for inventory control.

When oils are transferred from bulk storage to the process storage tank (16,000 gallon capacity), a dial gauge on the tank is monitored to indicate the oil level. However, this tank is a pressure tank with a float valve on the vent pipe and cannot overflow. All pumps are equipped with pressure release bypasses.

All oil process lines are schedule 40 threaded pipe or schedule 80 welded pipe. Heat exchangers are shell and tube type and are rated 300+ psi. Pumps are adjusted to 50 psi. When service is required, drip pans or drainage basins are used. When oils are diverted to the evaporator, the oil level is monitored. However, any overflow from the evaporator would be collected in a vacuum/condensate storage tank (11,500 gallons capacity) which is rated for 30 inches of vacuum. Our vacuum pump is capable of 15 inches vacuum. This tank also is equipped with a dial gauge. The capacity of this tank will never be used completely because the vacuum storage is important to our processing. We anticipate emptying this tank when truck load amounts accumulate (approximately 7,000 gallons). At present rates, this will be done approximately once a year. This portion of our plant was constructed in 1986 and put into service in January 1987.

- Processed oils are metered into two (2) finished product tanks (30,000 gallons each capacity). These tanks are constructed as pressure tanks (1 1/8" walls) but are now used at atmospheric pressure. They are contained by a concrete dike. Precipitation is pumped to a water separation unit in the bulk storage area. These tanks are filled at a rate between 10 and 20 G.P.M. Although their level may be determined by meter readings, they are visually checked on the hour until 75% capacity is reached. They are then visually checked every 15 minutes. At 500 gallons from capacity, they are constantly monitored until capacity is reached.

- Operations in processing and finished product storage are the responsibility of the operator on duty. The operator also reports any problems, such as leaky joints, valve stems, or pump packing that cannot be immediately repaired. These are assigned for maintenance. If this type of problem cannot be controlled through use of drip pans, absorbent clays, etc., immediate attention is required. Small spills are reported to the Plant

Manager and cleanup assigned if warranted. Any spill which poses a possibility of discharge off-site or is greater than 50 gallons, shall be immediately reported to local authorities and to the Plant Manager. All steps shall then be taken to contain and minimize adverse affects. This will include closing discharge valves, use of vacuum storage, system and absorbent clays. An accident report will be filed in the event of any such occurrence. (See enclosed Accident Report Form.)

EMPLOYEE TRAINING

Our six full time personnel have over 100 years combined experience in their respective fields. We are a family held corporation and employee turn over is nil. Several of us have attended the hearings sponsored by the E.P.A. in Frankfort, Georgetown, and Louisville. We have all read and debated new regulations as they have been set forth. On March 19, 1987, all personnel attended a seminar on risk identification and recent changes in E.P.A. guidelines presented by Ronald VanStockum, an attorney and environmental consultant in Louisville. We will continue these practices as needed.

We are well trained in spill control as it is a service we offer our customers and have for 25 years. All spills or releases will be documented with an accident investigation report (see attached copy) from originator to Plant Manager. The Plant Manager is then responsible to evaluate the incident, make any changes in procedure if necessary, and make any reports to regulatory agencies.

INSPECTION AND MAINTENANCE

All personnel are required to report any problems with any equipment to the Plant Manager. Inspections are performed during routine use of equipment, and during scheduled maintenance intervals. Any major overhaul or maintenance is performed during shutdown for boiler inspection and maintenance if practicable.

- Process operators also perform daily inspectons before start-up when operating Processor. Items inspected daily include gauges and flow meters, pump packing and shaft lube, belt drive tensions, valve stem packing and operation of steam traps and condensate returns. Product quality is also inspected upon start-up through sampling and analysis. All samples taken are returned to storage after analysis.

Inspection of storage vessels is performed weekly. All bulk storage is above ground. In the last ten years, only one leak has been discovered. This was a very small leak on an older tank when it was first put into service. It was immediately emptied and repaired. The nature of our product discourages any corrosion in storage vessels. Leaks generally involve valve stems and threaded joints. These are simply tightened or repacked and generally show no further problem.

GOOD HOUSEKEEPING

All maintenance procedures involve cleanup as a final step. Equipment out-of-service, spare parts, as well as tools, are kept in designated areas. Any oils or greases in work areas are promptly cleaned up with the use of rags or absorbent clays to prevent tracking and safety hazards.

Yearly appearance improvement plans are made during personnel meetings. Plans are developed by input of all involved and implemented as funds and manpower are available.



A Material Safety Data Sheet for our typical final product is enclosed along with a more recent chemical analysis. Our products are not reactive, nor is there any problem with compatibility.

SECURITY

The facility is enclosed by 7 foot link fencing that is topped by three strands of barb wire. Gates are padlocked at night. Security lights of "dusk-to-dawn" type light the entire area at night. Signs on the gates state the materials stored and necessary emergency phone numbers.

MATERIAL INVENTORY

(See Site Plan - Attachment B)

We use 21 storage tanks for bulk storage of fuels, oils, and fuel oil blends as follows:

1 - 2,000 gallon
14 - 5,000 gallon
2 - 8,000 gallon
3 - 10,000 gallon
1 - 20,000 gallon

We use two (2) process related tanks:

1 - 16,000 gallon tank for process transfer and heating of product

1 - 11,500 gallon tank for vacuum and condensate storage

We use two (2) tanks of the finished product:

2 - 30,000 gallon

All storage tanks are in diked containment areas.

There are also small fuel oil tanks and drums which we keep for use by potential customers. These are stored on-site and are empty. Motor oil, gear oil, antifreeze and kerosene for our uses are also stored on-site.

Attachment A



Mapped by the Army Map Service and the Geological Survey
Edited and published by the Geological Survey

Control by USGS, USC&GS, USCE, and the City of Louisville

Topography by photogrammetric methods from aerial photographs taken 1947. Field checked 1950
Revised by the Geological Survey 1965

Polyconic projection. 1927 North American datum
10,000-foot grid based on Kentucky coordinate system, north zone
1000-meter Universal Transverse Mercator grid ticks, zone 16, shown in blue

Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked

Red tint indicates areas in which only landmark buildings are shown



UTM GRID AND 1971 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

ATTACHMENT B ↔ = 10'

KENTUCKY PETROLEUM
6911 GRADE LANE
LOU. KY. 40213



MATERIAL SAFETY DATA SHEET

Kentucky Petroleum Waste

For health Hazard Information Call:

For Other Information Call:

Section I. Identification

Product Name: Reclaimed Oil DOT No. 1993

Chemical Name: Reclaimed Oil

Section II. Product and Component Hazard Data

A. Component	Percent	TLV	Notes
Lubricating Oil	75. %	Not Established	
Fuel Oils	25. %	Not Established	
Benzene	<0.1	10 ppm	1
Toluene	<0.1	200 ppm	
Xylene	<0.1	100 ppm	
Lead	<0.1	0.15 mg/cu m	
Dichloromethane	<0.1	100 ppm	1
Trichloroethylene	<0.1	50 ppm	1
Carbon Terachloride	<0.1	5 ppm (skin)	1
Perchloroethylene	<0.1	50 ppm	1

Note 1: This compound is a suspected carcinogen

Section III. Physical Data

Initial Boiling Point: >300 deg F Specific Gravity: 0.9

Percent Volitiles: > 98. %

Section IV. Fire and Explosion Hazard

Flash Point:180 to 212 deg F Lower Exposion Limit: 2.0

Extinguishing Media: Alcohol Foam, Carbon Dioxide, Dry Chemical

Hazardous Decomposition Products:

Special Firefighting Precautions:
Wear self-contained breathing apparatus with full facepiece in pressure demand mode.

Section V. Health Hazard Data

Effects of Overexposure:

Eyes: Can cause severe irritation, redness, tearing, blurred vision.

Skin: Can cause irritation

Breathing: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatique, nausea, headache, possible unconciousness, and even asphyxiation.

Swallowing: Can cause gastrointestinal irritation, nausea, vomitting, and diarrhea.

Firt Aid:

If on Skin: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use.

If in Eyes: Flush With large amounts of water, lifting upper and lower lids occasionally, get medical attention

If Swallowed: Immediately drink two glasses of water. Get medical attention immediately.

If Breathed: If affected remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artifical resperation. Get medical attention.

Section VI. Reactivity

Hazardous polymerization: Does not occur

Stability: stable

Incompatability: Aviod contact with oxidizers.

Section VII. Spill Procedures

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from the area until clean-up is completed. Stop leak at source.Contain liquid spill with dikes to prevent spill from spreading. Pick up liquid with sand or floor absorbant. Shoval diking material in drums. Dispose of in a landfill according to Local, State, and Federal regulations.

Section VIII. Protective equipment

Resperatory Protection: If the TLV of any component is exceeded, a NIOSH/MSHA jointly approved air supplied resperator is advised in absence of proper environmental controls. OSHA regulations allow the use of other NIOSH/MSHA reperators under certain conditions.

Ventilation: Provide sufficient mechanical ventilation to maintain exposure below TLVs.

Protective Gloves: Wear resistant gloves such as neoprene.

Eye Protection: Chemical spash goggles in complience with OSHA regulations are advised.

Other Protective Equipment: Wearing impervious chothing and boots is advised.

Section IX. Special Precautions

Containers may be hazardous when empty.

Store at ambient temperature out of direct sunlight. Store as a flammable liquid.

Metro Service Laboratories, Inc.

RECEIVED FROM: Kentucky Petroleum Waste **DATE RECEIVED:** 01/29/87

SAMPLE TYPE: Oil **ANALYSIS NUMBER:**35379

SAMPLED BY: Client **DATE REPORTED:** 02/11/87

MARKS: 209
Fuel Oil Blend

API Gravity @ 60°F	33.3
Specific Gravity @ 60°F	0.8586
lbs/gal	7.149
B.T.U./lb	17,767.
B.T.U./gal	127,016.
Sulfur Content	0.34 %
B.S.&.W.	0.15 %
Viscosity @ 100°F	47.6 s.u.s.
Flash Point (P.M.C.C.)	101°F
Pour Point	-21°F
Halogen	0.09 %
Lead	3. ppm
Cadmium	1.7 ppm
Chromium	3.7 ppm
Arsenic	<0.01 ppm

Reviewed By:

6309 FERN VALLEY PASS
LOUISVILLE, KENTUCKY 40228
PHONE (502) 964-0865

KENTUCKY PETROLEUM WASTE, INC.

ACCIDENT/INCIDENT INVESTIGATION REPORT

REPORT NO._____

REPORT DATE_____

ACCIDENT/INCIDENT INVESTIGATION DESCRIPTION

LOCATION_____DATE_____TIME_____ AM PM

TYPE OF ACCIDENT/INCIDENT PERSON(S) INVOLVED_____

___ Injury/Illness/Overexposure OR INJURED_____

___ Spill/Release

___ Equipment/Property Damage

___ Fire

___ Near Miss

___Performance/Procedure

Describe clearly what happened_____

_____

_____

_____

_____

_____

BASIC CAUSE (CHECK APPLICABLE SPACES)

Performance	Procedures	Equipment/Material/ Facility/Tools
__ Knowledge Deficiency	__ Lack of	__ Improper
__ Execution Deficiency	__ Inadequate	__ Defective

Comments_____

_____

_____

Immediate Action Taken_____

_____

_____

Suggestions to Prevent Recurrence_____

_____

_____

_____

Date_____ Signature_____

LOSS ESTIMATION

Material Loss_____ Gal/Lbs of_____ $ Value_____

Reportable Quantity_____Lbs. Report Made ___Yes ___No

Lost to ___Air ___Sewer ___Ground ___Water Body

Equipment Damage (Cost to Replace/Repair) $_____

_____

ACTION PLAN TO PREVENT RECURRENCE

Action Steps	Accountability	Date to Complete
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Comments_____

_____

Date_____ Signature_____

Comments_____

_____

Further Investigation Warranted Yes ___ No ___

Date_____ Signature_____

CORRECTIVE ACTION COMPLETED

Date_____ Signature_____

ROUTING: Copies 1, 2, 3 Copies 1, 2, 3 Xerox Copy

Originator _____ Immediate Supervisor _____ RSM/PM _____HS&EA

Copy 1 Copy 2

_____

Copy 3
File

Additional
Distribution
As Needed

REFERENCE # 5

NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DIVISION OF WASTE MANAGEMENT

INTERIM STATUS HAZARDOUS WASTE FACILITY REPORT

FACILITY NAME: Kentucky Petroleum WBT EPA ID NUMBER: KYD06-156-409T
FACILITY CLASSIFICATION: H.W. Fuel Marketer, Off Spec. Use & Used Marketer
COUNTY: Jefferson DATE: 9/7/86 TIME: 2pm ROUTINE ☒ FOLLOW-UP ☐

INSPECTION ITEM	CITE*	C	NC	NA	COMMENTS
I. REGISTRATION REQUIREMENTS					
1. Operations consistent with registration	32 010 § 3		✓		
2. Hazardous waste determination	32:020 § 2		✓		
II. GENERAL FACILITY REQUIREMENTS					
1. General waste analysis	35:020 § 4		✓		
2 Security	35 020 § 5		✓		
3. General inspection requirements	35:020 § 6		✓		
4. Personnel training	35:020 § 7		✓		
III. PREPAREDNESS AND PREVENTION					
1. Maintenance & operation of required equipment	35 030 § 3, 4 & 5	✓	✓		
2. Required aisle space	35:030 § 6	✓		✓	
3. Local authority notification	35:030 § 7		✓		
4. Contingency plan: (a) Content	35:040 § 3 & 6		✓		
(b) Maintained at facility	35:040 § 4		✓		
(c) Distribution	35:040 § 4		✓		
(d) Implementation	35:040 § 2 & 7		✓		
IV. PRETRANSPORT REQUIREMENTS					
1. Packaging	32:030 § 1			✓	
2. Labeling	32:030 § 2			✓	
3. Marking	32:030 § 3			✓	
4. Waste accumulation: (a) 90-day accumulation	32:030 § 5	✓			
(b) Accumulation dated	32:030 § 5			✓	
(c) "Hazardous Waste" marking	32:030 § 5		✓		
V. OPERATING RECORD/ MANIFEST					
1. Generator manifest requirements: (a) Required information	32:020 § 2		✓		
(b) Proper execution	32:020 § 3 & 4		✓		
(c) Manifest maintained	32:040 § 1		✓		
(d) Exception report submitted & maintained	32:040 § 1 & 3		✓		
(e) International shipments	32:050 § 1		✓		
2. Generator annual report submitted & maintained	32:040 § 1 & 2			✓	

AUG 15 2 19 PM '86
WASTE MANAGEMENT

*All regulatory cites are from Title 401 of the Kentucky Administrative Regulations. The number preceeding the colon is the chapter reference. The number appearing after the colon is the regulation number. The symbol "§" is a reference to the section. For example, the reference to 32:010 § 3 should be read 401 KAR 32:010, Section 3.

INTERIM STATUS FACILITY INSPECTION REPORT

FACILITY NAME: Kentucky Petroleum Waste, Inc. **DATE:** 7/7/86

INSPECTION ITEM	CITE*	C	NC	NA	COMMENTS
3. TSD manifest requirements:					
(a) TSD manifest execution	35:050 § 2		✓		
(b) Manifest discrepancies	35:050 § 3		✓		
(c) Unmanifested waste report	35:050 § 7		✓	✓	
(d) Foreign source notification	35:020 § 3		✓	✓	
4. Operating records:					
(a) Incoming waste records	35:050 § 4		✓	✓	
(b) Waste location records	35:050 § 4		✓	✓	
(c) Waste analysis records	35:050 § 4		✓	✓	
(d) Contingency plan implementation report	35:050 § 4		✓	✓	
(e) Inspection records	35:050 § 4		✓	✓	
(f) Groundwater monitoring records	35:050 § 4		✓	✓	
(g) Closure plan & cost estimate records	35:050 § 4		✓	✓	
5. TSD annual report submitted & maintained	35:050 § 6			✓	

*All regulatory cites are from Title 401 of the Kentucky Administrative Regulations. The number preceeding the colon is the chapter reference. The number appearing after the colon is the regulation number. The symbol "§" is a reference to the section. For example, the reference to 32:010 § 3 should be read 401 KAR 32:010, Section 3.

VI. ATTACHMENTS: Container Facility Report ☐ Tank Facility Report ☐ Surface Impoundment Report ☐ Waste Pile Report ☐ Land Treatment Facility Report ☐ Landfill Report ☐ Incinerator Report ☐ Thermal Treatment Facility Report ☐ U I C Well Report ☐ Chemical, Physical & Biological Treatment Facility Report ☐

VII. GENERAL INFORMATION:

	YES	NO	N/A
1. Photographs taken?	☐	☒	☐
2. Samples collected?	☐	☒	☐
3. Previous non-compliances corrected?	☐	☒	☐

VIII. COMMENTS INCLUDING REMEDIAL MEASURES AND EXPECTED CORRECTION DATES:

Waste analysis does not have ignitability, pH, reactivity, & metals. No Part A permit filed with U.S. EPA. No copy of notice on site as required by 401 KAR 36:040, Section 8(3). No determination of still bottoms material sold once per year to Outer Loop Landfill; may be a generator [illegible]

INVESTIGATOR'S SIGNATURE [signature] **TITLE** Env. Inspector Sr.

I hereby acknowledge receipt of a copy of this report and further acknowledge that I have been advised of the discrepancies and alleged violations noted during the inspection.

OWNER'S or OPERATOR'S SIGNATURE [signature] **TITLE** Engineer

I do not necessarily agree with proceeding —

REFERENCE # 6

FOR DEPARTMENT USE

APPLICATION NUMBER _____

SUBMISSION DATE _____

PERMIT NUMBER _____

EXPIRATION DATE _____

COMMONWEALTH OF KENTUCKY

DEPARTMENT FOR NATURAL RESOURCES
AND ENVIRONMENTAL PROTECTION

DIVISION OF HAZARDOUS
MATERIAL AND WASTE MANAGEMENT

PERMIT APPLICATION FOR TRANSPORTING AND HANDLING OF HAZARDOUS WASTES

GENERAL INFORMATION

Hazardous waste means any substance or combination of substances the disposition of which may create a threat to public health or to animal and aquatic life.

Three applications shall be submitted to the Department. The information requested on pages 1 and 2 shall be provided for each hazardous waste collected from each source.

If difficulty is encountered in providing the information requested in this applicatior please call or write the Division of Hazardous Material and Waste Management, Department for Natural Resources and Environmental Protection, Frankfort, Kentucky, 40601. Phone: (502) 564-6716

APPLICANT INFORMATION

A. Applicant's business name Ky. PETROLEUM PRODUCTS, Co.

B. If applicant is a partnership, the name and address of each partner shall be listed on a separate sheet.

C. Applicant's business address 4019 BLANTON LANE

D. Applicant's business phone: area code 502 number 447-1802

E. Name and phone number of an individual to be contacted should an emergency occur. LEO SHIRCLIFF -502-447-1802

F. To the best of my knowledge, the information contained in this application is true, correct, and complete.

Leo Shircliff	Owner	6-22-77
Signature	Title	Date

HAULER'S SURVEY FORM

I. Hauler:

Business Name: Kentucky Petroleum Products No. of Employees 2
Business Address: 4019 BLANTON LANE (City) LOUISVILLE (Zip) 40216
County: JEFFERSON (Business Phone) 502-447-1802 (Area Code) 502
Person Completing Form: LEO SHIRCLIFF Title: OWNER

II. Disposal and/or Processing Facilities used by Hauler:

A. Business Name: KY PETROLEOM PRODUCTS Co.
Business Address: 6911 GRADE LANE City LOU. State KY
County JEFFERSON Zip _____ Business Phone 447-1802 Area Code 40216

_____ Land Disposal
_____ Incinerator
_____ Liquid Waste Treatment
_____ Other (Specify) WASTE OIL COLLECTION & spraying

B. Business Name: _____
Business Address: _____ City _____ State _____
County _____ Zip _____ Business Phone _____ Area Code _____

_____ Land Disposal
_____ Incinerator
_____ Liquid Waste Treatment
_____ Other (Specify)

C. List any additional disposal and/or facilities used by Hauler on back of this form.

III. Storage Facilities Owned or Used by Hauler:

A. Yes ___ No ___ Storage facilities used. (If yes, describe waste & type storage on back)
B. Maximum quantity stored at any time 120,000 gals.).
C. Frequency of transfer to storage area: Daily
D. Frequency of transfer from storage area: 3 or 4 Days per. week
E. Method of transfer from storage area: Tank Truck.

IV. Additional Information:

A. Indicate number of customers served by Hauler of each item below:

___ Residental ✓ Industrial 20-30 ✓ Commercial 100-150 ___ Governmental ___ Institutional

B. Indicate quantity collected for each type (tons/week):

___ Residental 400,000 Gals ✓ Industrial 10,000-15,000 ✓ Commercial ___ Governmental ___ Institutional

C. List below the areas (by city or county) served by Hauler:

all of Jefferson County

D. Indicate amount of equipment owned or used by Hauler:

_____ Packer Trucks
1 Pick-Up Trucks
_____ Stationary Compactors
2 Tank TRUCKS Other (Specify)
_____ Non-Compacter Trucks
_____ Dumpster Boxes
_____ Open Top Boxes

FOR DEPARTMENT USE

REFERENCE # 7

APPLICATION NUMBER _____

SUBMISSION DATE _____

PERMIT NUMBER _____

EXPIRATION DATE _____

COMMONWEALTH OF KENTUCKY

DEPARTMENT FOR NATURAL RESOURCES
AND ENVIRONMENTAL PROTECTION

DIVISION OF HAZARDOUS
MATERIAL AND WASTE MANAGEMENT

PERMIT APPLICATION FOR TRANSPORTING AND HANDLING OF HAZARDOUS WASTES

GENERAL INFORMATION

Hazardous waste means any substance or combination of substances the disposition of which may create a threat to public health or to animal and aquatic life.

Three applications shall be submitted to the Department. The information requested on pages 1 and 2 shall be provided for each hazardous waste collected from each source.

If difficulty is encountered in providing the information requested in this application please call or write the Division of Hazardous Material and Waste Management, Department for Natural Resources and Environmental Protection, Frankfort, Kentucky, 40601. Phone: (502) 564-6716

APPLICANT INFORMATION

A. Applicant's business name Ky. Petroleum Products Co

B. If applicant is a partnership, the name and address of each partner shall be listed on a separate sheet.

C. Applicant's business address 4019 Blanton Lane - Lou. Ky-402

D. Applicant's business phone: area code 502 number 447-1802

E. Name and phone number of an individual to be contacted should an emergency occur. LEO SHIRCLIFF - 502-447-1802

F. To the best of my knowledge, the information contained in this application is true, correct, and complete.

Leo Shircliff	Owner	11-28-77
Signature	Title	Date

HAULER'S SURVEY FORM

Kentuckiana

I. Hauler:

Business Name: Kentucky Petroleum Products No. of Employees 3
Business Address: 4019 Blanton Lane (City) Louisville (Zip) 40216
County: Jefferson (Business Phone) 502 — (Area Code) 447-1802
Person Completing Form: Title:

II. Disposal and/or Processing Facilities used by Hauler:

A. Business Name: Ky. Petroleum Products Co.
Business Address: 4019 Blanton Lane City Louisville State Ky.
County Jefferson Zip 40216 Business Phone 447-1802 Area Code 502

____ Land Disposal
____ Incinerator
____ Liquid Waste Treatment
____ Other (Specify)- Resale & spraying.

B. Business Name: Mobil Waste Land Fill
Business Address: Outer Loop - City Louis. State Ky
County Jefferson Zip ____ Business Phone 969-2393 Area Code 502

✓ Land Disposal
____ Incinerator
____ Liquid Waste Treatment
____ Other (Specify)

C. List any additional disposal and/or facilities used by Hauler on back of this form.

III. Storage Facilities Owned or Used by Hauler:

A. Yes ✓ No ___ Storage facilities used. (If yes, describe waste & type storage on back)
B. Maximum quantity stored at any time 120000 Gals or gals.).
C. Frequency of transfer to storage area: Daily
D. Frequency of transfer from storage area: Daily
E. Method of transfer from storage area: Tank truck.

RECEIVED
NOV 2 8 1977
DEPARTMENT FOR NATURAL RESOURCES & ENVIRONMENTAL PROTECTION
DIVISION OF HAZARDOUS MATERIAL & WASTE MANAGEMENT

IV. Additional Information:

A. Indicate number of customers served by Hauler of each item below:

___ Residental 30 Off. Industrial 100 Off. Commercial ___ Governmental ___ Institutional

B. Indicate quantity collected for each type (tons/week):

___ Residental 250,000 Off 200,000 to Industrial 700,000 500,000 to Commercial ___ Governmental ___ Institutional

C. List below the areas (by city or county) served by Hauler:

Jefferson County - Bay Ky
Parts of Hardin County
Lexington Ky.

Jeffersonville, New Albany Ind.

D. Indicate amount of equipment owned or used by Hauler:

____ Packer Trucks
____ Pick-Up Trucks
____ Stationary Compactors
2 Tank Trucks Other (Specify)
____ Non-Compacter Trucks
____ Dumpster Boxes
____ Open Top Boxes

REFERENCE # 8

Ken - please reply by memo

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

September 26, 1986

MEMORANDUM

TO: John Brooks, Area Supervisor
Louisville Field Office

THRU: Carl Millanti, Acting Branch Manager CM.
Field Operations Branch

Caroline Patrick Haight, Manager CPH
Permit Review Branch

FROM: Carol Glaser, Secretary CG
Permit Review Branch

RE: Kentucky Petroleum Waste, Inc.
4019 Blanton Lane
Louisville, Ky. 40216
EPA I.D. #KYD06-156-4001

Attached is a Notification from Kentucky Petroleum Waste stating they are a Transporter and TSD facility. Please make a determination based on your knowledge of the facility or by inspection whether they actually are a Transporter and TSD facility.

If you have any questions, please feel free to contact me.

JAD:cg

Attachment

Please print or type with ELITE type (12 characters per inch) in the unshaded areas only.

Form Approved. OMB No. 2050-0028 Expires 9-30-88
GSA No. 0246-EPA-AF

United States Environmental Protection Agency
Washington, DC 20460

EPA Notification of Hazardous Waste Activity

Please refer to the instructions for Filing Notification before completing this form. The information requested here is required by law (Section 3010 of the Resource Conservation and Recovery Act).

For Official Use Only

Comments

Installation's EPA ID Number: KYD061564001 (T/A C)

Approved | Date Received (yr. mo. day)

I. Name of Installation

KY. PETROLEUM WASTE INC.

II. Installation Mailing Address

Street or P.O. Box: 4019 BLAWTOW LANE

City or Town: LOUISVILLE | State: KY. | ZIP Code: 40216

III. Location of Installation

Street or Route Number: 6911 GRADE LANE

City or Town: LOUISVILLE | State: KY | ZIP Code: 40213

IV. Installation Contact

Name and Title (last, first, and job title): SHIRCLIFF JAMES OWNER

Phone Number (area code and number): 502 447 8602

V. Ownership

A. Name of Installation's Legal Owner: JAMES L. SHIRCLIFF

B. Type of Ownership (enter code): CORPORATION

VI. Type of Regulated Waste Activity (Mark 'X' in the appropriate boxes. Refer to instructions.)

A. Hazardous Waste Activity

- [ ] 1a. Generator
- [ ] 1b. Less than 1,000 kg/mo.
- [X] 2. Transporter
- [X] 3. Treater/Storer/Disposer
- [ ] 4. Underground Injection
- [X] 5. Market or Burn Hazardous Waste Fuel (enter 'X' and mark appropriate boxes below)
  - [ ] a. Generator Marketing to Burner
  - [X] b. Other Marketer
  - [ ] c. Burner

B. Used Oil Fuel Activities

- [ ] 6. Off-Specification Used Oil Fuel (enter 'X' and mark appropriate boxes below)
  - [ ] a. Generator Marketing to Burner
  - [X] b. Other Marketer
  - [ ] c. Burner
- [ ] 7. Specification Used Oil Fuel Marketer (Or On-Site Burner) Who First Claims the Oil Meets the Specification.

RECEIVED
JAN 24 1 13 PM '86
LOUISVILLE WASTE MANAGEMENT

VII. Waste Fuel Burning: Type of Combustion Device (enter 'X' in all appropriate boxes to indicate type of combustion device(s) in which hazardous waste fuel or off-specification used oil fuel is burned. See instructions for definitions of combustion devices.)

- [ ] A. Utility Boiler
- [ ] B. Industrial Boiler
- [ ] C. Industrial Furnace

VIII. Mode of Transportation (transporters only — enter 'X' in the appropriate box(es))

- [ ] A. Air
- [ ] B. Rail
- [X] C. Highway
- [ ] D. Water
- [ ] E. Other (specify)

IX. First or Subsequent Notification

Mark 'X' in the appropriate box to indicate whether this is your installation's first notification of hazardous waste activity or a subsequent notification. If this is not your first notification, enter your installation's EPA ID Number in the space provided below.

- [ ] A. First Notification
- [X] B. Subsequent Notification (complete item C)

C. Installation's EPA ID Number: KYD066156406

EPA Form 8700-12 (Rev. 11-85) Previous edition is obsolete.

Continue on reverse

ID — For Official Use Only														T/A	C
C															
W															1

IX. Description of Hazardous Wastes (continued from front)

A. Hazardous Wastes from Nonspecific Sources. Enter the four-digit number from 40 CFR Part 261.31 for each listed hazardous waste from nonspecific sources your installation handles. Use additional sheets if necessary.

1	2	3	4	5	6
7	8	9	10	11	

B. Hazardous Wastes from Specific Sources. Enter the four-digit number from 40 CFR Part 261.32 for each listed hazardous waste from specific sources your installation handles. Use additional sheets if necessary.

13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30

C. Commercial Chemical Product Hazardous Wastes. Enter the four-digit number from 40 CFR Part 261.33 for each chemical substance your installation handles which may be a hazardous waste. Use additional sheets if necessary.

31	32	33	34	35	36
37	38	39	40	41	42
43	44	45	46	47	48

D. Listed Infectious Wastes. Enter the four-digit number from 40 CFR Part 261.34 for each hazardous waste from hospitals, veterinary hospitals, or medical and research laboratories your installation handles. Use additional sheets if necessary.

49	50	51	52	53	54

E. Characteristics of Nonlisted Hazardous Wastes. Mark 'X' in the boxes corresponding to the characteristics of nonlisted hazardous wastes your installation handles. (See 40 CFR Parts 261.21 — 261.24)

☐ 1. Ignitable (D001) ☐ 2. Corrosive (D002) ☐ 3. Reactive (D003) * ☑ 4. Toxic (D000)

X. Certification

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this and all attached documents, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

Signature	Name and Official Title (type or print)	Date Signed
James L. Shircliff	JAMES SHIRCLIFF OWNER	1/29/86

EPA Form 8700-12 (Rev. 11-85) Reverse

BILLING CODE 6560-50-C

RECEIVED JAN 27 1 13 PM '86 WASTE MANAGEMENT

RECEIVED JAN 29 9 46 AM '86 WASTE MANAGEMENT

* THE ONLY THING I DEAL IN IS USED OILS.

NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DIVISION OF WASTE MANAGEMENT

INTERIM STATUS HAZARDOUS WASTE FACILITY REPORT

FACILITY NAME: Kentucky Petroleum, Inc. EPA ID NUMBER: KYD067567091
FACILITY CLASSIFICATION: H.W. Fuel Blenders, Used Oil Fuel Marketers
COUNTY: Jefferson DATE: 7/7/86 TIME: 2pm ROUTINE ☒ FOLLOW-UP ☐

INSPECTION ITEM	CITE*	C	NC	NA	COMMENTS
I. REGISTRATION REQUIREMENTS					
1. Operations consistent with registration	32:010 § 3		✓		
2. Hazardous waste determination	32:020 § 2		✓		
II. GENERAL FACILITY REQUIREMENTS				✓	
1. General waste analysis	35:020 § 4		✓	✓	
2. Security	35:020 § 5		✓	✓	
3. General inspection requirements	35:020 § 6		✓	✓	
4. Personnel training	35:020 § 7		✓		
III. PREPAREDNESS AND PREVENTION					
1. Maintenance & operation of required equipment	35:030 § 3, 4 & 5		✓		
2. Required aisle space	35:030 § 6	✓		✓	
3. Local authority notification	35:030 § 7		✓		
4. Contingency plan:					
(a) Content	35:040 § 3 & 6		✓		
(b) Maintained at facility	35:040 § 4		✓		
(c) Distribution	35:040 § 4		✓	✓	
(d) Implementation	35:040 § 2 & 7		✓		
IV. PRETRANSPORT REQUIREMENTS					
1. Packaging	32:030 § 1			✓	
2. Labeling	32:030 § 2			✓	
3. Marking	32:030 § 3			✓	
4. Waste accumulation:					
(a) 90-day accumulation	32:030 § 5	✓			✓
(b) Accumulation dated	32:030 § 5			✓	
(c) "Hazardous Waste" marking	32:030 § 5		✓		
V. OPERATING RECORD/ MANIFEST					
1. Generator manifest requirements:					
(a) Required information	32:020 § 2		✓		
(b) Proper execution	32:020 § 3 & 4		✓		
(c) Manifest maintained	32:040 § 1		✓		
(d) Exception report submitted & maintained	32:040 § 1 & 3		✓		
(e) International shipments	32:050 § 1		✓		
2. Generator annual report submitted & maintained	32:040 § 1 & 2			✓	

AUG 15 2 18 PM '86
WASTE MANAGEMENT BRANCH

*All regulatory cites are from Title 401 of the Kentucky Administrative Regulations. The number preceeding the colon is the chapter reference. The number appearing after the colon is the regulation number. The symbol "§" is a reference to the section. For example, the reference to 32:010 § 3 should be read 401 KAR 32:010, Section 3.

INTERIM STATUS FACILITY INSPECTION REPORT

FACILITY NAME: Kentucky Petroleum Waste, Inc. **DATE:** 7/7/86

INSPECTION ITEM	CITE*	C	NC	NA	COMMENTS
3. TSD manifest requirements:					
(a) TSD manifest execution	35:050 § 2		✓		
(b) Manifest discrepancies	35:050 § 3		✓		
(c) Unmanifested waste report	35:050 § 7		✓	✓	
(d) Foreign source notification	35:020 § 3		[illegible]	✓	
4. Operating records:					
(a) Incoming waste records	35:050 § 4		✓	✓	
(b) Waste location records	35:050 § 4		✓	✓	
(c) Waste analysis records	35:050 § 4		✓	✓	
(d) Contingency plan implementation report	35:050 § 4		✓	✓	
(e) Inspection records	35:050 § 4		✓	✓	
(f) Groundwater monitoring records	35:050 § 4		✓	✓	
(g) Closure plan & cost estimate records	35:050 § 4		✓	✓	
5. TSD annual report submitted & maintained	35:050 § 6				

*All regulatory cites are from Title 401 of the Kentucky Administrative Regulations. The number preceeding the colon is the chapter reference. The number appearing after the colon is the regulation number. The symbol "§" is a reference to the section. For example, the reference to 32:010 § 3 should be read 401 KAR 32:010, Section 3.

VI. ATTACHMENTS: Container Facility Report ☐ Tank Facility Report ☐ Surface Impoundment Report ☐ Waste Pile Report ☐ Land Treatment Facility Report ☐ Landfill Report ☐ Incinerator Report ☐ Thermal Treatment Facility Report ☐ U I C Well Report ☐ Chemical, Physical & Biological Treatment Facility Report ☐

VII. GENERAL INFORMATION:

	YES	NO	N/A
1. Photographs taken?	☐	☒	☐
2. Samples collected?	☐	☒	☐
3. Previous non-compliances corrected?	☐	☒	☐

VIII. COMMENTS INCLUDING REMEDIAL MEASURES AND EXPECTED CORRECTION DATES:

Waste analysis [illegible] without [illegible] [illegible] pH, [illegible] & metals. No Part A permit filed with U.S. EPA. No copy of notice on site as required by 401 KAR 36:040, Section 13(3). No determination if still [illegible] [illegible] once per year to [illegible] [illegible] may be a [illegible]

INVESTIGATOR'S SIGNATURE [signature] **TITLE** Env. Inspector Sr.

I hereby acknowledge receipt of a copy of this report and further acknowledge that I have been advised of the discrepancies and alleged violations noted during the inspection.

OWNER'S or OPERATOR'S SIGNATURE [signature] **TITLE** Engineer

I do not [illegible] agreement [illegible] proceeding –

REFERENCE # 9

DIVISION OF WASTE MANAGEMENT
CERTIFICATE OF REGISTRATION

Kentucky Petroleum Waste, Inc.
4019 Blanton Lane
Louisville, Ky. 40216

The Division of Waste Management hereby issues the above-named installation a Certificate of Registration for the hazardous waste activity specified below. This Certificate is issued pursuant to KRS 224 and regulations issued pursuant thereto. This registration does not confer an unqualified right, but is subject to all applicable waste management provisions of KRS Chapter 224 and regulations promulgated pursuant thereto. Conformance with all such laws and regulations is the responsibility of the registrant. All rights of inspection by Division of Waste Management representatives are reserved.

Receipt of the registration fee specified below is hereby acknowledged.

COUNTY: Jefferson

REGISTRATION NUMBER: KYD06-156-4001

Not a facility

LEGAL STRUCTURE: Corporation

EFFECTIVE DATE: January 29, 1986

REGISTRATION FEE: N/A

Check TSD + Transporter

EXPIRATION DATE: N/A

ACTIVITY: Hazardous Waste Fuel Marketer
Off Specification Used Oil
Fuel Marketer

DATE OF ISSUE: May 9, 1986

DIRECTOR, DIVISION OF WASTE MANAGEMENT

Please print or type with ELITE type (12 characters per inch) in the unshaded areas only

Form Approved. OMB No. 2050-0028. Expires 9-30-88
GSA No. 0246-EPA-AF

United States Environmental Protection Agency
Washington, DC 20460

EPA Notification of Hazardous Waste Activity

Please refer to the *Instructions for Filing Notification* before completing this form. The information requested here is required by law (Section 3010 of the Resource Conservation and Recovery Act).

For Official Use Only

Comments

C/C

Installation's EPA ID Number	Approved	Date Received (yr. mo. day)
C/F: KYD061564001 T/A C/1		

I. Name of Installation

KY. PETROLEUM WASTE INC.

II. Installation Mailing Address

Street or P.O. Box

C/3: 4019 BLAWTOWN LANE

City or Town	State	ZIP Code
C/4: LOUISVILLE	KY.	40216

III. Location of Installation

Street or Route Number

C/5: 6911 GRADE LANE

City or Town	State	ZIP Code
C/6: LOUISVILLE	KY	40213

IV. Installation Contact

Name and Title (last, first, and job title)	Phone Number (area code and number)
C/2: SHIRCLIFF JAMES OWNER	502 447 8802

V. Ownership

A. Name of Installation's Legal Owner	B. Type of Ownership (enter code)
C/8: JAMES L. SHIRCLIFF	CORPORATION

VI. Type of Regulated Waste Activity (Mark 'X' in the appropriate boxes. Refer to instructions.)

A. Hazardous Waste Activity

- ☐ 1a. Generator
- ☐ 1b. Less than 1,000 kg/mo.
- ☒ 2. Transporter
- ☒ 3. Treater/Storer/Disposer
- ☐ 4. Underground Injection
- ☒ 5. Market or Burn Hazardous Waste Fuel (enter 'X' and mark appropriate boxes below)
  - ☐ a. Generator Marketing to Burner
  - ☒ b. Other Marketer
  - ☐ c. Burner

B. Used Oil Fuel Activities

- ☐ 6. Off-Specification Used Oil Fuel (enter 'X' and mark appropriate boxes below)
  - ☐ a. Generator Marketing to Burner
  - ☒ b. Other Marketer
  - ☐ c. Burner
- ☐ 7. Specification Used Oil Fuel Marketer (Or On-Site Burner) Who First Claims the Oil Meets the Specification.

VII. Waste Fuel Burning: Type of Combustion Device (enter 'X' in all appropriate boxes to indicate type of combustion device(s) in which hazardous waste fuel or off-specification used oil fuel is burned. See instructions for definitions of combustion devices.)

☐ A. Utility Boiler ☐ B. Industrial Boiler ☐ C. Industrial Furnace

VIII. Mode of Transportation (transporters only — enter 'X' in the appropriate box(es))

☐ A. Air ☐ B. Rail ☒ C. Highway ☐ D. Water ☐ E. Other (specify)

IX. First or Subsequent Notification

Mark 'X' in the appropriate box to indicate whether this is your installation's first notification of hazardous waste activity or a subsequent notification. If this is not your first notification, enter your installation's EPA ID Number in the space provided below.

☐ A. First Notification ☒ B. Subsequent Notification (complete item C)

C. Installation's EPA ID Number: KYD061564001

EPA Form 8700-12 (Rev. 11-85) Previous edition is obsolete.

Continue on reverse

RECEIVED
JAN 29 4 40 PM '86
LOUISVILLE WASTE MGT.

ID — For Official Use Only

C W | T/A | C 1

IX. Description of Hazardous Wastes (continued from front)

A. Hazardous Wastes from Nonspecific Sources. Enter the four-digit number from 40 CFR Part 261.31 for each listed hazardous waste from nonspecific sources your installation handles. Use additional sheets if necessary.

1	2	3	4	5	6
7	8	9	10	11	12

B. Hazardous Wastes from Specific Sources. Enter the four-digit number from 40 CFR Part 261.32 for each listed hazardous waste from specific sources your installation handles. Use additional sheets if necessary.

13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30

C. Commercial Chemical Product Hazardous Wastes. Enter the four-digit number from 40 CFR Part 261.33 for each chemical substance your installation handles which may be a hazardous waste. Use additional sheets if necessary.

31	32	33	34	35	36
37	38	39	40	41	42
43	44	45	46	47	48

D. Listed Infectious Wastes. Enter the four-digit number from 40 CFR Part 261.34 for each hazardous waste from hospitals, veterinary hospitals, or medical and research laboratories your installation handles. Use additional sheets if necessary.

49	50	51	52	53	54

E. Characteristics of Nonlisted Hazardous Wastes. Mark 'X' in the boxes corresponding to the characteristics of nonlisted hazardous wastes your installation handles. (See 40 CFR Parts 261.21 — 261.24)

☐ 1. Ignitable (D001) ☐ 2. Corrosive (D002) ☐ 3. Reactive (D003) ☒ * 4. Toxic (D000)

X. Certification

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this and all attached documents, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

Signature	Name and Official Title (type or print)	Date Signed
James L. Shircliff	JAMES SHIRCLIFF OWNER	1/29/86

EPA Form 8700-12 (Rev. 11-85) Reverse

BILLING CODE 6560-50-C

RECEIVED

* THE ONLY THING I DEAL IN IS USED OILS.

REFERENCE # 10

Kentucky Natural Resources and Environmental Protection Cabinet
Department for Environmental Protection
Division of Waste Management

CERTIFICATE OF REGISTRATION FOR HAZARDOUS WASTE MANAGEMENT ACTIVITY

INSTALLATION NAME: Kentucky Petroleum Waste, Inc.
MAILING ADDRESS: 6911 Grade Lane, Louisville, Kentucky 40213
LOCATION: 6911 Grade Lane, Louisville, Kentucky 40213
CONTACT PERSON: Beverly Coffman

☐ NEW ☐ AMENDED/MODIFIED ☒ RENEWAL ☐ REISSUED

The Division of Waste Management hereby issues the above-named installation a Certificate of Registration for the hazardous waste activity specified below. This Certificate is issued under the provisions of KRS Chapter 224 and regulations promulgated pursuant thereto. Conformance with all applicable laws and regulations is the responsibility of the registrant. All rights of inspection by representatives of the Division of Waste Management are reserved. Receipt of the registration fee specified below is hereby acknowledged.

This Certificate supercedes all previous Certificates of Registration.

COUNTY/STATE: Jefferson/KY
LEGAL STRUCTURE: P
REGISTRATION FEE: $600.00
WASTESTREAMS: N/A

REGISTRATION NUMBER: KYD-061-564-001
EXPIRATION DATE: January 31, 1991
ACTIVITY: Other Off-Spec. Used Oil Fuel Marketer
Off-Spec. Used Oil Fuel Burner
Spec. Used Oil Fuel Marketer

Issued and effective this 19th day of January 1990

Susan C. Bush
Susan C. Bush, Director

Arthur L. Williams
Arthur L. Williams, Commissioner

DEP7019 (10/88)

Printed on Recycled Paper

Please type or print clearly in ink (Do not use pencil.) DEP-7050 (effective November 1989)

Kentucky Natural Resources and Environmental Protection Cabinet
Department for Environmental Protection - Division of Waste Management

Annual Registration of Hazardous Waste Activity

18 Reilly Road - Frankfort, Kentucky
(502) 564-6716

DEC 8 8 12 AM '89

See attached INSTRUCTIONS to complete this form.

☐ FEE SUBMITTED: $ 600.00

FOR OFFICIAL USE ONLY: Receipt No. 010119 Date: 1/15/90

DO NOT WRITE IN THIS SPACE

I. GENERAL INFORMATION

KENTUCKY PETROLEUM WASTE, INC.
KYD061564001 00
~~SHINCLIFF~~ ~~CHARLES R~~ Coffman Beverly
6911 GRADE LANE
LOUISVILLE KY 40213

KENTUCKY PETROLEUM WASTE, INC.
KYD061564001 00
5023677766
6911 GRADE LANE
LOUISVILLE 40213

A. CORRECTIONS TO FIRST LABEL:

EPA ID Number: Same
Contact Person: Coffman Beverly
Mailing Address: Same

B. CORRECTIONS TO SECOND LABEL:

EPA ID Number:
Name:
Location:
Phone Number:

C. County: Jefferson *Important see INSTRUCTIONS:* Latitude: 38° 08' 58" Longitude: 85° 44' 08"
D. Name of Installation's Legal Owner: Kentucky Petroleum Waste Inc.
E. Type of Ownership Code: P *(see INSTRUCTIONS for the correct codes)*

II. TYPE OF REGULATED ACTIVITY

Enter an "X" in every applicable box.

mgf ☒ 1a. Full Quantity Generator *(over 2200 pounds/month or over 1000 kg/month)*
☐ 1b. Small Quantity Generator *(between 220 and 2200 pounds/month or between 100 and 1000 kg/month)*
☐ 1c. Limited Quantity Generator *(under 220 pounds/month or under 100 kg/month every month)*
Identify the type of on-site accumulation : ☐ Containers ☐ Tank(s) ☐ Containers & Tank(s)

Complete this section only if you transport your own waste.
☐ 2. Transporter: ☐ Air ☐ Rail ☐ Highway ☐ Water ☐ Other:

mgf ☒ 3a. Treatment / Storage / Disposal Facility
☐ 3b. Underground Injection Well

☐ 4a. Generator Marketing Hazardous Waste Fuel to a Burner *(see 401 KAR 36:040)*
☐ 4b. Other Hazardous Waste Fuel Marketer
☐ 4c. Hazardous Waste Fuel Burner: ☐ Utility Boiler ☐ Industrial Boiler ☐ Industrial Furnace
Source of Waste Fuel Being Burned: ☐ Generated On-Site Exclusively ☐ Received From Off-Site
☐ 5a. Generator Marketing Off-Specification Used Oil Fuel to a Burner *(see 401 KAR 36:050)*
☑ 5b. Other Off-Specification Used Oil Fuel Marketer
☑ 5c. Off-Specification Used Oil Fuel Burner: ☐ Utility Boiler ☑ Industrial Boiler ☐ Industrial Furnace
Source of Used Oil Being Burned: ☐ Generated On-Site Exclusively ☐ Received From Off-Site
☑ 5d. Specification Used Oil Fuel Marketer (or On-site Burner) Who First Claims the Oil Meets Specification

☐ 6. Lead Acid Battery Recycler *(see 401 KAR 36:030)*
☐ 7. Precious Metals Recycler *(i.e., Silver Recovery - see 401 KAR 36:060)*
☐ 8. Other Recycler *(401 KAR 31:010, Section 6 - specify)*

III. SOURCE OF ANY WASTE BEING MANAGED AT THIS LOCATION: *Refer to INSTRUCTIONS.*

☐ Generated On-Site Exclusively ☑ Received from Off-Site
Is this site a commercial facility? ☑ Yes ☐ No

IV. DESCRIPTION OF HAZARDOUS WASTES

EPA ID Nur r:

A. Description of Waste (List all current wastestreams)	B. EPA Waste Numbers	C. Physical State	D. Maximum Amount of Waste In Calendar Month	E. Estimated Annual Quantity of Waste	F. Unit
G. TOTALS →					

V. COMMENTS

VI. CERTIFICATION - I certify under penalty of law that I have personally examined and am familiar with the information submitted in this and all attached documents, and that based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

Signature	Name and Official Title (Type or print)	Date Signed
Beverly Coffman	Plant Manager	12-5-89

NUS CORPORATION AND SUBSIDIARIE.	REFERENCE # 11	TELECON NOTE
CONTROL NO.	**DATE:** December 17, 1990	**TIME:** 1650

DISTRIBUTION:

Kentucky Petroleum Products
(Kentucky Petroleum Waste, Inc.)
Louisville, Kentucky

BETWEEN: Christie Harrington	**OF:** RCRA Hazardous Waste Permitting	**PHONE:** 502-564-6716

AND: Wendell C. McLendon, NUS Corporation

DISCUSSION:

Kentucky Petroleum Waste is permitted as a marketer of off-spec oil and spec oil and as a burner of off-spec oil. They are not a generator or a TSD facility. They do not have an active enforcement case at this time.

ROBER
SEC

REFERENCE # 12

JULIAN M. CARROLL
GOVERNOR

COMMONWEALTH OF KENTUCKY
DEPARTMENT FOR NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION
BUREAU OF ENVIRONMENTAL PROTECTION
JOHN A. ROTH
COMMISSIONER
FRANKFORT, KENTUCKY 40601

March 22, 1978

Mr. Leo Shircliffe
Kentucky Petroleum Products
4019 Blanton Lane
Louisville, Kentucky

Dear Mr. Shircliffe:

On Thursday, March 9, 1978, Steve Shannon witnessed the unauthorized deposition of approximately one thousand gallons of waste oil into the working face of Mobile Waste landfill site - by a tank-truck drive from Kentucky Petroleum Products Company. Kentucky Administrative Regulations - governing the disposal of waste - prohibit the discharge of liquids into a landfill without special permission (KAR 2:010; Section 11 (4)).

There are no special permissions issued by this department for the disposal of waste oil in this manner. Waste Oil may be recovered or incinerated. It is useful in road oiling as a dust control measure during dry weather. But disposal in the manner Mr. Shannon and I observed is unlawful, un-necessary, and if the practice is continued may subject your company to economic penalties of $1,000.00 or more.

If you are not aware of the legal alternatives in waste oil, I will be glad to discuss them with you and provide the information, both technical and with respect to local oil disposal operations, that is available to this office.

Please feel free to contact me at (502) 564-6716.

Sincerely,

Robert L. Sholar

Robert L. Sholar
Environmental Specialist I
Hazardous Mateial Management Section
Division of Hazardous Materials and
Waste Management

RS:cjg

REFERENCE # 13

CHARLC
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-681
SA No: 84-541

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director SB for WEO
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1110

Sample Identification: Waste Oil Tank # 6

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

ts:

METER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	56.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	1,600.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	80.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-682
SA No: 84-542

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1115

Sample Identification: Waste Oil Tank # 7

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	18.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	26.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	21.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-683
SA No: 84-543

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1120

Sample Identification: Waste Oil Tank # 8

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	190.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	10.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	42.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-684
SA No: 84-544

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director WEB for WED
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1125

Sample Identification: Waste Oil Tank # 9

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	190.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	5.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	22.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-685
SA No: 84-545

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director *WED for*
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1130

Sample Identification: Waste Oil Tank # 10

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	230.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	22.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	2000.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-686
SA No: 84-546

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1135

Sample Identification: Waste Oil Tank # 11

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	480.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	21.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	4700.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-687
SA No: 84-547

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director *WED for*
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1140

Sample Identification: Waste Oil Tank # 12

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	85.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	4.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	94.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-688
SA No: 84-548

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste, Inc.
Louisville, Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director
Environmental Services

DATE: March 13, 1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1145

Sample Identification: Waste Oil Tank # 13

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	25.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	1.1
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	16.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-676
SA No: 84-536

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director SB for WED
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1045

Sample Identification: Hydrolic Oil Tank

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	640.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	110.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	770.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-677
SA No: 84-537

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director *WB for WED*
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1050

Sample Identification: Crude Oil Tank

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	19.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	15.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	70.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-678
SA No: 84-538

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director SB for WED
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1055

Sample Identification: Crude Oil Tank

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	15.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	19.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	27.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-679
SA No: 84-539

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director SB for WED
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1100

Sample Identification: Waste Oil Tank # 4

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	81.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	<1.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	104.
Chlorobenzene	<1.

CHARLOTTE E. BALDWIN
SECRETARY

MARTHA LAYNE COLLINS
GOVERNOR

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL PROTECTION CABINET
DEPARTMENT FOR ENVIRONMENTAL PROTECTION
FORT BOONE PLAZA
18 REILLY ROAD
FRANKFORT, KENTUCKY 40601

Report No: B02-680
SA No: 84-540

TO: Division of Waste Management
#18 Reilly Road, Fort Boone Plaza
Frankfort, Kentucky 40601

Re: Kentucky Petroleum
Waste,Inc.
Louisville,Ky.

ATTN: Carl Horneman

FROM: William E. Davis, Director *WED for*
Environmental Services

DATE: March 13,1984

Sample Collector: Mildred Archer Date: 02/29/84 Time: 1105

Sample Identification: Waste Oil Tank # 5

REPORT OF ANALYSIS

Date:
Received: 02/29/84 Started: 02/29/84 Finished: 03/08/84

Results:

PARAMETER	CONCENTRATION (mg/kg)
Hexachlorobenzene	<1.0
Hexachlorocyclohexane, alpha isomer	<1.0
Hexachlorocyclohexane, gamma isomer	<1.0
Heptachlor	<1.0
Aldrin	<1.0
Heptachlor Epoxide	<1.0
t-Chlordane	<1.0
c-Chlordane	<1.0
O,P'-DDE	<1.0
P,P'-DDE	<1.0
Dieldrin	<1.0
Endrin	<1.0
O,P'-DDD	<1.0
P,P'-DDD	<1.0

O,P'-DDT	<1.0
P,P'-DDT	<1.0
Total DDT	<1.0
Methoxychlor	<1.0
Mirex	<1.0
Endosulfan I	<1.0
Endosulfan II	<1.0
Endosulfan Sulfate	<1.0
Endrin Aldehyde	<1.0
Endrin Ketone	<1.0
Toxaphene	<1.0
Technical Chlordane	<1.0
Aroclor 1016	<1.0
Aroclor 1221	<1.0
Aroclor 1232	<1.0
Aroclor 1242	<1.0
Aroclor 1248	<1.0
Aroclor 1254	<1.0
Aroclor 1260	<1.0
Aroclor 1262	<1.0
Aroclor 1268	<1.0
Methylene Chloride	<1.
1,2-Dichloroethene	<1.
Chloroform	<1.
1,2-Dichloroethane	<1.
1,1,1-Trichloroethane	117.
Carbon Tetrachloroide	<1.
Bromodichloromethane	<1.
Trichloroethene	<1.
1,2-Dichloropropane	<1.
Dibromochloromethane	<1.
Chloroethyvinyl ether	<1.
Bromoform	<1.
Tetrachloroethene	170.
Chlorobenzene	<1.

REFERENCE # 14

COMMONWEALTH OF KENTUCKY
NATURAL RESOURCES AND ENVIRONMENTAL
PROTECTION CABINET

FILED

OCT 03 1988

DIVISION OF HEARINGS

IN THE MATTER OF:

Kentucky Petroleum Waste, Inc.
6911 Grade Lane
Louisville, Kentucky 40213
KYD06-156-4001

AGREED ORDER WM87-059C

* * * * * * * * * * * * * * * *

Statements of Fact

1. The Natural Resources and Environmental Protection Cabinet (hereinafter the Cabinet) is charged with the statutory duty of enforcing the laws of the Commonwealth of Kentucky relating to waste management under KRS Chapter 224;
2. Kentucky Petroleum Waste, Inc., (hereinafter the Firm) operates a pertroleum recycling plant in Louisville, Kentucky, for the production of fuels for industrial uses from both new and used petroleum products;
3. The Firm registered as a Hazardous Waste Fuel Marketer and Off Specification Used Oil Fuel Marketer effective January 29, 1986;
4. The Firm amended its registration to include the following categories:
   A. Recycler;
   B. Off Specification Used Oil Fuel Marketer and Burner; and
   C. Specification Used Oil Fuel Marketer effective June 1, 1987;
5. An inspection conducted July 7, 1986, revealed the Firm to be in violation of standards applicable to Used Oil Fuel Marketers and Burners as follows:
   A. The Firm failed to provide invoices for shipment of off specification used oil to the receiving facility in violation of 401 KAR 36:050, Section 4(2)(d);

B. The Firm failed to provide copies of the notices required to burners and other marketers in violation of 401 KAR 36:050, Section 4(2)(e); and

C. The Firm failed to maintain a record of the analysis used to make the determination of whether the used oil fuel was specification or off-specification in violation of 401 KAR 36:050, Section 4(2)(f).

NOW, THEREFORE, in the interest of settling all claims and controversies involving these matters, the Natural Resources and Environmental Protection Cabinet and Kentucky Petroleum Waste, Inc., hereby consent to entry of this AGREED ORDER and agree as follows:

1. The above statements of fact are true and correct.

2. By August 15, 1988, the Firm shall submit to the Division a sample copy of the invoice it sends to the receiving facility when initiating a shipment of off-specification used oil as required by 401 KAR 36:050, Section 4(d).

3. The Firm shall send each receiving facility an invoice with each shipment of off-specification used oil in compliance with 401 KAR 36:050, Section 4(d).

4. By August 15, 1988, the Firm shall submit to the Division a sample copy of the notices required by 401 KAR 36:050, Section 4(e).

5. The Firm shall comply with the requirements that notices be obtained from burners or other marketers before initiating the first shipment of off-specification used oil in compliance with 401 KAR 36:050, Section 4(e).

6. By August 15, 1988, the Firm shall submit to the Division copies of the analyses for the time period June 1, 1987, through May 31, 1988, used to make the determination that its used oil fuel meets the specification as required by 401 KAR 36:050, Section 4(f).

7. The Firm shall maintain all records required by 401 KAR 36:050, Section 4(f) for three years and shall comply with all other recordkeeping requirements of 401 KAR 36:050, Section 4(f) not otherwise specified in this ORDER.

8. By August 15, 1988, the Firm shall submit a plan to the Division outlining procedures it shall follow to prevent its acceptance of hazardous waste mixed with oil picked up from its customers. The plan shall contain a schedule for implementation of the procedures outlined therein.

9. The Firm shall implement the plan upon approval by the Division.

10. Kentucky Petroleum Waste, Inc., shall pay a civil penalty of Five Hundred Dollars ($500) by certified check, cashier's check, or money order payable to "Kentucky State Treasurer" and submitted to the Docket Coordinator, Division of Hearings, Natural Resources and Environmental Protection Cabinet, Capital Plaza Tower, Frankfort, Kentucky 40601 within twenty (20) days of execution of this ORDER.

11. This AGREED ORDER or any of its provisions, conditions or dates contained herein may be amended, modified, deleted or extended only upon a written request stating the reasons therefor; and by the approval and written Order of the Secretary or his designee. Any such amendment, modification, deletion or extension shall not affect any other provision, condition or date within the AGREED ORDER unless specifically and expressly so provided by the written Order.

12. This AGREED ORDER addresses only those violations specifically set out or referred to in this AGREED ORDER and nothing contained herein shall be construed to waive or limit any remedy or cause of action of the Cabinet based on violations of other laws or regulations under the jurisdiction of the Cabinet.

13. Strict compliance with all the terms of this AGREED ORDER shall be considered as a satisfactory resolution of the violations of KRS Chapter 224 specifically set out in this ORDER.

14. Failure of Kentucky Petroleum Waste, Inc., to comply strictly with the terms of this AGREED ORDER shall be grounds for the Cabinet to seek enforcement of this ORDER as well as penalties for its violation and any appropriate administrative or judicial action under KRS Chapter 224.

15. Each separate provision, condition or duty contained herein may be the basis for an enforcement action for a separate violation and penalty pursuant to KRS Chapter 224, upon failure of Kentucky Petroleum Waste, Inc., to comply strictly with the terms of this ORDER.

16. Kentucky Petroleum Waste, Inc., waives its rights to a formal hearing to contest the violations alleged herein.

17. This AGREED ORDER shall be of no force or effect unless and until it is executed by the Secretary or his designee as evidenced by his signature thereon. Should this Order contain any date by which the Defendant is to take any action, and should the Secretary sign the Order after that date, then the Defendant is nonetheless obligated to have taken the action by the date contained in this Order.

AGREED TO BY:

Authorized Representative
Kentucky Petroleum Waste, Inc.

8-29-88
Date

Donald F. Harker, Director
Division of Waste Management

9/1/88
Date

James T. Corum, D.M.D., M.P.H.
Commissioner
Department for Environmental Protection

9-14-88
Date

Attorney, Office of General Counsel

9/22/88
Date

Arthur L. Williams, Acting General Counsel
Office of General Counsel

9/23/88
Date

****

ORDER

WHEREFORE, the Secretary or his designee, taking cognizance of the agreement of the parties as evidenced herein, does hereby order that the foregoing AGREED ORDER be, and is hereby entered as the final Order of this Natural Resources and Environmental Protection Cabinet this 29 day of Sept., 1988.

Carl H. Bradley, Secretary
Natural Resources and
Environmental Protection Cabinet

CERTIFICATE OF SERVICE

I hereby certify that a true and accurate copy of the foregoing AGREED ORDER was mailed, pre-paid, to the following this the 3rd day of October, 1988.

Kentucky Petroleum Waste, Inc.
6911 Grade Lane
Louisville, Kentucky

Rita A. Hardin
DOCKET COORDINATOR

DISTRIBUTION:

Division of Waste Management
Order File
Attorney, Office of General Counsel – Hon. Robert Yarbrough

This Copy to Main file
Addional Copies to:
Louisville R.O.
Lou Martin
Enforcement file (C80)
U.S. EPA

AVAILABILITY

OF

GROUND WATER FOR DOMESTIC USE

IN

JEFFERSON COUNTY, KENTUCKY

By L. M. MacCary

1956

IN

JEFFERSON COUNTY, KENTUCKY

By L. M. MacCary

1956

DEPARTMENT OF THE INTERIOR
UNITED STATES GEOLOGICAL SURVEY

HYDROLOGIC INVESTIGATIONS ATLAS HA 8

Prepared in cooperation with the State of Kentucky Agricultural and Industrial Development Board

For sale by the U. S. Geological Survey
Washington 25, D. C.—Price 75 cents



MAP OF JEFFERSON COUNTY, KENTUCKY, SHOWING THE AVAILABILITY OF GROUND WATER TO DRILLED WELLS, DEPTH OF WELL, AND DEPTH TO WATER

INTRODUCTION

This atlas showing the availability of ground water for domestic use in Jefferson County, Ky., is presented to make ground-water information available to residents and drillers of the region. Because the cost of drilling a domestic well is several dollars a foot, it is advantageous to both driller and owner to know the probability of success of a well before drilling is begun. The map and tables will make it possible to estimate the chances of success of a drilled domestic well anywhere in the county.

Jefferson County borders the Ohio River in the north-central part of Kentucky and covers an area of 394 square miles. Louisville, the county seat, is the largest city in the State. Many good Federal and State highways traverse the county and hard-surfaced rural roads make most of the region accessible in all weather conditions.

SURFACE FEATURES

Jefferson County lies on the west flank of the Cincinnati arch, a major structural feature within the Interior Low Plateaus physiographic province (Fenneman, 1938). The topography of the area ranges from nearly flat to fairly rugged. The eastern part of the county is drained by Floyds Fork, and the rest of the county by smaller tributaries of the Ohio River. The physiographic units, based on topography and geology, include the Outer Blue Grass, Muscatatuck regional slope, Scottsburg lowland, and Knobs. The Muscatatuck regional slope and the Scottsburg lowland are subdivisions of the Outer Blue Grass, but they are treated as separate units in this report. The alluvial terraces along the Ohio River constitute a fifth physiographic subdivision.

That part of the county lying east of a line through Thixton, Jeffersontown, and Avoca is in the Outer Blue Grass. This dissected area, a part of the Lexington peneplain, is underlain by shale and limestone of Late Ordovician age. To the west the Outer Blue Grass grades into the Muscatatuck regional slope, a rolling surface developed on Silurian and Devonian limestones. Along a line connecting Okolona, [illegible] and Louisville the regional slope merges with the Scottsburg lowland, a plain of low relief which is underlain by shale of Late Devonian age. West and south of the lowland lies the Knobs, a highly dissected area developed on shale, sandstone, and limestone of Mississippian age. The eastern edge of this upland forms the so-called Knobstone escarpment.

The alluvial terraces along the Ohio River form a distinct physiographic unit. The river has carved a deep, wide channel through rocks ranging in age from Ordovician to Mississippian. Throughout nearly all its length in Jefferson County the river flows on glacial outwash, which has filled the old channel to a depth of 100 feet or more. The only exception to this is at the Falls of the Ohio where the river flows on exposed bedrock of Devonian age.

AVAILABILITY OF GROUND WATER

The occurrence of ground water in Jefferson County is controlled by several factors among which the nature of the openings in the rocks and the westerly regional dip are of prime importance. Limestone, sandstone, and shale make up the bulk of the consolidated rocks. Limestone may transmit large amounts of water through openings along joints and bedding planes enlarged by solution. Sandstone may transmit water through openings along bedding planes and joints and also through intergranular pores. Shale beds are important, not generally as water carriers, but because they may impede the upward or downward motion of water from other beds. Large quantities of ground water move through the intergranular openings in the unconsolidated sand and gravel of the alluvium (glacial outwash) along the Ohio River. Ground water moves in the bedrocks westward down the regional dip, and to some extent northward or northwestward across the dip, to discharge into the alluvium and thence to the Ohio River.

Except in the area of alluvial terraces along the Ohio River, about half the wells drilled in Jefferson County are failures as sources of household water supplies, because they either yield salty or sulfurous water or do not yield enough water. The following discussion explains the chances of obtaining a successful well in each of the physiographic subdivisions of the county. These subdivisions are outlined and numbered on plate 1. The water-bearing properties of the rock formations in the county are summarized in table 1; information on individual wells and springs is presented in tables 2 and 3; table 4 lists chemical analyses of water from some typical wells and springs; and figure 1 shows graphically the results of these analyses.

Area 1--Outer Blue Grass

The Outer Blue Grass, which includes about one-fifth the area of the county along the eastern boundary, is underlain by shale and limestone of Late Ordovician age. The shale beds total about 150 feet in thickness and erode to produce ridges separated by relatively broad, flat stream valleys.

enough fresh water for household use. One spring in the Sellersburg limestone formerly served 11 tenant houses and a dairy barn but is now abandoned because a municipal water supply has become available.

Area 3--Scottsburg Lowland

The Scottsburg lowland, which includes a small area in the south-central part of the county, offers a better chance for a successful drilled well than the Outer Blue Grass but not so good as the Muscatatuck regional slope. Of the 12 drilled wells inventoried in the lowland, 6 produced enough fresh water for household use and 6 produced salty or sulfurous water.

The New Albany shale, a black fissile carbonaceous shale about 100 feet thick, underlies almost the entire lowland. It is probable that water obtained in wells comes from openings along fractures in the shale. According to one driller, wells can be obtained to depths as great as 40 feet. Below this depth openings in the shale are very small and no water or only a little salty or sulfurous water is generally obtained. The water in some of the wells contains enough iron to stain laundry and bathroom fixtures.

Because of the poor drainage in the tight shale, the water table during wet seasons stands within a few feet of the surface in much of the lowland area. Failure of septic tanks to function properly is common in this area.

Area 4--Knobs

The Knobs, a region of ridges, spurs, and knobs, is a small area in the southwestern part of the county. Some of the ridges are flat-topped, owing to a capping of thin but resistant limestones and sandstones. The typical knobs develop where these resistant caps are small or missing. The chances of obtaining a successful drilled well are about the same in the Knobs as in the Scottsburg lowland. However, the topography and geology of the Knobs are much more varied, and the chances of obtaining a successful well in some parts of the upland are much better than in other parts. Of 13 drilled wells inventoried in the Knobs, 8 produced enough fresh water for domestic use.

The New Providence shale, a soft green shale about 150 feet thick, crops out in the lower parts of the Knobs, especially along the eastern and northern boundaries where it merges with the Scottsburg lowland. A few successful wells were found in the outcrop area of the New Providence shale, but it is probable that less than half the wells drilled will be successful. The shale slakes readily and thus has a tendency to fill up any uncased hole in the formation.

The Kenwood sandstone, consisting of 40 feet of fine-grained gray to brown sandstone alternating with shale, caps a few of the knobs and low hills and crops out along the sides of the higher ridges. It yields water to a few wells in its outcrop area.

The Rosewood shale, a blue-gray siliceous shale about 190 feet thick, crops out in the southwestern third of the Knobs. A few successful wells have been obtained in the Rosewood shale in its outcrop area.

The Holtsclaw sandstone, a thick-bedded fine-grained blue-gray sandstone, is only 20 feet thick and crops out as a very narrow band near the top of the highest ridges in the Knobs. It probably yields some water to wells that are drilled into it through the overlying Warsaw limestone.

The Warsaw limestone is a fine-grained siliceous, argillaceous limestone containing geodes and chert. This 65- to 80-foot limestone caps the highest ridges in the Knobs. Some of the wells drilled on top of these ridges probably obtain water from the limestone and some from the underlying Holtsclaw sandstone.

Area 5--Ohio River Alluvial Terraces

The alluvial terraces on the Ohio River along the northwest boundary of the area include about one-fifth of the county. Almost every well drilled in the alluvium yields enough water of a quality satisfactory for household use. The water is generally hard, but can be softened for household use by commercial softeners.

Most of the wells in this area obtain water from the alluvium, but some industrial wells produce from the limestone bedrock beneath the alluvial sand and gravel. In 1952 about 25 million gallons of water per day was pumped from the alluvium for industrial use. Yields of about 100 gpm are average for industrial users and yields of more than 500 gpm are not uncommon.

The ground water conditions in this area have been described in detail by Rorabaugh (1946, 1956) and Rorabaugh, Schrader, and Laird (1953).

SELECTED BIBLIOGRAPHY

Butts, Charles, 1915, Geology and mineral resources of Jefferson County, Ky.: Ky. Geol. Survey, ser. 4, v. 3, 270 p.

Fenneman, N. M., 1938, Physiography of Eastern United States: New York, McGraw-Hill Book Co., Inc., 714 p.

Rorabaugh, M. I., 1946, Ground-water resources of the southwestern part of the Louisville area, Kentucky: Rubber Reserve Company, City of Louisville, and Jefferson County (duplicated rept.).

——1956, Ground-water resources of the northeastern part of the Louisville area, Kentucky: U. S. Geol. Survey Water-Supply Paper 1360-B.

Rorabaugh, M. I., Schrader, F. F., and Laird, L. B., 1953, Water resources of the Louisville area, Kentucky and Indiana: U. S. Geol. Survey Circ. 276.

Table 1.—Water-bearing formations in Jefferson County, Ky.

System	Series	Group	Formation	Thickness (feet)	Character of material	Water-bearing properties

coarse-grained light- to dark-gray li... about 20 feet thick. Above it is the Sellersburg limestone, a 14-foot limestone of variable character. These two limestones cap the highland areas in the northern part of the county and descend to valley level in places along the border of the Ohio River alluvial terraces. About 3 of 4 wells drilled in these limestones produce



ing quality of water by formation in Jefferson County

of fine-grained gray to brown sandstone alternating with shale, caps a few of the knobs and low hills and crops out along the sides of the higher ridges. It yields water to a few wells in its outcrop area.

Table 1.—Water-bearing formations in Jefferson County, Ky.

System	Series	Group	Formation	Thickness (feet)	Character of material	Water-bearing properties
Quaternary	Recent		Alluvium		Soil, clay, fine sand.	Not important as an aquifer.
	Pleistocene		Alluvium of glacial-outwash origin along the Ohio River	0-130	Gravel, sand, and clay deposited in the buried valley of the Ohio River.	Stores large quantities of fresh water. Yields of 100 to 500 gpm are common.
Mississippian		Meramec	Warsaw limestone	65-80	Fine-grained limestone with geodes and chert, siliceous and argillaceous. Some shale.	Yield some water to ridge-top wells.
		Osage	Holtsclaw sandstone	15-25	Fine-grained sandstone, thick-bedded, soft.	
			Rosewood shale	190	Bluish shale with thin lenses of limestone.	Not commonly a source of water.
			Kenwood sandstone	40	Thin beds of fine-grained greenish sandstone in bluish shale.	Yields some water to domestic wells.
			New Providence shale	150-160	Soft clay shale, green or bluish.	Not commonly a source of water.
Devonian	Upper		New Albany shale	90-100	Black shale, carbonaceous and fissile.	Yields water from openings along fractures. Water generally has high iron content.
	Middle		Sellersburg limestone	12-24	Light-gray limestone, thick bedded; upper bed coarse grained; lower bed fine grained	Yield fresh water to wells in uplands. Springs occur along the contact between these limestones.
			Jeffersonville limestone	20-25	Coarse-grained dark-gray limestone, thick bedded	
Silurian	Niagara		Louisville limestone	40-100	Fine-grained thick-bedded dolomitic limestone.	Yields fresh water over most of its outcrop area.
			Waldron shale	8-12	Greenish shale, calcareous and magnesian.	Does not produce water. Impedes upward or downward movement of water.
			Laurel dolomite	30-40	Fine-grained dolomite, medium thick bedded.	Generally yields salty or sulfurous water. Many holes are dry.
			Osgood formation	22-30	Thick limestone bed with underlying bed of shale.	Forms spring horizon in many localities.
			Brassfield limestone	3-7	Coarsely crystalline limestone.	Not important as an aquifer owing to small thickness.
Ordovician	Cincinnatian	Richmond	Saluda limestone	30-40	Fine-grained limestone, thick bedded, magnesian.	Yields water to ridge-top wells.
			Liberty formation	36-50	Alternating shale and thin limestone.	Not commonly a source of ground water. Salty or sulfurous water occurs at shallow depths. Many holes are dry.
			Waynesville limestone	40-50	Thick-bedded limestone; shale at top and bottom.	
			Arnheim formation	80-100	Thin limestone interbedded with shale.	

WELL-NUMBERING SYSTEM USED IN JEFFERSON COUNTY

Jefferson County lies between 85°24' and 85°57' west longitude and 38°00' and 38°22' north latitude. The area has been subdivided by a grid of 1-minute meridians of longitude and 1-minute parallels of latitude. The wells and springs in each of these quadrangles are numbered, beginning with 1, in the order inventoried. A well is designated by a composite of three numbers: the first indicates the minute of longitude at the south edge of the quadrangle; the second, the minute of latitude at the east edge; and the third, the number of the well in that quadrangle. Thus, well 39-05-1 is the first well inventoried in the 1-minute quadrangle west of longitude 85°39' W. and north of latitude 38°05' N. The complete number is shown in the table; only the third part of the number is shown on the map.

REFERENCE # 16

EPA-600/2-87-035
April 1987

DRASTIC: A Standardized System for Evaluating Ground Water Pollution Potential Using Hydrogeologic Settings

by

Linda Aller
Truman Bennett
Jay H. Lehr
Rebecca J. Petty
and
Glen Hackett
National Water Well Association
Dublin, Ohio 43017

Cooperative Agreement CX-810715-01

Project Officer
Jerry Thornhill
Applications and Assistance Branch
Robert S. Kerr Environmental Research Laboratory
Ada, Oklahoma 74820

ROBERT S. KERR ENVIRONMENTAL RESEARCH LABORATORY
OFFICE OF RESEARCH AND DEVELOPMENT
U.S. ENVIRONMENTAL PROTECTION AGENCY
ADA, OKLAHOMA 74820

6. NONGLACIATED CENTRAL GROUND-WATER REGION



6A	Mountain Slopes
6B	Alluvial Mountain Valleys
6C	Mountain Flanks
6Da	Alternating Sandstone, Limestone and Shale - Thin Soil
6Db	Alternating Sandstone, Limestone and Shale - Deep Regolith
6E	Solution Limestone
6Fa	River Alluvium With Overbank Deposits
6Fb	River Alluvium Without Overbank Deposits
6G	Braided River Deposits
6H	Triassic Basins
6I	Swamp/Marsh
6J	Metamorphic/Igneous Domes and Fault Blocks
6K	Unconsolidated and Semi-consolidated Aquifers

6. NONGLACIATED CENTRAL REGION

(Thin regolith over fractured sedimentary rocks)

The nonglaciated Central region is an area of about 1,737,000 km^2 extending from the Appalachian Mountains on the east to the Rocky Mountains on the west. The part of the region in eastern Colorado and northeastern New Mexico is separated from the remainder of the region by the High Plains region. The Nonglaciated Central region also includes the Triassic Basins in Virginia and North Carolina and the "driftless" area in Wisconsin, Minnesota, Iowa, and Illinois where glacial deposits, if present, are thin and of no hydrologic importance. The region is a topographically complex area that ranges from the Valley and Ridge section of the Appalachian Mountains on the east westward across the Great Plains to the foot of the Rocky Mountains. It includes, among other hilly and mountainous areas, the Ozark Plateaus in Missouri and Arkansas. Altitudes range from 150 m above sea level in central Tennessee and Kentucky to 1,500 m along the western boundary of the region.

The region is also geologically complex. Most of it is underlain by consolidated sedimentary rocks that range in age from Paleozoic to Tertiary and consist largely of sandstone, shale, carbonate rocks (limestone and dolomite), and conglomerate. A small area in Texas and western Oklahoma is underlain by gypsum. Throughout most of the region the rock layers are horizontal or gently dipping. Principal exceptions are the Valley and Ridge section of the Wichita and Arbuckle Mountains in Oklahoma, and the Ouachita Mountains in Oklahoma and Arkansas, in all of which the rocks have been folded and extensively faulted. Around the Black Hills and along the eastern side of the Rocky Mountains the rock layers have been bent up sharply toward the mountains and truncated by erosion. The Triassic Basins in Virginia and North Carolina are underlain by moderate to gently dipping beds of shale and sandstone that have been extensively faulted and invaded by narrow bodies of igneous rock. These basins were formed in Triassic time when major faults in the crystalline rocks of the Piedmont resulted in the formation of structural depressions up to several thousand meters deep and more than 25 km wide and 140 km long.

The land surface in most of the region is underlain by regolith formed by chemical and mechanical breakdown of the bedrock. In the western part of the Great Plains the residual soils are overlain by or intermixed with eolian (wind-laid) deposits. The thickness and composition of the regolith depend on the composition and structure of the parent rock and on the climate, land cover, and topography. In areas underlain by relatively pure limestone, the regolith consists mostly of clay and is generally only a few meters thick. Where the limestones contain chert and in areas underlain by shale and sandstone, the regolith is thicker, up to 30 m or more in some areas. The

8. PIEDMONT BLUE RIDGE GROUND-WATER REGION





8A	Mountain Slopes
8B	Alluvial Mountain Valleys
8C	Mountain Flanks
8D	Regolith
8E	River Alluvium
8F	Mountain Crests
8G	Swamp/Marsh

8. PIEDMONT BLUE RIDGE REGION

(Thick regolith over fractured crystalline and metamorphosed sedimentary rocks)

The Piedmont and Blue Ridge region is an area of about 247,000 km2 extending from Alabama on the south to Pennsylvania on the north. The Piedmont part of the region consists of low, rounded hills and long, rolling, northeast-southwest trending ridges whose summits range from about a hundred meters above sea level along its eastern boundary with the Coastal Plain to 500 to 600 m along its boundary with the Blue Ridge area to the west. The Blue Ridge is mountainous and includes the highest peaks east of the Mississippi. The mountains, some of which reach altitudes of more than 2,000 m, have smooth-rounded outlines and are bordered by well-graded streams flowing in relatively narrow valleys.

The Piedmont and Blue Ridge region is underlain by bedrock of Precambrian and Paleozoic age consisting of igneous and metamorphosed igneous and sedimentary rocks. These include granite, gneiss, schist, quartzite, slate, marble, and phyllite. The land surface in the Piedmont and Blue Ridge is underlain by clay-rich, unconsolidated material derived from in situ weathering of the underlying bedrock. This material, which averages about 10 to 20 m in thickness and may be as much as 100 m thick on some ridges, is referred to as saprolite. In many valleys, especially those of larger streams, flood plains are underlain by thin, moderately well-sorted alluvium deposited by the streams. When the distinction between saprolite and alluvium is not important, the term regolith is used to refer to the layer of unconsolidated deposits.

The regolith contains water in pore spaces between rock particles. The bedrock, on the other hand, does not have any significant intergranular porosity. It contains water, instead, in sheetlike openings formed along fractures (that is, breaks in the otherwise "solid" rock). The hydraulic conductivities of the regolith and the bedrock are similar and range from about 0.001 to 1 m day^{-1}. The major difference in their water-bearing characteristics is their porosities, that of regolith being about 20 to 30 percent and that of the bedrock about 0.01 to 2 percent. Small supplies of water adequate for domestic needs can be obtained from the regolith through large-diameter bored or dug wells. However, most wells, especially those where moderate supplies of water are needed, are relatively small in diameter and are cased through the regolith and finished with open holes in the bedrock. Although, as noted, the hydraulic conductivity of the bedrock is similar to that of the regolith, bedrock wells generally have much larger yields than regolith wells because, being deeper, they have a much larger availble drawdown.

10. ATLANTIC AND GULF COASTAL PLAIN GROUND-WATER REGION





10Aa	Regional Aquifers
10Ab	Unconsolidated & Semi-Consolidated Shallow Surficial Aquifer
10Ba	River Alluvium With Overbank Deposits
10Bb	River Alluvium Without Overbank Deposits
10C	Swamp

10. ATLANTIC AND GULF COASTAL PLAIN

(Complexly interbedded sand, silt, and clay)

The Atlantic and Gulf Coastal Plain region is an area of about 844,000 km^2 extending from Cape Cod, Massachusetts, on the north to the Rio Grande in Texas on the south. This Region does not include Florida and parts of the adjacent States; although those areas are a part of the Atlantic and Gulf Coastal Plain physiographic province, they together form a separate ground-water region. (See region 11, "Southeast Coastal Plain").

The Atlantic and Gulf Coastal Plain region ranges in width from a few kilometers near its northern end to nearly a thousand kilometers in the vicinity of the Mississippi River. The great width near the Mississippi reflects the effect of a major downwarped zone in the Earth's crust that extends from the Gulf of Mexico to about the confluence of the Mississippi and Ohio Rivers. This area is referred to as the Mississippi embayment.

The topography of the region ranges from extensive, flat, coastal swamps and marshes 1 to 2 m above sea level to rolling uplands, 100 to 250 m above sea level, along the inner margin of the region.

The region is underlain by unconsolidated sediments that consist principally of sand, silt, and clay transported by streams from the adjoining uplands. These sediments, which range in age from Jurassic to the present, range in thickness from less than a meter near the inner edge of the region to more than 12,000 m in southern Louisiana. The greatest thicknesses are along the seaward edge of the region and along the axis of the Mississippi embayment. The sediments were deposited on floodplains and as deltas where streams reached the coast and, during different invasions of the region by the sea, were reworked by waves and ocean currents. Thus, the sediments are complexly interbedded to the extent that most of the named geologic units into which they have been divided contain layers of the different types of sediment that underlie the region. These named geologic units (or formations) dip toward the coast or toward the axis of the Mississippi embayment, with the result that those that crop out at the surface form a series of bands roughly parallel to the coast or to the axis of the embayment. The oldest formations crop out along the inner margin of the region, and the youngest crop out in the coastal area.

Within any formation the coarsest grained materials (sand, at places interbedded with thin gravel layers) tend to be most abundant near source areas. Clay and silt layers become thicker and more numerous downdip.

11. SOUTHEAST COASTAL PLAIN GROUND-WATER REGION





11A	Solution Limestone and Shallow Surficial Aquifers
11B	Coastal Deposits
11C	Swamp
11D	Beaches & Bars

11. SOUTHEAST COASTAL PLAIN

(Thick layers of sand and clay over semi-consolidated carbonate rocks)

The Southeast Coastal Plain is an area of about 212,000 km^2 in Alabama, Florida, Georgia, and South Carolina. It is a relatively flat, low-lying area in which altitudes range from sea level at the coast to about 100 m down the center of the Florida peninsula and as much as 200 m on hills in Georgia near the interior boundary of the region. Much of the area, including the Everglades in southern Florida, is a nearly flat plain less than 10 m above sea level.

The land surface of the Southeast Coastal Plain is underlain by unconsolidated deposits of Pleistocene age consisting of sand, gravel, clay, and shell beds and, in southeastern Florida, by semiconsolidated limestone. From the coast up to altitudes of nearly 100 m, the surficial deposits are associated with marine terraces formed when the Coastal Plain was inundated at different times by the sea. In most of the region the surficial deposits rest on formations, primarily of middle to late Miocene age, composed of interbedded clay, sand, and limestone. The most extensive Miocene deposit is the Hawthorn Formation. The formations of middle to late Miocene age and, where those formations are absent, the surficial deposits overlie semiconsolidated limestones and dolomites that are as much as 1,500 m thick. These carbonate rocks range in age from early Miocene to Paleocene and are generally referred to collectively as Tertiary limestones.

The Tertiary limestone that underlies the Southeast Coastal Plain constitutes one of the most productive aquifers in the United States and is the feature that justifies treatment of the region separately from the remainder of the Atlantic and Gulf Coastal Plain. The aquifer, which is known as the Floridan aquifer, underlies all of Florida and southeast Georgia and small areas in Alabama and South Carolina. The Floridan aquifer consists of layers several meters thick composed largely of loose aggregations of shells of foraminifers and fragments of echinoids and other marine organisms interbedded with much thinner layers of cemented and cherty limestone. The Floridan, one of the most productive aquifers in the world, is the principal source of ground-water supplies in the southeast Coastal Plain region.

In southern Florida, south of Lake Okeechobee, and in a belt about 30 km wide northward along the east coast of Florida to the vicinity of St. Augustine, the water in the Floridan aquifer contains more than 100 mg/l of chloride. In this area, most water supplies are obtained from surficial aquifers, the most notable of which underlies the southeastern part of Florida and which in the Miami area consists of 30 to 100 m of cavernous limestone and

REFERENCE # 17

CLIMATIC ATLAS OF THE UNITED STATES

ronmental Science Services Administration . Environmental

L ANNUAL TOTAL PRECIPITATION (Inches)



N AND LAKE EVAPORATION





DEPARTMENT OF COMMERCE
[illegible] Roberts, Secretary

WEATHER BUREAU
[illegible]

TECHNICAL PAPER NO. 40

RAINFALL FREQUENCY ATLAS OF THE UNITED STATES

for Durations from 30 Minutes to 24 Hours and Return Periods from 1 to 100 Years

Prepared by
DAVID M. HERSHFIELD
Cooperative Studies Section, Hydrologic Services Division
for
Engineering Division, Soil Conservation Service
U.S. Department of Agriculture


1-YEAR 24-HOUR RAINFALL (INCHES)
Jefferson County, Kentucky
GULF OF MEXICO



Summary of Hydrologic Conditions of the Louisville Area Kentucky

By EDWIN A. BELL

CONTRIBUTIONS TO THE HYDROLOGY OF THE UNITED STATES

GEOLOGICAL SURVEY WATER-SUPPLY PAPER 1819-C

Prepared in cooperation with the Commonwealth of Kentucky and the University of Kentucky, Kentucky Geological Survey

UNITED STATES GOVERNMENT PRINTING OFFICE, WASHINGTON : 1966

UNITED STATES DEPARTMENT OF THE INTERIOR

STEWART L. UDALL, *Secretary*

GEOLOGICAL SURVEY

William T. Pecora, *Director*

For sale by the Superintendent of Documents, U.S. Government Printing Office
Washington, D.C. 20402 - Price $1.50

CONTENTS

ILLUSTRATIONS

[Plates are in pocket]

TABLES

CONTRIBUTIONS TO THE HYDROLOGY OF THE UNITED STATES

SUMMARY OF HYDROLOGIC CONDITIONS OF THE LOUISVILLE AREA, KENTUCKY

By EDWIN A. BELL

ABSTRACT

Water problems and their solution have been associated with the growth and development of the Louisville area for more than a century. Many hydrologic data that aided water users in the past can be applied to present water problems and will be helpful for solving many similar problems in the future. Most of the water problems of Louisville, a water-rich area, concern management and are associated with the distribtuion of supplies, the quality of water, drainage, and waste disposal.

The local hydrologic system at Louisville is dominated by the Ohio River and the glacial-outwash deposits beneath its flood plain. The water-bearing limestones in the uplands are secondary sources of water. The average flow of the Ohio River at Louisville, 73 billion gallons per day, and the potential availability of 370 million gallons per day of ground water suitable for industrial cooling purposes minimize the chance of acute water shortage in the area. Under current development, use of water averages about 211 million gallons per day, excluding about 392 million gallons of Ohio River water circulated daily through steampower plants and returned directly to the river. Optimum use and control of the water resources will be dependent on solving several water problems.

The principal sources of water are in the Ohio River bottom land, whereas the new and potential centers of use are in the uplands. Either water must be piped to these new centers from the present sources or new supplies must be developed. Available data on streamflow and ground water are adequate to plan for the development of small local supplies.

Since the completion of floodwalls and levees in 1953, widespread damage from flooding is a thing of the past in the Louisville area. Some local flooding of unprotected areas and of lowlands along tributary streams still takes place. The analyses of streamflow data are useful in planning for protection of these areas, but additional streamflow records and flood-area mapping are needed to best solve the problem. Droughts are a problem only to users of small water supplies in the uplands, where additional water either can be imported or developed locally.

Pollution and undesirable chemical quality of water for some uses are the most serious drawbacks to the optimum development of the water resources in Louisville and Jefferson County. Available chemical analyses of ground water

are useful for determining its suitability for various uses, but additional data are needed to guide management decisions. Sources of contamination should be inventoried and water samples analyzed periodically to monitor changes in quality.

PURPOSE AND SCOPE

This report describes the hydrologic system and its operation, identifies Louisville's water problems, and shows how the analysis and interpretation of basic water-resource data are applied to water problems. Special emphasis is given to ground-water problems and to summarizing data that are useful to water managers in developing and utilizing ground-water supplies in the area.

Geologic investigations in the area provided data to describe the natural environment in which the hydrologic cycle operates. Hydrologic and hydraulic studies resulted in knowledge of the occurrence and movement of water within the area. The types of basic data include determinations of physical and hydrologic characteristics of soil and rock, determinations of streamflows and ground-water levels, determinations of temperature, and the physical and chemical properties of waters. Correlations of the basic data with natural phenomena, such as precipitation, and with changes in the environment imposed by man delineate the water regimen and relate the hydrologic system to the development and conservation of Louisville's water resources.

RESULTS OF INVESTIGATIONS

Most of the data collected and analyzed during investigations of ground-water resources in the Louisville area since 1943 are incorporated in Geological Survey reports resulting from those investigations. Before the 1950's, the reports were generally released to open file and duplicated in limited quantities. A tropical summary of basic ground-water information is given in table 1.

COOPERATION AND ACKNOWLEDGMENTS

The U.S. Geological Survey in cooperation with city, county, State, or Federal agencies, and currently in cooperation with the Kentucky Geological Survey, has been active in water-resources investigations in the Louisville area since 1938. Intensive studies of ground-water resources in the area began in 1943 in cooperation with the Geological Division, Kentucky State Department of Mines and Minerals (now the Kentucky Geological Survey, a research and service department of the University of Kentucky), and with the city of Louisville. The studies were continued in cooperation with Jefferson County, the Rubber Reserve Company (a wartime agency of the Federal

TABLE 1.—*Classification of references by topic*

Reference	Bell (1962)	Bell and others (1963)	Guyton (1946)	Guyton and others (1944)	Hamilton (1944)	Mac-Cary (1955)	Mac-Cary (1956)	Price (1964a)	Price (1964b)	Rorabaugh (1946a)	Rorabaugh (1946b)	Rorabaugh (1946c)	Rorabaugh (1956a)	Rorabaugh (1956b)	Rorabaugh and others (1953)	Sublett (1945)	USGS (1944)	USGS (1943)	USGS[1] (1944–58)	Whitesides and Nicholls (1961)
Aquifer characteristics																				
Areas of pumping	X	XXX	X	X															X	
Artificial recharge																				
Availability of water	X	XXX		X	X	X	XXXX	XX	XX	XXX	X	X		XXX		X	X			
Bedrock		X		X	X	X	X	X	X	X						X				
Chemical analyses											X									
Geography					X	X														
Geologic structure			X	X			X		X	X	X			X						
Glacial deposits	XX	X											X							
Ground-water potential																				
Induced infiltration from river	X			X						X										
Mineral constituents of water		X		X			XX	X	X	X	XXX			XX					X	X
Movement of water	XXX	XXX	X	XX																
Natural discharge							XXX	X	X	XXXX	XXX			XX						
Natural recharge																				
Occurrence of water				XX	X		X	X	X	X				X		X				
Physical character of water																				
Physiography					X								X							
Precipitation	X	X	X				X													
Pumpage																		X	XX	
Pumping tests																				
Soil and rock characteristics					X	X	X									X	X			
Stratigraphy				X																
Temperature of water																				
Test drilling	XX	XXX	X	X			XXXX	X	X	XXXX	X	X	X	XXXX	XXX				X	X
Water in storage																				
Water levels		XXX	X	X	X		XXXX	X	X	XXXX	X	X	X	XXXX	XXX	X	X	X	X	X
Water use																				
Well characteristics		XXX		XX	X		XX	X	X	XXXX	X	X		XXXX	X	X		X	X	X
Well logs																				
Well-numbering system		XX		XX	X		XX	X	X	XXXX	X	X		XXXX	X	X		X	X	X
Well records																				

[1] U.S. Geol. Survey Water-Supply Papers 1017, 1024, 1072, 1097, 1127, 1157, 1160, 1192, 1222, 1266, 1322, 1403, and 1538. (See list of references, p. C34.)

Government), the city of Louisville, and the Economic Development Board of Kentucky (formerly the Agricultural and Industrial Development Board) and are currently in cooperation with the Kentucky Geological Survey.

Most of the data used in this report were collected by the U.S. Geological Survey during the period 1943–62. However, much information was furnished by other Federal agencies, State, county, and city officials, well drillers, industrial managers, and many individuals too numerous to list, who also permitted the Survey to make observations and to collect data at many installations.

WELL-NUMBERING SYSTEM

The Louisville area lies between long. 85° and 86° W. and lat. 38° and 39° N. and has been subdivided into quadrangles by a grid of 1-minute meridians of longitude and 1-minute parallels of latitude. The wells in each of the quadrangles are numbered in the order inventoried. A well is designated by a composite of three numbers: the first, indicates the minutes of longitude; the second, the minutes of latitude; and the third, the number of the well in that quadrangle. Thus, well 43–15–1 is the first well inventoried in the 1-minute quadrangle west of long. 85°43′ W. and north of lat. 38°15′ N.

DESCRIPTION OF THE AREA

The Louisville area, as described in this report, includes all Jefferson County (fig. 1) an area of 394 square miles in the north-central part of the State. It is in the drainage basin of the Ohio River, which forms the west boundary of the area. The climate is mild and humid, and extreme conditions seldom prevail for long periods. The Population Committee of the Louisville Chamber of Commerce estimated that the present (1963) population of 650,000 is expected to increase to about 745,000 by 1970. Industrial and commercial enterprises are the basis of a stable economy. Farming, principally in the eastern part of the county, is less significant in the general economy of the area. Adjustments after World War II included an expansion of industry and a shift of the increasing population from city to outlying areas.

THE HYDROLOGIC SYSTEM

The dominant feature of the hydrologic system in the Louisville area is the Ohio River and its flood plain underlain by about 100 feet of permeable sand and gravel deposits. At Louisville the river carries the drainage from an area of 91,170 square miles. The river fur-



FIGURE 1.—Area covered by this report.

nishes water suitable for all local uses, provides a navigation avenue for 80 million tons of freight annually (1959–61), and provides recreational areas. The average discharge of the river at Louisville is so large—113,900 cfs (cubic feet per second), or more than 73 billion gallons per day—that a water shortage seems inconceivable. Despite the abundance of water, its chemical and biological quality is affected by contamination from untreated domestic sewage and industrial wastes discharged into the river upstream from Louisville.

The smaller streams in the Louisville area, which all flow directly or indirectly into the Ohio River, are relatively unimportant as sources of water because their flows in dry years become very low or cease entirely.

The part of local precipitation that does not become surface runoff or is not evaporated enters the ground and replenishes soil moisture or seeps further downward to the zone of saturation and recharges the ground-water reservoirs. Ground water in the area is discharged through wells and springs or moves generally westward and northwestward where it seeps into the river or leaves the area as subsurface underflow. Figure 2 is a generalized diagram showing the occurrence and direction of movement of waters in the Louisville area.

GEOLOGIC FRAMEWORK

The geologic framework that controls the availability of water in the Louisville area is illustrated by the block diagram (pl. 1). The upland areas are underlain by shale and limestone of Silurian, Devonian, and Mississippian ages. These rocks dip to the southwest at about 40 feet per mile. The present valley of the Ohio River along the western and northwestern part of the area was cut into the shale and



FIGURE 2.—Hydrologic cycle in the Louisville area, Kentucky.

limestone during glacial times. The rock valley is filled with alluvium of Quarternary age which underlies the Ohio River flood plain to a maximum depth of 130 feet. (In this report, the Ohio River flood plain is defined as the entire surface area of the alluvium filling the rock valley.) The alluvium consists of glacial outwash, sand, and gravel and a blanket of Recent silt and clay, and is connected hydraulically with the Ohio River along much of its course in the area.

The glacial deposit of sand and gravel in the flood plain has a vast water-storage capacity and high transmissibility and is the principal aquifer in the Louisville area. The limestone provides a secondary aquifer, particularly where solution openings occur along extensive joint systems and well-formed bedding planes. Limestone in the central part of Jefferson County yields water to many domestic wells, and the limestone bedrock beneath the glacial sand and gravel in the city yields large quantities of water to industrial wells.

The clay and shale are not significant as aquifers but are important because they influence the flow of water to and from other formations.

Formations of Ordovician and Silurian ages are exposed in the eastern third of the county. Formations of Mississippian age comprise the bedrock of the Knobs area in the southwestern part of the county. These formations, however, are not of hydrologic importance locally and are not defined in the local hydrologic system.

HYDROLOGY

The Louisville area is at times affected by cold airmasses from the northwest and Great Lakes area, by the warmer air sweeping up the Mississippi and Ohio Valleys from the Gulf region, and by the meeting of these two opposing airmasses. The resulting variation in precipitation affects the local hydrologic system.

The normal annual precipitation at Standiford Airport (U.S. Weather Bur. records) for the period 1931–60 is 41.32 inches. (See fig. 3.) If it is assumed that this amount is the average throughout the Louisville area and that losses to evaporation and transpiration are about 60 percent of the precipitation, an average of nearly one-third of a billion gallons is added daily to the amount of water that moves through the area, either on or in the ground. This is less than one-half of 1 percent of the average amount of water that the Ohio River brings in from outside the area each day.

In the eastern third of Jefferson County and in the Knobs area south of Louisville, topographic highs and lows are pronounced, and much of the precipitation leaves the area rapidly as overland runoff to local streams. Only a small amount of water seeps below the soil mantle



FIGURE 3.—Departure from normal precipitation at U.S. Weather Bureau station, Louisville, Ky., 1943–62. Normal precipitation determined by U.S. Weather Bureau, based on period 1931–60.

to the underlying limestone. In the central part of the county, and extending to the Ohio River valley, the relief is relatively flat, the runoff is generally slower, and recharge to ground-water storage in the underlying limestone is substantially higher. Ground-water flow is generally toward the Ohio River valley except in the extreme eastern part of the county where the flow is toward the south.

In the flood plain the many buildings and great amount of pavement limit the area in which water can enter the ground; also, the low permeability of a silt-and-clay blanket impedes downward seepage of water into the more permeable sand and gravel. Consequently, direct recharge of the alluvial aquifer by precipitation is decreased. Infiltration from the Ohio River in the northeastern part of Louisville and flow through the rock valley wall are major contributors of water to the sand and gravel. The deposit of sand and gravel with its vast storage of water, estimated to be nearly 100 billion gallons (Bell, 1962), supplies many industrial wells in the area and is the source of water for the Louisville Extension Water District in the southwestern part of the county.

Water in the area is predominantly of calcium magnesium bicarbonate type and contains appreciable concentrations of sulfate. Ground water is generally harder than surface water and contains more dissolved solids.

RELATION OF HYDROLOGIC SYSTEM TO WATER UTILIZATION

The Louisville area has an abundant water supply: Its optimum use is controlled primarily by the (1) variation of precipitation (seasonal and local), (2) hydrologic character of soil and rock, and (3) dynamics of fluid flow.

Seasonal and local variations in precipitation directly affect availability of water outside the flood plain. During dry summers most of the small streams and many wells finished in the limestone become dry, making it necessary for users to store water or to import it. Seasonal variation is also noted in the flood plain, but it is small compared with the total amount of water available, and no critical shortage occurs there.

The porosity of soil and rock determines how water might be absorbed and accumulated in the ground. The permeability, or water-transmitting capacity, determines the quantity of water that will move through the rocks and can be utilized. An abundance of ground water is available in the porous and permeable sand and gravel deposits in the Ohio River flood plain. Only small amounts of ground water are available from the less permeable limestone of the uplands.

Water on the surface and in the ground moves down a hydraulic gradient. Water on the surface, unless stored in the area of use, runs away rather quickly to the Ohio River and its flood plain. Mechanical energy must then be provided to move the water to the area of use. Downgradient movement of water through cracks in limestone and pore spaces in the sand and gravel, however, is slower, and the water is held in storage for longer periods of time. Thus storage is provided naturally, and the water is available in the area where it is to be used. Industrial pumping of water at high rates from the alluvium in parts of the Louisville area has altered the hydraulic gradients which influence the direction of flow and locally limit the utilization of ground-water supplies.

The chief adverse effect of water use on the local hydrologic system is pollution. Because the Louisville area obtains most of its water from the Ohio River, its problems of chemical and biological pollution originate in upstream areas. Therefore, extensive treatment of water is required to control the quality for domestic and industrial uses.

THE AVAILABLE WATER SUPPLY

The large quantity of water that flows in the Ohio River and moves through the alluvial sand-and-gravel deposit in the Ohio River flood plain at Louisville is the major source for development in the area. The availability of adequate public and industrial water supplies contributes much to Louisville's economic growth and to the welfare of its population. Sources of smaller supplies are the tributary streams (mainly Beargrass Creek, Floyds Fork, Harrods Creek, and Pond Creek) which drain the various parts of the county and the ground water contained in the bedrock of the uplands.

THE OHIO RIVER

The Ohio River has provided the municipal water supply for more than a century, and it provides most of the water for all other uses including industrial supplies, fire protection, irrigation, navigation, hydroelectric power, recreation, and dilution of wastes. It also carries away local surface drainage and supports fish and wildlife. But in contrast to the many benefits it provides, the Ohio River has been a relentless force of destruction during severe flooding.

DISCHARGE

Although the average flow of the Ohio River at Louisville (114,000 cfs, or 73 billion gallons per day) equals more than half the average flow over Niagara Falls, it cannot be used to provide a basis for determining water-supply availability. Evaluations must be based primarily on data showing the magnitude and frequency of minimum flows and to some extent on duration-of-flow data.

The duration curve of flow (fig. 4) shows the percentage of time that the daily flow of the Ohio River at Louisville exceeds various values. The shape of the curve is indicative of the flow characteristics of the drainage basin. The graph (fig. 4) shows that the discharge equaled or exceeded 3.88 billion gallons per day 99 percent of the time during the period 1928–62 and that the discharge equaled or exceeded 73 billion gallons per day (the average flow) about 37 percent of the time. The minimum daily flow was less than 3.88 billion gallons per day at an average interval of 2.7 years (fig. 5).

The low-flow frequency curves shown on figure 5 were derived from the daily flow records at Louisville for the period 1928–62.

These curves represent the average of plotted points computed from the lowest mean flows for periods of 1 day, 7 days, and 30 consecutive days in each year of record. The curves show the expected recurrence interval in years for the indicated minimum flows.

The low-flow frequency curves show that on the average of every 20 years the flow of the Ohio River at Louisville recedes so that the lowest mean flow for 30 consecutive days will be less than 7,000 cfs, for 7 consecutive days will be less than 5,500 cfs, and for 1 day will be less than 4,100 cfs.

The minimum flows shown for the year 1930 (30-day low flow, 4,320 cfs; 7-day low flow, 3,530 cfs; 1-day low flow, 2,100 cfs) are extremely low as compared to the frequency curves. An analysis of the plotting indicates that the 1930 drought was a very unusual occurrence and that the recurrence expectancy of minimum flows comparable to those in 1930 will be a long period of years, possibly many times the



FIGURE 4.—Duration curve of daily flows, Ohio River at Louisville, Ky., 1928–62. Drainage area 91,170 square miles. Example: The daily flow at Louisville equaled or exceeded 6,000 cfs (3,878 mgd) 99 percent of the time during the period 1928–62.

In evaluating the potential water supply of the Ohio River at Louisville, it is noted that the Louisville Water Company reported an average daily pumpage of 135 cfs from the Ohio River in 1963 and a maximum daily pumpage of 195 cfs in 1962. Compared to the 20-year flow expectancy, the average daily pumpage for 1963 represents only 4 percent of the minimum daily flow expected and less than 3 percent of the 7-day minimum flow. The maximum daily pumpage of 195 cfs in 1962 represents only 5 percent of the 20-year minimum daily flow and less than 4 percent of the 20-year 7-day minimum flow. Even during the extreme drought of 1930 the maximum daily pumpage would have been only about 9 percent of the minimum daily flow and less than 6 percent of the 7-day minimum flow.

Another factor used in evaluating the future water-supply poten-



FIGURE 5.—Low-flow frequencies, Ohio River at Louisville, Ky., 1928–62. Drainage area 91,170 square miles. Examples: (1) The minimum daily flow at Louisville will be less than 5,000 cfs (3,232 mgd) at average interval of 4.5 years, (2) The minimum 7-day flow will be less than 8,000 cfs (5,170 mgd) at average interval of 3.2 years, (3) The minimum 30-day flow will be less than 8,000 cfs (5,170 mgd) at average interval of 9.7 years.

upstream from Louisville in the four-State area of Pennsylvania, Ohio, West Virginia, and Kentucky. It has been estimated that the reservoirs on tributary streams in those States, including those reservoirs completed in recent years, would augment Ohio River flows at Louisville by as much as 50 percent during minor droughts and that, on recurrence of an extreme drought similar to that in the 1930's, releases from the reservoirs would double the minimum flows at Louisville.

CHEMICAL QUALITY AND POLLUTION

The water in the Ohio River under natural conditions would be slightly hard and of the calcium bicarbonate or calcium magnesium bicarbonate type. However, because of pollution by industrial and domestic wastes, the concentrations of sodium, sulfate, chloride, fluoride, nitrate, and the hardness are increased and the basic character of the water is changed. In addition, oils, toxic substances, and taste- and odor-producing compounds are discharged into the river from various sources. Also, there is considerable variation in the chemical quality owing to changes in riverflow and in the amounts of the pollutants entering the stream. As a result, treatment is required to make the water suitable for human consumption and for some industrial uses. The amount of treatment necessary varies seasonally with the variation in riverflow and locally with the change in the volume of waste entering the stream.

In 1961 the water of the Ohio River had an average hardness of 137 ppm (parts per million), as reported by the Ohio River Valley Water Sanitation Commission (ORSANCO). The hardness ranged from 93 to 197 ppm. Total dissolved solids ranged from 150 to 334 ppm and averaged 214 ppm. The total dissolved solids were well below the 500-ppm limit recommended by the U.S. Public Health Service (1962) in a year when riverflows were above normal.

There is also considerable variation in bacterial pollution. During 1961 ORSANCO reported that coliform bacteria ranged from 1,100 to 13,000 (most probable number per 100 ml). In relation to previous years this range is low and is the result of the river cleanup by ORSANCO and of dilution by the above-normal riverflow in 1961.

The quality of the water in the Ohio River at Louisville in 1961, as reported by ORSANCO, is summarized in the following table.

Constituent	Concentration (ppm)		
	Maximum	Minimum	Average
Silica (SiO_2)	7.0	2.4	5.6
Iron (Fe)	2.2	.2	.8
Calcium (Ca)	56	28	39
Magnesium (Mg)	15	7.6	10
Sodium (Na)	31	6.3	15
Potassium (K)	3.2	.9	2.1
Sulfate (SO_4)	131	38	74
Chloride (Cl)	59	8.0	24
Fluoride (F)	.4	.1	.2
Nitrate (NO_3)	6.0	2.0	4.0
Dissolved solids (total)	334	150	214
Total hardness (as $CaCO_3$)	197	93	137
Alkalinity (as $CaCO_3$)	107	49	74
Specific conductance, micromhos at 25°C	543	243	351
pH	8.8	6.7	
Temperature, °F	81	35	60

SMALL STREAMS

An average of about 15 inches of the annual precipitation (Rorabaugh and others, 1953, p. 6) in the Louisville area becomes runoff. The total drainage, averaging more than 0.2 billion gallons per day, is carried to the Ohio and Salt Rivers by tributary streams, principally Floyds Fork in eastern Jefferson County, Harrods Creek and Beargrass Creek in the north-central part of the area, and Pond Creek in the southern and western parts of the county. These streams provide recreational areas and furnish some water for stock and for

irrigation, but their flows are not adequate for dependable supplies. During the late summer and fall, the flow of these streams usually recedes to a very low quantity, sometimes going dry for periods of a few days to several weeks. In recent years, however, the flow of Pond Creek has been augmented by inflow diverted by manufacturing plants from the Louisville public water supply.

Ponds for stock are necessary on most farmlands in Jefferson County. As more land is developed for housing, the stock ponds are gradually disappearing and are becoming less important in the general water regimen. In contrast, artificial lakes formed by stream impoundments are becoming more important as recreational areas for fishing and water sports.

GROUND WATER IN ALLUVIUM

The occurrence and availability of water in the Louisville area are described by Rorabaugh and others (1953), by MacCary (1956), and by Bell and others (1963).

The alluvium in the Ohio River flood plain is the second most important source of water. It comprises outwash sand and gravel of Pleistocene age ranging from 0 to 100 feet in thickness, overlain by a blanket of silt and clay as much as 40 feet thick. Very thin deposits of clay and silt of Recent age cover parts of the flood plain. The permeability of the top clay and silt is low and impedes vertical seepage of water from the surface. Nevertheless, the glacial deposit of sand and gravel is a good, permeable water-bearing formation, and the entire thickness is considered a single hydrologic unit. The thickness of the saturated sand and gravel varies considerably (pl. 2) because of the shape of the underlying bedrock surface and because of the lowered water table in heavily pumped areas (pl. 3).

The alluvium northeast of downtown Louisville between the Ohio River and the rock bluffs is mostly saturated. Along the reach northeast of Zorn Avenue, the alluvium ranges in thickness from about 120 feet near Goose Creek to about 90 feet at Zorn Avenue and averages about 100 feet in thickness (pl. 2). The water in the alluvium along the reach is connected hydraulically with the river, and changes in the river stage are reflected rapidly by corresponding changes in ground-water storage.

Southwest of Zorn Avenue the hydraulic gradient generally slopes toward downtown Louisville where water levels have been lowered by pumping for air conditioning (pl. 3). From downtown Louisville the gradient steepens progressively toward the heavily pumped industrial center southwest of the city. The average thickness of the alluvium within the city limits is greater than in the reach along the river northeast of Zorn Avenue, but the thickness of saturated sand and gravel is less because of the lowered water table.

Southwest of downtown Louisville ground water flows northwestward toward the heavily pumped industrial center and westward toward the Ohio River. A large quantity of ground water is available, but the thickness of saturated sand and gravel varies considerably because of several domes in the underlying bedrock.

Southward from Bells Lane to Lees Lane the gradient is from the river toward heavily pumped centers where the water level has been drawn down below river level. South of Lees Lane the gradient is toward the river, except during floods. Although the potential is not so great as that northeast of the city, much infiltration can be induced from the river along its reach south of Lees Lane.

Bell (1962, p. 17) estimated that the maximum supply that could be developed in the alluvial aquifer of the flood plain in the Louisville area without depletion of storage is about 370 mgd (million gallons per day). However, to attain that supply, maximum infiltration from the Ohio River would have to be induced. This would require infiltration galleries or high-capacity wells virtually along the entire reach of the river where it is connected hydraulically with the aquifers.

The river is connected hydraulically with the alluvial aquifer, in varying degrees of effectiveness, along most of its distance within the Louisville area (pl. 2). The most effective connection—and hence the greatest potential infiltration that could be induced from the river—is along the reach northeast of Zorn Avenue. The hydraulic connection between the river and aquifer becomes progressively less effective downstream toward McAlpine Dam because of clay barriers. In the northwestern part between McAlpine Dam and Bells Lane, except in a small area of low permeability opposite Sand Island, the connection is poor. The infiltration potential is large southward from Bells Lane.

A large amount of water stored in the alluvium underlying the Ohio River flood plain is a reserve ground-water supply that could be drawn in emergencies. Bell (1962, p. 22) estimated that nearly 100 billion gallons are stored in the alluvium within the Ohio River flood plain of the Louisville area.

NATURAL RECHARGE TO THE ALLUVIUM

Natural recharge, which is nature's way of maintaining or replenishing ground-water supplies, is derived from precipitation. Some rain falling in areas where permeable rock, chiefly limestone, crops out, fills the crevices and voids of the rock and flows by gravity from the limestone into the alluvium. Elsewhere, direct downward seepage of local rainfall through the permeable alluvium adds to the ground-

water storage. Natural recharge to the alluvium in the flood plain of the Louisville area, therefore, is partly by flow through the permeable rocks of the uplands adjacent to the deposits of sand and gravel and partly by direct downward seepage. Rorabaugh (1949b, p. 20) estimated that flow through the valley wall northeast of Beargrass Creek in 1946 was about 200,000 gpd (gallons per day) per mile of valley wall and southwest of Louisville in 1945 was about 100,000 gpd per mile of valley wall. The flow through the valley wall in the strip between Beargrass Creek and Shively should be as great or greater than in the other areas because of the predominance of limestone and the steeper hydraulic gradients toward the sand and gravel. Because of hydrostatic pressure some water moves upward from limestones underlying the alluvium, particularly in the west-central subarea.

The natural recharge by downward seepage to the alluvium is impeded by the considerable thickness of clay overlying the deposit of sand and gravel and is further minimized in the city because of buildings and pavings. Neverthless, there are substantial amounts of recharge to the alluvium outside the built-up area. Accretion to the aquifer in the area southwest of Louisville was estimated by Rorabaugh (1949b, p. 21) as about 250,000 gpd per square mile in 1945, which was a wet year, but it would be much less in dry years. The changing use of land caused by urbanization in that part of the Louisville area has probably reduced the direct recharge from rainfall penetrating the flood plain. Supplementary recharge at times has resulted from an accumulation of runoff in large open pits that were excavated for various purposes.

INDUCED RECHARGE TO THE ALLUVIUM

In addition to the natural recharge to the area, a large amount of water can be induced by infiltration from the Ohio River. If high-capacity wells very near the river are pumped at high rates over a long period of time, the steep hydraulic gradient that is created will induce a large amount of water to flow through the banks and bed of the river. Rorabaugh (1956b, p. 159) estimated that about 280 mgd could be induced by infiltration from the river northeast of Zorn Avenue and (Rorabaugh, 1949b, p. 5) about 59 mgd from the reach south of Lees Lane.

NATURAL DISCHARGE FROM THE ALLUVIUM

All the recharge to the ground water in the alluvial area is not a net gain because water moves downgradient through the aquifer and is discharged through seeps along the banks of streams or joins the underflow through the aquifer out of the area. The normal hydraulic gradient of ground water between Zorn Avenue at the Ohio River corresponds to the difference of head in the river between the upper and lower pools at Louisville. Most of the natural discharge from the alluvium is lost to the Ohio River south of Lees Lane. The loss in 1945 was estimated by Rorabaugh (1949b, p. 4) to be about 800,000 gpd per mile of river.

CHEMICAL QUALITY AND TEMPERATURE

Throughout the area the quality of the water in the alluvium varies depending on the nearness of the alluvium to sources of recharge or pollution. Water from alluvium is generally very hard, high in bicarbonate, and contains dissolved solids ranging from 250 to more than 1,500 ppm. The most highly mineralized water is in the central and west-central parts of Louisville where the alluvium is underlain by limestone. The median hardness of water from wells in deposits of sand and gravel overlying limestone bedrock sampled in 1952 was 642 ppm; from wells in sand and gravel overlying shale, 470 ppm (Rorabaugh and others, 1953, p. 37). Without softening, ground water from alluvium is not satisfactory for many purposes and is unacceptable for most industrial uses.

The chemical characteristics of water from wells finished in the alluvium and in the underlying bedrock are shown on plate 4 by polygons, called Stiff diagrams. The polygons are formed by plotting on four parallel horizontal axes the cations to the left and anions to the right of a vertical zero reference line. The concentrations for the cations calcium, magnesium, sodium, potassium,[1] and iron and for the anions bicarbonate, sulfate, chloride, and nitrate are expressed in equivalents per million. Lines connecting the plotted points form a polygon which represents the chemical character of the water. The polygons show that this water is predominately a calcium bicarbonate type containing substantial magnesium and sulfate. The sodium, potassium, and chlorides are present in lesser amounts. The iron and nitrate, though generally found in concentrations less than 0.1 epm (equivalents per million), are plotted because of their undesirable effect on water for certain uses.

In general, wells along the Ohio River yield water with less hardness and dissolved solids than those in the remainder of the area—a condition reflecting the effect of recharge by floodwater and river water induced by heavy pumping. Normally, the dilution effects of river-water infiltration diminish rapidly as the distance from the river increases. The effect is generally noticeable only within 400 or 500 feet of the river. However, it is more pronounced in the area between the river and the "Rubbertown" and downtown subareas.

Ground-water temperatures are fairly constant and approximate the average air temperature. In the Louisville area the ground-water

[1] Sodium and potassium are shown as one constituent.

temperature averages about 58° F except where it is affected by river infiltration, by seepage from leaky sewers, or by artificial recharge. The temperature of water from wells ranges from 47° to 66° F.

GROUND WATER IN BEDROCK

The water-bearing properties of the principal bedrock formations in the Louisville area were described by Hamilton (1944, p. 9), by Rorabaugh (1949b, p. 20), and in more detail by MacCary (1956, p. 3).

The Louisville Limestone of Silurian age and the Jeffersonville and Sellersburg Limestones of Devonian age are exposed in the northern, central, and south-central parts of Jefferson County. They also underlie the valley fill under the central part of the city and are exposed in the riverbed at the Falls of the Ohio River. These formations form a single aquifer of secondary importance that yields most of the water pumped from consolidated rocks. Water in this aquifer is contained in and moves along interconnected cracks and solution channels.

In the uplands the ability of the limestone to transmit water along joint systems, bedding planes, and solution openings is good, but its ability to retain or store water is low. The openings in the limestone are rapidly filled by downward seepage and lateral percolation. During wet seasons the limestone remains saturated, and large quantities of water are available. Between rains the limestone rapidly discharges water downgradient, and during droughts many of the solution channels at the higher altitudes are drained, causing shallow wells to become dry. However, many deep wells and springs at low altitudes in the uplands yield enough water for domestic use. The areal variation of available ground water is indicated by plate 5.

This same limestone underlies much of the alluvium in the central part of the city. There, the solution channels are probably developed more extensively than in the uplands. The limestone beneath the flood plain is hydraulically connected with the deposits of sand and gravel, from which a continuing source of recharge is available, and consequently greater yields are available from the bedrock. Further, river water may enter the limestone bedrock at the Falls of the Ohio and flow southwestward along numerous narrow openings to areas of pumping. The most extensive joint system trends N. 30° E.; the most productive wells in the limestone are in a well-defined belt that is parallel to the joint system and that traverses the northwestern part of the Louisville area (area 2, pl. 4). One rock well in this belt is reported to have yielded 1,100 gpm (gallons per minute) for many years.

The water from the limestone bedrock is of the calcium bicarbonate type. It is generally very highly mineralized, but its mineral concentration varies greatly from place to place. The average hardness of water from 15 limestone wells beneath the alluvium of the Ohio River flood plain, sampled annually during the years 1944–52, is 580 ppm (Rorabaugh and others, p. 37). The hardness of the water from one of the wells sampled in 1953 was 1,140 ppm. The total dissolved solids in water from the limestone generally exceeded 1,200 ppm and in one well was 1,480 ppm. The concentration of calcium, bicarbonate, and sulfate is particularly high.

WATER-SUPPLY DEVELOPMENT

The development of water supplies in the Louisville area is directly related to the growth of the city. Since 1858 when the Louisville Water Company began pumping from the Ohio River for the public supply, developments have expanded to include several other river pumping stations for industrial uses and many wells for domestic and industrial uses.

The first extensive development of ground-water supplies was for air conditioning in downtown Louisville in the late 1930's. Development of ground-water supplies for industrial cooling, especially by manufacturers of chemicals and synthetic rubber, was greatest during the early 1940's. Most recently, the Louisville Extension Water District has developed a well field for public supply in the southwestern part of the county.

UTILIZATION OF WATER

Water in the Louisville area is used for public, commercial, and industrial supplies, for generation of electricity, and for irrigation and stock supply. It is withdrawn principally from the Ohio River and from the alluvium adjacent to the Ohio River (ground water). A small amount is withdrawn from small streams and ponds and from bedrock.

In 1962 water sources in the area furnished an average of 211.3 mgd of water for public and industrial uses. This excludes about 392 mgd of water which is diverted from the Ohio River for steam-generating plants and returned directly to the river, and a small amount of water pumped by privately owned wells and ponds for domestic and stock uses. The amount of water pumped for irrigation is not known but is probably small.

The following table shows the average amount of water used daily in the area in 1962.

Source and use	Average use (mgd)
Ohio River:	
Louisville Water Co	88.1
Industry (private sources)	83.0
Steam-generating plants	392.1
Ground water:	
Louisville Extension Water District	3.3
Industry (private sources)	35.1
Commercial (private sources)	1.7
Domestic and stock (private sources)	Small
Total	603.3

The distribution of pumping of ground water by industrial and commercial establishments is shown on figure 6.

EFFECTS OF WATER DEVELOPMENT

The hydrologic cycle is a constant process, and some water from precipitation is continuously migrating toward areas of withdrawal to replenish the supply. Withdrawals in any part of the Louisville area will adversely affect the hydrologic system if they exceed the rate of replenishment. The effects may be felt in a number of ways, such as changes in water level, changes in water quality or temperature, and changes in the flow of a stream or yield of a well. Table 2 and plate 6 summarize these effects.

CONDITIONS AFFECTING OPTIMUM DEVELOPMENT OF WATER RESOURCES

The Falls of the Ohio, a series of shallow rapids navigable only during periods of high-river stage, played an important part in the location of the city of Louisville. People and goods normally had to be transported overland around the falls, and the stopping place grew into a river-trade town. Since that time the number and the complexity of water problems have increased with the population.

Optimum development of the water resources of the Louisville area depends chiefly on the ability of the water manager to cope with problems such as distribution of available supplies, flooding, droughts, quality of water and pollution, and drainage. An appraisal and analysis of Louisville's water problems are needed to plan the development and management of the water resources, particularly ground water. Development has reached a stage beyond which it should not progress without an orderly plan that will insure against waste and misuse. A shortage of water probably will never be a problem in the Louisville area owing to the abundance of water in the Ohio River and in the alluvium beneath the flood plain.



FIGURE 6.—Distribution of ground-water pumping in the Louisville area, 1962.

DISTRIBUTION OF AVAILABLE WATER SUPPLIES

The two major sources of water supply, the Ohio River and the alluvial deposits of the Ohio River flood plain, lie along the west border of Jefferson County, and water from these sources is directly available to only 15 percent of the county. Water is piped to the metropolitan and residential sections outside this area for municipal and industrial uses.

Ground water from wells and springs in the limestone of the uplands is generally adequate for farm and domestic supplies. However, dry

TABLE 2.—*Effects of water development on hydrologic conditions in the Louisville area*

Type and (or) area of use	Source	Effects on—			
		Water levels	Chemical quality	Temperature	Yield or flow
Industrial (private sources):					
Air conditioning—Downtown subarea.	Wells in alluvium.	Levels declined to minimum of 373 ft above msl in 1955; recovered to 380 ft in 1962. See pl. 6.	Negligible	Negligible	Natural flow toward west intercepted; yields sustained.
Cooling—West-Central subarea.	Wells in alluvium and in limestone.	Levels declined to minimum of 375 ft above msl in 1960; recovered to 378 ft in 1962. See pl. 6.	Increase in hardness, sulfate, and total dissolved solids.	do	Loss of water to heavily pumped Rubbertown subarea; yields sustained after pumping was reduced in 1956.
Cooling—Southwest subarea.	Wells in alluvium.	Levels declined to minimum of 360 ft above msl in 1943; recovered to 392 ft in 1962. See pl. 6.	Negligible	do	Diverted natural flow toward points of pumping; yields sustained after pumping reduced.

Cooling—Rubbertown subarea.	Wells in alluvium.	Levels declined to less than 360 ft above msl in 1945; recovered to 370 ft in 1962. Nearly reached practical limit of drawdown in 1945. See pl. 6.	Increase in chloride in small local areas; increase in sulfate.	Small increase in seasonal range of temperature in wells near river.	Created hydraulic gradients from all directions toward center of pumping. Induced some water from river.
Public:					
Louisville Water Co.	Ohio River at Zorn Ave.	Negligible	None	Negligible	Normally withdraws a fraction of 1 percent of flow.
Louisville Extension Water District.	Wells in alluvium.	Levels declined to 385 ft above msl in 1962. Levels stabilized for present withdrawal (1962).	Increase in iron content.	do	Intercepts flow that formerly was lost to river; yields sustained for present withdrawals.
Domestic (private sources).	Wells in alluvium and in limestone; ponds.	Negligible	None	None	Negligible.

holes and wells with inadequate yields have been drilled, and springs that dry up during late summer and fall are present throughout the area. Surface water from small tributary streams, such as Beargrass Creek and Floyds Fork, does not have a perennial flow and cannot sustain a continuous supply without impoundment.

CURRENT CONDITIONS

As a source of water supply, the Ohio River is relatively unaffected by seasonal fluctuations; high flows or flooding have no adverse effects on use, and minimum flows exceed the maximum daily withdrawal by many times. Consequently at no time is water from the Ohio River in short supply.

In the alluvial deposits of the flood plain, underlying about 15 percent of Jefferson County, seasonal variation in precipitation and the resulting change in river stage affect the amount of ground water in storage. Heavy rains and resulting high flows of streams during the winter and spring recharge these deposits. The total effect of the recharge, however, is not apparent until late summer and early fall, and during these periods the overall increase in storage may be somewhat obscured by heavy withdrawals for industrial and municipal supplies. During the late fall, when storage is at a minimum, heavy pumping for municipal and industrial uses in southwestern Louisville has sometimes lowered the water table locally, giving cause for concern. No apparent problem of decreased supply has arisen in other areas of the alluvium.

In the uplands, which comprise approximately 85 percent of the county, the seasonal fluctuation of precipitation more directly affects the yield from wells and springs and the flow of streams than it does in the Ohio River bottom lands. In the uplands less water is stored because water moves rapidly through joints and solution openings in the limestone, and because stream gradients are steep, causing rapid runoff.

AVAILABLE HYDROLOGIC DATA

Data available for the Ohio River at Louisville consist of daily river stages collected since 1872 and daily discharges since 1928. These data show periods during which high and low flows are most likely to occur and their recurrence interval for the period of record to date. The data include the minimum-flow measurements needed as a base for planning withdrawals.

The hydrologic properties of the Ohio River alluvium have been determined primarily from water-level measurements. At some wells the water-level measurements are made periodically, whereas at others they are made with continuous-recording gages. In specific areas

pumping tests have been conducted under controlled conditions to measure the rate of change of water level with time at various pumping rates. These tests are useful in determining the coefficients of transmissibility and storage and the amount of water that can be induced from the Ohio River. Contours have been drawn on the water surface to show the actual position of the water table throughout the alluvial deposits. The water-level measurements are also used to determine the effect and time lag of high and low river stages and precipitation as well as the effect of nearby pumping wells.

Definition of water moving from the river to the alluvium or vice versa and the movement of water from the limestone of the upland into the alluvium are determined from a composite of both pumping tests and water-level measurements.

The present data on the alluvial area are adequate for most purposes, but continuation of water-level readings in the network of observation wells is of utmost importance for future reference.

Geologic data have been compiled to determine the position of the underlying bedrock and thus to determine the thickness and lithology of the alluvium.

In the uplands the collection of basic data for evaluation of ground- and surface-water studies has been less intensive than that for the Ohio River and its alluvial deposits. Data on ground water are included in a work by MacCary (1956) and in the annual series of U.S. Geological Survey water-supply papers entitled "Surface water supply of the United States" (see list of references, p. C34).

The data show that yields from wells and springs and the flow of streams are subject to seasonal fluctuations; consequently, their water-supply yield is limited. The water resources of the upland area warrant further studies because the data collected to date (1962) are insufficient for a proper evaluation of the area's potential.

APPLICABILITY OF EXISTING DATA FOR MANAGEMENT PURPOSES

Effective management of available water resources in the Louisville area requires that data be adequately applied to answer pertinent questions regarding the potential supply and the effects of water development.

Data collected for the Ohio River at Louisville are used to plot curves that show flow data such as the recurrence interval for flows of known magnitude. To the water manager, the recurrence of low flows would be important with regard to the probable deterioration of chemical and bacteriological quality and increased temperature. The recurrence interval for floods of a specific stage height would de-

termine the type of installation for setting and protecting pumping and other equipment at the river.

Data collected throughout the area of the alluvial deposits have been used to show the potential supply and the effects of water development in specific areas. Several examples of the use of the data are as follows:

1. An investigation to determine the quantity and quality of water available in northeastern Louisville was made during the period 1945–47. Analyses of data collected during this period showed that 280 mgd of water of suitable quality for domestic and industrial uses could be induced from a 6.4-mile reach of the Ohio River northeast of Louisville (Rorabaugh 1956b).
2. An appraisal of the available ground-water supply southwest of Louisville during the period 1944–46 is described by Rorabaugh (1946a). He estimated the storage to be about 1.5 billion gallons per foot below the water table; infiltration from rainfall on the area, about 11 mgd; and flow into the deposit of glacial sand and gravel from the east, about 1 mgd. Natural discharge to the river in the area was about 800,000 gpd per mile along the river.
3. Periodic water-level measurements have been used to compile the water-level contour maps which show the cones of depressions in the four subareas (pl. 3). Heavy pumping by industry had lowered the water level as much as 60 feet in the south distillery area by 1944, and 65 feet in the downtown subarea by 1955. In both areas the water levels were only about 10 feet above the underlying bedrock at the given drawdowns. In the Rubbertown subarea, record lows were observed in 1945. Water levels recovered through 1948, but increased pumpage has again introduced a downward trend, and in the west-central subarea water levels declined to within 10 to 15 feet of the underlying bedrock in 1948.

In the upland area of the county the limitations of ground water in limestone and of the water in streams as a major source of supply have been recognized from the initial water studies. The water manager can interpret the data in terms of the local situation and choose between the alternatives of installing individual water supplies for homes or developments, impounding a nearby stream, or bringing in water from outside the area.

FLOODING

CURRENT CONDITIONS

The great 1937 flood on the Ohio River inundated large parts of the city and adjacent areas and caused property damage of $57 million in the Louisville area, according to the U.S. Army Corps of Engineers. Eight years later, in 1945, the second highest flood of record caused property damage estimated at $4 million. Subsequent planning by many agencies resulted in the construction—completed in 1953 by the Corps of Engineers at a cost of about $29 million—of floodwalls, levees, and pumping stations to protect the city (pl. 3).

In recent years many flood-control dams and reservoirs have been constructed on tributary streams upstream from Louisville in the Ohio River basin. These control structures will have an effect in reducing flood heights at Louisville by delaying part of the floodwaters which normally would contribute to floods at Louisville. These structures in conjunction with the floodwall-levee system at Louisville have largely eliminated the damage caused by flooding of the Ohio River.

Most of the damage from flooding in Jefferson County in recent years can be attributed to flash floods on the tributary streams, notably on Beargrass, Pond, Fern, and Mill Creeks. Generally, average floods on the tributary streams are not troublesome. In extremely high floods, however, poor runoff conditions cause the flooding of homes in wide, flat overflow areas. In particular, this occurs in the upper reaches of Beargrass and Pond Creeks which extend into the suburban residental parts of Louisville. Most of the Beargrass Creek basin drains inside the Louisville floodwall-levee system, and downstream flooding is controlled by the Beargrass Creek pumping station. In the lower reaches of Pond Creek, backwater from Ohio River floods contributes to the flooding of residential areas.

Some flooding occurs in the basin of Floyds Fork, which drains most of the east half of the county, but the basin is sparsely settled and floods mainly affect the bottom farmlands.

AVAILABLE HYDROLOGIC DATA AND ADEQUACY

Flow records available for the Ohio River at and upstream from Louisville and for the larger tributary streams in Jefferson County are adequate for most needs. There is a continuous record of flood stages on the Ohio River at Louisville for almost 100 years, and continuous daily flow records have been obtained at Louisville since 1928. Continuous flow records have been obtained for Middle and South Fork Beargrass Creek, Pond Creek, and Floyds Fork since August 1944. Flood-stage and floodflow frequency curves have been developed from these records and are available for water development planning purposes and for design of control and use structures.

A flood-inundation map is available for the 1937 flood, but similar maps are not available or are incomplete for the later major floods. Such maps are essential to fix precise floodwater elevations and limits.

Modern topographic maps are available for the entire area but have been rapidly outdated by construction activities.

APPLICABILITY OF EXISTING DATA FOR MANAGEMENT PURPOSES

Design of control structures and many planning and zoning activities related to flooding are based on the availability of basic hydrologic records. Flood-frequency curves provide an evaluation of the average frequency of recurrence which may be expected for floods of various magnitudes on the Ohio River at Louisville. Based on this evaluation, a flood equaling or exceeding flood stage—crest elevation, 431 feet msl (mean sea level); peak discharge, 500,000 cfs—may be expected to occur every 1 or 2 years, on the average.

On this same basis average recurrence frequencies for floods of other magnitudes on the Ohio River at Louisville are as follows:

Recurrence interval (years)	Crest elevation (ft above msl)	Peak discharge (cfs)
20	445.5	720,000
50	450	820,000

Most floods and all high floods on the Ohio River at Louisville have occurred during the 4-month period January through April. Major floods rise and recede at a relatively slow rate, usually remaining at or near the crest for several days. For example, in the record 1937 flood, the stage of the Ohio River at Louisville was within a foot of the crest for 3 days and within 5 feet of the crest for 9 days.

Damage from flooding on tributary streams in Jefferson County could be relieved further by small flood-control structures and reservoirs in the upper reaches of the streams. The water thus stored could be used for irrigation and stock supplies and for recreation if the quality is satisfactory. The planning for these structures should be done in conjunction with an adequate program of planning and zoning to insure that residential building does not take place in floodwater-retention areas. To this end flood-inundation maps should be prepared for all tributary basins to indicate areas where waters will pond during and after floods.

Collection and analysis of continuous-flow records should be continued to monitor changes brought about by flood-control structures and urbanization. The addition of hundreds of acres of streets, drives, sidewalks, and roofs will increase the speed and magnitude of runoff, and existing frequency curves will need to be adjusted accordingly.

Flood-inundation maps should be updated as rapidly as construction progresses and land contours are changed. These maps should be published and made available to all interested users.

DROUGHTS

Periods of unusual dryness occur at frequent intervals in the Louisville area, but the periods do not follow a regular sequence and extreme conditions do not prevail for long periods of time. Serious droughts occurred in the summer of 1930 and in the successive summers of 1952–54. From the standpoint of the area's water resources, the seriousness of a drought is measured by its effect on water supply, power generation, and waste disposal. The usual effects are lowering of streamflow and ground-water levels.

CURRENT CONDITIONS

Droughts of the magnitude experienced in the Louisville area have little effect on municipal and industrial water supplies and on power generation. Because of the large volume of water flowing in or stored in the major sources of these supplies (the Ohio River and the deposits of alluvial sand and gravel), prolonged drought rarely lowers the supply to a point that approaches the demand.

Local water problems, however, are caused by droughts. Water shortages become acute in the uplands of the eastern and southeastern parts of Jefferson County where public water supplies are not available. Flow in most of the streams ceases and many shallow wells, springs, cisterns, and ponds become dry. Water for domestic and stock uses must be hauled into the area affected. Lack of streamflow for dilution of sewage and industrial waste creates a health hazard in some localities. Growth of algae during these periods imparts an unpleasant taste that is difficult to eliminate from the water.

AVAILABLE HYDROLOGIC DATA AND ADEQUACY

Flow records are available for the Ohio River and for the larger tributary streams in Jefferson County and are adequate to indicate the seriousness of drought. Drought-frequency curves showing the recurrence expectancy of minimum flows have been developed from these records and are adequate for use in planning for reservoir-storage facilities for emergency supply and for dilution of waste. Available ground-water information includes continuous and periodic water-level measurements in sand-and-gravel aquifers and periodic measurements in bedrock aquifers. Quantitative estimates of ground water in storage are available for most sand-and-gravel aquifers but are not available for bedrock aquifers. The available data are adequate to indicate the effect of droughts on sand-and-gravel aquifers and to predict problem areas. Additional information is needed for bedrock aquifers.

APPLICABILITY OF EXISTING DATA FOR MANAGEMENT PURPOSES

Flow data indicate that droughts have little effect on the adequacy of the Ohio River to supply water needs at current use rates and at projected use rates for the near future. The minimum daily flow of the Ohio River of 2,100 cfs recorded in 1930 during the height of the most serious drought of record is shown to be about 11 times greater than the maximum daily pumpage to date (1962) by the Louisville Water Company. Thus, water managers can plan for greater withdrawals from the Ohio River without fear of depleting the supply. In contrast, the flow of most tributary streams in the uplands of Jefferson County recedes to a very low quantity in late summer and fall, and the streams sometimes go dry for periods of a few days to a few weeks. The use of these streams as sources of perennial water supply or for dilution of waste would require that storage facilities be provided. The drought-frequency curves can be used to determine the amount of storage required to maintain specific outflow rates for a specific period of time.

Additional ground water is available for development from the sand-and-gravel aquifer in the flood plain. The potential supply available from the deposit of sand and gravel without depletion of storage is estimated to be about 370 mgd (Bell, 1962). Thus, the estimated average withdrawal of about 40 mgd in 1962 is only 11 percent of the available supply. Drought decreases the amount of ground water in storage in the sand-and-gravel deposit, but the long-term record of water-level measurements shows that there is little need for concern during the average drought. A more serious drought, such as the droughts experienced in the three successive summers of 1952–54, caused water levels in two centers of pumping to decline to levels that were only 10 feet above the surface of the bedrock. The amount of the decline that may have been due to increased pumping is difficult to assess, however.

The available records indicate that water levels in the bedrock aquifers of the uplands are more affected by drought than are those in the flood plain. Springs and the shallower wells often go dry during average droughts. The coverage of periodic water-level measurements is not now adequate to indicate minimum levels for all parts of the upland, but the data can be used to predict minimum levels, which can be used to specify the desired depth of drilling of wells in bedrock. Sufficient ground water is available to sustain the yield of many more wells in the area, provided that the wells are drilled to the proper depth.

CHEMICAL QUALITY AND POLLUTION

CURRENT CONDITIONS

Through the efforts of ORSANCO and Federal, State, and local governments, almost a billion dollars has been invested by cities and towns in the Ohio Valley for pollution-abatement facilities. Sewage-treatment plants serving 90 percent of the sewer-using population of the Ohio Valley are in operation or under construction (1962); 97 percent of the population on the main stem of the Ohio River is thus served. In addition, ORSANCO minimum requirements for waste control, are being met by 85 percent of the industrial establishments. As a result the quality of the water in the Ohio River at Louisville has improved steadily in the 14 years since ORSANCO was formed. Periodic monitoring of the quality of the Ohio River is done by the Louisville Water Company in cooperation with ORSANCO.

The quality of the water in the tributary streams in Jefferson County is not monitored on a systematic basis but is checked periodically by State and local health agencies. The quality has been improved by the extension of sewage systems and the installations of sewage-treatment facilities for suburban developments. The chemical character of the water in Pond Creek is altered by industrial wastes discharged into it, and thus its quality is the least acceptable of all the tributary streams.

The chemical quality of ground water in the area is suitable for domestic and some industrial uses except in a few local areas where the water is contaminated by outside sources. The ground water is generally hard; water from alluvium contains a high concentration of iron. In addition, a high concentration of sulfate is present in alluvial ground water in the north-central part of the city. The presence of these constituents requires that the water be treated for some industrial uses. The water from alluvium is sampled periodically by the Geological Survey at 12 wells, and local industries collect samples at additional wells.

AVAILABLE HYDROLOGIC DATA AND APPLICABILITY FOR MANAGEMENT PURPOSES

Data on the quality of the Ohio River water are available through the monitoring system of ORSANCO and the Louisville Water Company and are probably adequate for most management decisions. The type and cost of treatment for various requirements can be estimated from the accumulated data, and changes in treatment needed for changing river quality are forecast from the monitoring system. The river quality should change little in the reach through Jefferson

County, provided that the quality of the water entering the main stream from the several tributary streams is controlled.

Some analyses of the water from the smaller streams in the county are available and are useful for planning and for developing supplies. The existing data are probably adequate to show the suitability of the water for specific uses. However, the usefulness of the data could be enhanced by periodic monitoring of the streams downstream from known or potential sources of pollution. Changes in quality with time would be indicated and would serve as a guide for future treatment.

Sampling and analysis of ground water in the alluvial area of Louisville is done annually by the Geological Survey. There is no periodic sampling from wells in the bedrock of the uplands, but spot analyses are available for this area. The existing data on quality of ground water are sufficient to show the suitability of the water for specific uses. They are also adequate to show the location and extent of the concentrations of mineral constituents and the physical properties of the ground water that are objectionable. Periodic sampling near known centers of contamination should be continued to indicate changes in quality.

DRAINAGE

Lack of adequate surface drainage is a pressing problem when it becomes detrimental to human health and well-being and affects the economy of a community. Areas of poor drainage that are subject to waterlogging affect the operation of individual household sewage-disposal systems and become a health hazard. Heavy rains sometimes overload the smaller drainageways, causing local floods. A problem also exists during long periods of little or no runoff when drainage channels become overgrown with weeds or serve as breeding grounds for mosquitoes.

CURRENT CONDITIONS

The low-lying areas in the southern and southwestern parts of Louisville and Jefferson County, extending from Shively northeast to the St. Matthews area, part of which formerly was known as the "Wet Woods," have little topographic relief and are underlain by silt and clay or impermeable shale at shallow depth. Downward seepage of water is restricted, and during rainy seasons water accumulates in numerous small depressions. Natural drainage is poor and water is carried off primarily in manmade ditches, some of which are too shallow or narrow to drain away the water as fast as it accumulates.

Ponding and saturation of the soil on top of the shale often result in flooded basements and in malfunction of septic tanks and leaching fields. The drainage problem is aggravated in summer months because the ditches become clogged with weeds and refuse that impede the flow of water.

AVAILABLE HYDROLOGIC DATA AND APPLICABILITY

Problems of inadequate drainage were not within the scope of the Survey's water-resource investigations in the Louisville area. The Louisville Metropolitan Sewer District has investigated and made recommendations on the need for storm sewers, drainage ditches, culverts, and concrete-lined channels within the city of Louisville and in southwestern Jefferson County. There is a need for a similar study of the whole of Jefferson County outside the city. Many of the local problems are related to impermeable soil and rock material that limit subsurface drainage. Some of the problems in the past have been lessened by restrictions on the installation of new septic tanks and leaching fields in saturated areas and by the gradual extension of storm and sanitary sewers to serve the problem areas.

Data used in solving drainage problems include data on magnitude of runoff with time from the tributary basins, geologic and subsurface maps, and information on the depth to the water table.

CONCLUSIONS

The abundance of water in the Ohio River and in the alluvium beneath the flood plain practically precludes a serious shortage of water in the Louisville area. The minimum flow of record of the Ohio River at Louisville of 2,100 cfs (1,360 mgd) plus the estimated potential available ground water of 370 mgd far exceeds the 211 mgd of water withdrawn for public and industrial uses in 1962.

The Ohio River supplies water for all uses in the area and is the source of the municipal supply for Louisville. Ground water in the alluvium is utilized for industrial cooling and, in the southwestern part of the area, is also a source of municipal supply. Limestone underlying the alluvium in the west-central part of Louisville is a secondary source of water for industrial cooling. Bedrock in the uplands yields water to some wells and springs for domestic and stock uses.

Natural waters in the area are generally of the calcium bicarbonate or calcium magnesium bicarbonate type and contain varying amounts of sulfate. Ground water is very hard and commonly contains iron in excess of 1 ppm.

Water problems of the area are chiefly those of managament and are associated with floods, drought, drainage, and the distribution and quality of available supplies.

Much information on water resources, contained in reports resulting from water investigations during the past two decades, has been helpful to water users for planning and developing supplies. Although the data are applicable in similar situations, up-to-date water information will be needed to resolve problems created by demands in the future.

SELECTED REFERENCES

American Water Works Association Journal, 1945, Conservation of ground water in the Louisville area, Kentucky: Am. Water Works Assoc. Jour., v. 37, no. 6, p. 543–560.

Bell, E. A., 1962, The ground-water situation in the Louisville area, Kentucky, 1945–61: Kentucky Geol. Survey, ser. 10, Inf. Circ. 10, 24 p.

Bell, E. A., Kellogg, R. W., and Kulp, W. K., 1963, Progress report on the ground-water resources of the Louisville area, Kentucky, 1949–55: U.S. Geol. Survey Water-Supply Paper 1579, 49 p.

Butts, Charles, 1915a, Geological map of Jefferson County, Kentucky: Frankfort, Ky., Kentucky Geol. Survey.

——— 1915b, Geology and mineral resources of Jefferson County, Kentucky: Kentucky Geol. Survey, ser. 4, v. 3, 270 p.

Caye, W. M., 1939, Ground water-well report: Louisville, Ky., Comm. of Sewerage of Louisville, 24 p., 9 illus.

Commissioners of Sewerage of Louisville, 1942, Final report of the Commissioners of Sewerage of Louisville, 1919–42: Louisville, Ky., p. 369–387, 6 figs.

Diehl, R. B., 1943, The diminishing supply and conservation of the underground water supply of Louisville, Kentucky: Louisville, Ky., Diehl Pump and Supply Co. open-file rept., 20 p., 2 illus.

Grover, N. C., 1938, Floods of Ohio and Mississippi Rivers, January-February 1937, with a section on the flood deposits of the Ohio River, January-February 1937, by G. R. Mansfield: U.S. Geol. Survey Water-Supply Paper 838, p. 693–736.

Guyton, W. F., 1944, Artificial recharge of ground-water reservoir with water from city's surface supply at Louisville, Ky.: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div., 6 p., 1 fig.

——— 1945, Depleted wells at Louisville recharged with city water: Water Works Eng., v. 98, no. 1, p. 18–20.

——— 1946, Artificial recharge of glacial sand and gravel with filtered river water at Louisville, Ky.: Econ. Geology, v. 41, no. 6, p. 644–658.

Guyton, W. F., Stuart, W. T., and Maxey, G. B., 1944, Progress report on the ground-water resources of the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div. and city of Louisville, 20 p., 12 figs.

Guyton, W. F., and Sublett, H. E., 1944, Conservation of ground water in the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div., 4 p., 9 illus.

Hamilton, D. K., 1944, Ground water in the bedrock beneath the glacial outwash in the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div., 22 p. incl. maps.

Kazmann, R. G., 1948, River infiltration as a source of ground-water supply: Am. Soc. Civil Engineers Trans., v. 113, p. 404–420.

Louisville Water Company, Annual reports: Louisville, Ky.

MacCary, L. M., 1955, Map of the Louisville area, Kentucky, showing contours on the bedrock surface: U.S. Geol. Survey Hydrol. Inv. Atlas HA–5, 1 sheet.

——— 1956, Availability of ground water for domestic use in Jefferson County, Kentucky: U.S. Geol. Survey Hydrol. Inv. Atlas HA–8, 5 p.

McFarlan, A. C., 1943, Geology of Kentucky: Lexington, Ky., Univ. Kentucky, 531 p.

Maier, F. J., 1950, Fluoridation of public water supplies: Am. Water Works Assoc. Jour., v. 42, pt. 1, p. 1120–1132.

Maxey, K. F., 1950, Report on the relation of nitrate concentration in well waters to the occurrence of methemoglobinemia: Natl. Research Council, Bull. Sanitary En., app. D., p. 265.

Ohio River Valley Water Sanitation Commission, 1950, Pollution patterns in the Ohio River: Cincinnati, Ohio, 30 p.

Price, W. E., Jr., 1964a, Geology and hydrology of alluvial deposits along the Ohio River between Prospect and southwestern Louisville, Kentucky: U.S. Geol. Survey Hydrol. Inv. Atlas HA–130, 2 sheets.

——— 1964b, Geology and hydrology of alluvial deposits along the Ohio River between southwestern Louisville and West Point, Kentucky: U.S. Geol. Survey Hydrol. Inv. Atlas HA–111, 2 sheets.

Rorabaugh, M. I., 1946a, Ground-water resources of the southwestern part of the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Rubber Reserve Co., city of Louisville, and Jefferson County. 39 p.

——— 1946b, Inventory of water wells, Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with city of Louisville and Jefferson County, 35 p., 1 fig.

——— 1949a, Investigation discloses large ground-water supply: The Louisville Engineer and Scientist, v. 5, no. 4, p. 1–10.

——— 1949b, Progress report on the ground-water resources of the Louisville area, Kentucky, 1945-49: U.S. Geol. Survey open-file rept. prepared in coop. with city of Louisville and Jefferson County, 64 p.

——— 1951, Stream-bed percolation in development of water supplies: Brussels, Internat. Assoc. Hydrology, p. 165–174.

——— 1956a, Prediction of ground-water levels on basis of rainfall and temperature correlations: Am. Geophys. Union Trans., v. 37, no. 4, p. 436–441.

——— 1956b, Ground water in northeastern Louisville, Kentucky: U.S. Geol. Survey Water-Supply Paper 1360-B, p. 101–169.

Rorabaugh, M. I., Schrader, F. F., and Laird, L. B., 1953, Water resources of the Louisville area, Kentucky and Indiana: U.S. Geol. Survey Circ. 276, 49 p., 2 pls.

Schrader, F. F., 1945, Water: Univ. Kentucky, Bur. School Service Bull., v. 18, no. 2, p. 45–122.

Shoecraft, E. C., Drury, W. R., and McNamee, R. L., 1944, Report on water resources for the Underground Water Users Association, Louisville, Ky.: Open-file rept., 120 p., 20 illus.

Spicer, H. C., 1946, Electrical resistivity studies of the depth to bedrock in the Louisville area, Kentucky: U.S. Geol. Survey open-file rept., 21 p., 2 figs.

Stuart, W. T., 1944, Conservation of ground water, including artificial recharge, by two companies in the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div., 10 p.

Sublett, H. E., 1945, Chemical quality of ground water in the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div., 8 p., 4 figs.

U.S. Geological Survey, 1944, Chemical analyses of water from wells in the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div., 6 p.

——— 1945, Drillers' logs of wells and test borings in the Louisville area, Kentucky: U.S. Geol. Survey open-file rept. prepared in coop. with Kentucky Dept. Mines Minerals Geol. Div., 70 p., 1 map.

——— issued annually through 1960 and on a 5-year basis thereafter, Surface-water supply of the United States, Part 3–A, Ohio River basin except Cumberland and Tennessee River basins: U.S. Geol. Survey water-supply papers.

——— issued annually through 1955, on a 3-year basis for 1956-58, and on a 5-year basis thereafter, Water levels and artesian pressure in observation wells in the United States, Part 2, Southeastern States: U.S. Geol. Survey water-supply papers.

U.S. Public Health Service, 1962, Drinking water standards: U.S. Public Health Service Pub. no. 956, 61 p.

Walker, W. H., 1957, An aquifer test in the southwestern part of the Louisville area, Kentucky: U.S. Geol. Survey open-file rept., 41 p.

Wenger, H. V., 1943, Report on the ground-water supply, Louisville, Kentucky: [U.S.] War Production Board open-file rept., 12 p.

Whitesides, D. V., and Nichols, Edith S., 1961, Water levels in observation wells in Jefferson County, Kentucky, 1935 through 1960: Kentucky Geol. Survey, ser. 10, Inf. Circ. 6, 75 p.

O

Hydrology of the Alluvial Deposits in the Ohio River Valley in Kentucky

By JOHN T. GALLAHER and W. E. PRICE, Jr.

GEOLOGICAL SURVEY WATER-SUPPLY PAPER 1818

Prepared in cooperation with the Commonwealth of Kentucky, University of Kentucky, Kentucky Geological Survey, and the Kentucky Department of Commerce

UNITED STATES GOVERNMENT PRINTING OFFICE, WASHINGTON : 1966

The least favorable areas for the development of ground-water supplies are in the valley of the Licking River and near the walls of the Ohio River valley. The alluvium of the Licking River valley is fine grained and yields only small quantities of water to wells; the highest reported yield is 60 gpm. The chances of obtaining large supplies of water become progressively less closer to the valley walls, because the section of saturated alluvium becomes thinner and generally finer grained.

Probably the best areas for obtaining large ground-water supplies are where thick deposits of sand and gravel are present in the old deep channel of the Ohio River beneath the cities of Ludlow, Covington, Newport, and Bellevue.

In terms of water quality, the poorest areas for development are those close to the valley walls and near areas of known industrial contamination of water. The most favorable sites are near the bank of the Ohio River. Here the river water enters the sand and gravel and dilutes the hardness and dissolved solids of the ground water to less-than-average concentrations. Ground water in the Licking River valley seems to be less mineralized than that in most places in the Ohio Valley alluvium, but more analyses are needed to substantiate this conclusion.

LOUISVILLE AREA

LOCATION

The Louisville area is in a large alluvial bottom near the midpoint of the Ohio River valley in Kentucky. For convenience of discussion, the authors have divided the Louisville area into subareas (fig. 21) on the basis of ground-water pumpage and industrial usage.

More detailed study has been made of the geology, hydrology, and quality of water in this area than at any other place in the Ohio River valley. To date more than 25 atlases and written reports have been published concerning the area. The latest of these reports are Hydrologic Investigations Atlases 130 and 111 ("Geology and Hydrology of Alluvial Deposits along the Ohio River between Prospect and Southwestern Louisville, Kentucky," and "Geology and Hydrology of Alluvial Deposits along the Ohio River between Southwestern Louisville and West Point, Kentucky" (Price, 1964)) and Water-Supply Paper 1819–C ("Summary of Hydrologic Conditions of the Louisville Area, Kentucky" (E. A. Bell, 1966)). Other pertinent reports are included in the list of references at the end of this report. Because of the amount of detailed coverage, this section is intended to serve only as a brief summary of the hydrologic system of the area.



FIGURE 21.—Distribution of ground-water pumping in the Louisville area, 1962.

GEOLOGY AND SATURATED THICKNESS

The bedrock underlying the Ohio River alluvium of the area is made up primarily of limestones and shales of Silurian, Devonian, and Mississippian ages. The old deep channel, cut into these rocks down to an altitude of about 335 feet, trends southwest across the area from Towhead Island to a point south of the Rubbertown industrial subarea. Upstream and downstream from these points, the old channel approximately follows the present river channel.



ouisville area, 1962.

ss

n of the area is
n, Devonian, and
hese rocks down
ss the area from
dustrial subarea.
channel approxi-

The alluvial deposits in the Louisville area are mostly of glacial origin. Their thickness ranges from 0 to 150 feet, depending upon the altitude of the erosional surface of the underlying bedrock formations. The upper part of the unconsolidated deposits consists of 5–40 feet of relatively impermeable clay, silt, and fine sand. Beneath this layer are thick deposits of permeable sand and gravel. The general distribution of the alluvial deposits is shown in figure 22.

The saturated thickness of alluvium varies widely with local pumpage, but ranges from 0 to 80 feet. The water table (fig. 22), generally slopes toward the river, but heavy pumpage has created local cones of depression. Close to the river, pumping levels have been lowered to such a degree locally that the normal water-level gradient is reversed, and the water flows from the river toward pumped wells.

WATER SOURCE AND USE

More than 40 billion gallons of water is used annually (Kulp and Hopkins, 1960) in the Louisville area. Three-fourths of this is taken from the Ohio River for public supply; most of the remainder of the water comes from alluvium and is used by the Louisville Extension Water District for public supply and by most of the industries for manufacturing, air conditioning, and cooling purposes. Supplies of



FIGURE 22.—Water-level contours in the Louisville area, December 1960 (from Whitesides and Nichols, 1961). Altitude given in feet above mean sea level. Contour interval, 5 feet. Arrows indicate direction of ground-water movement.

ground water in this area are obtained primarily from large-diameter drilled wells that penetrate the full thickness of the aquifer; exceptions are two radial-collector wells within a few hundred feet of the Ohio River. Some water used by local distilleries is pumped from the limestone aquifer underlying the alluvium.

Much water, especially that which has been used for cooling purposes, is returned to the aquifer by means of recharge wells. Though primarily a means of avoiding payment of sewer-rental taxes, this method of disposal helps to maintain an overall balance between the total withdrawal and the total recharge of the aquifer. From 1944 to 1960 the amount of water returned to the aquifer by artificial recharge ranged from 0.6 to 1.6 mgd (million gallons per day). There has been an apparent decline in this practice within the past several years. however, and the recharge amount reported by industry for 1962 was only 0.517 mgd.

WELL YIELDS AND AQUIFER TESTS

The average yield for all drilled wells in alluvium is probably about 200 gpm, but each of the better wells of the area produces 400–500 gpm, and a few yield 800–1,000 gpm. The two radial-collector wells reportedly pump 2,600 and 3,500 gpm. Specific capacities for wells in alluvium range from 6 to 500 gpm per ft. with a median of 38 gpm per ft. Permeabilities, determined on the basis of laboratory studies of alluvial samples, ranged from 120 to 1,700 gpd per sq ft, with a median of 500 gpd per sq ft. Transmissibilities, determined by pumping tests, ranged from 18,000 to 121,000 gpd per ft, with a median of 68,500 gpd per ft.

QUALITY OF WATER

Ground-water quality varies widely throughout the area; it changes according to location, type of underlying bedrock, and rate of withdrawal.

Water from wells in limestone is very highly mineralized. Hardness as $CaCO_3$ averages about 580 ppm, and sulfates average about 450 ppm.

Water in alluvium varies in quality but is generally very hard, high in bicarbonate and iron, and, in many places, high in sulfate. Average hardness of water from wells in alluvium in the part of Louisville included in Hydrologic Investigations Atlas 130 is 422 ppm and in Hydrologic Investigations Atlas 111, is 296 ppm. Sulfate content of water in these atlas areas averaged 162 and 26 ppm. The alluvium in the upstream part (HA–130) overlies limestone bedrock, from which it derives its high mineralization. Downstream, the underlying impermeable shale effectively prevents much of the mineralized limestone water from entering the alluvium.

GROU

There is also cons
to variation in distar
within a few hundr
in wells that are farr
water that enters the
formation by infiltra

A notable change
pumping. Large w
areas and thereby i
water is softer and
pumpage has not in
the West-Central su
bedrock are pumpin
water.

Average ground-w
from 47° to 66° F. d
river water induced l

The most favorabl
of good-quality wat
makes perennially l
southwestern Louis
Louisville Gas & Ele
subarea, however, t
limited because the
lowered to the maxi
the river and in all
mineralized water.

The alluvial area
vestigations Atlas 9
the Ohio Valley. It
37 river miles down
half a mile wide) it
this point. The lar
Flipping Creek and
level at the riverban
at the upstream an
land, however, is be

There is also considerable variation in the quality of water, owing to variation in distance of wells from the Ohio River. Water in wells within a few hundred feet of the river is less mineralized than that in wells that are farther away. This reflects the diluting effect of river water that enters the alluvium during flood stage or is induced into the formation by infiltration.

A notable change in water quality has occurred in areas of heavy pumping. Large withdrawals have lowered the water table in some areas and thereby induced infiltration from the river; the pumped water is softer and of lower overall mineral content. Where heavy pumpage has not induced infiltration from the river, however, as in the West-Central subarea, wells in alluvium overlying the limestone bedrock are pumping increasing amounts of hard, highly mineralized water.

Average ground-water temperature in the area is 58°F. The range, from 47° to 66° F, depends largely on the temperature and quantity of river water induced by infiltration.

CONCLUSIONS

The most favorable areas for future development of large quantities of good-quality water are near the river, where induced infiltration makes perennially large supplies possible. This condition exists in southwestern Louisville, and in northeastern Louisville from the Louisville Gas & Electric plant to Harrods Creek. In the Rubbertown subarea, however, the opportunity for further development is very limited because the cone of depression there (fig. 22) has already been lowered to the maximum allowable for sustained yields. Wells near the river and in alluvium overlying shale bedrock produce the least mineralized water.

BRANDENBURG AREA

LOCATION

The alluvial area near Brandenburg, included in Hydrologic Investigations Atlas 95, is typical in size to many river bottoms along the Ohio Valley. It is a crescent-shaped bottom 6½ miles long about 37 river miles downstream from Louisville. Though narrow (about half a mile wide) it occupies the width of the Ohio River valley at this point. The land surface has been dissected by Doe Run and Flipping Creek and ranges in altitude from 400 feet above mean sea level at the riverbank to more than 460 feet along the valley wall and at the upstream and downstream ends of the bottom. Most of the land, however, is between 440 and 450 feet above mean sea level.

REFERENCE # 21

R. Allan Freeze

Department of Geological Sciences
University of British Columbia
Vancouver, British Columbia

John A. Cherry

Department of Earth Sciences
University of Waterloo
Waterloo, Ontario

GROUNDWATER

Prentice-Hall, Inc.
Englewood Cliffs, New Jersey 07632

Table 2.2 Range of Values of Hydraulic Conductivity and Permeability



Table 2.3 Conversion Factors for Permeability and Hydraulic Conductivity Units

	Permeability, k*			Hydraulic conductivity, K		
	cm^2	ft^2	darcy	m/s	ft/s	U.S. gal/day/ft^2
cm^2	1	1.08×10^{-3}	1.01×10^{8}	9.80×10^{2}	3.22×10^{3}	1.85×10^{9}
ft^2	9.29×10^{2}	1	9.42×10^{10}	9.11×10^{5}	2.99×10^{6}	1.71×10^{12}
darcy	9.87×10^{-9}	1.06×10^{-11}	1	9.66×10^{-6}	3.17×10^{-5}	1.82×10^{1}
m/s	1.02×10^{-3}	1.10×10^{-6}	1.04×10^{5}	1	3.28	2.12×10^{6}
ft/s	3.11×10^{-4}	3.35×10^{-7}	3.15×10^{4}	3.05×10^{-1}	1	6.46×10^{5}
U.S. gal/day/ft^2	5.42×10^{-10}	5.83×10^{-13}	5.49×10^{-2}	4.72×10^{-7}	1.55×10^{-6}	1

*To obtain k in ft^2, multiply k in cm^2 by 1.08×10^{-3}.

OVERSIZED

DOCUMENT

REFERENCE # 23

NUS CORPORATION AND SUBSIDIARIE.

TELECON NOTE

CONTROL NO. F4-8801-41	DATE: May 2, 1988	TIME: 0835

DISTRIBUTION:

McCracken County Landfill
F4-8801-41

BETWEEN: Mark Lyverse	OF: USGS, Louisville, Kentucky	PHONE: (502) 582-5241

AND: Carol Northern, NUS Corporation

Carol Northern 5/2/88

DISCUSSION:

The Ohio River is well entrenched and acts as a sink. Groundwater in the formation on either side of the river flows towards and eventually into the Ohio River.

The river is gaining water from both sides and little or no water flows under the river.

REFERENCE # 24

NUS CORPORATION AND SUBSIDIARIES | **TELECON NOTE**

CONTROL NO.	DATE: July 13, 1988	TIME: 1415
DISTRIBUTION:		
BETWEEN: John Huber	OF: Louisville Water Company	PHONE: (502) 569-3600
AND: Carol Northern		

Carol Northern 7/13/88

DISCUSSION:

The Louisville Water Company serves the city of Louisville, most of Jefferson County and parts of Bullitt and Oldham Counties, Kentucky. The Louisville Water Company (LWC) relies exclusively for water on two (2) surface water intakes on the Ohio River. One intake is located at river mile 600.6 (Zorn Avenue). The second intake is located above Herrods Creek at Mayfair Avenue and Jacobs School Road.

LWC has 205,000 customer attachments which serve approximately 700,000 people. LWC also wholesales water to other systems, including the Jeffersontown Water and Sewer Commission. These systems serve an additional 40,000 persons. The water distributed by LWC undergoes extensive treatment which includes fluoridation and chlorination.

There are private wells located within the LWC service area. These wells probably obtain water from the flood plain alluvium at depths ranging from 60-90 feet. LWC has a very liberal water main extension policy which has encouraged many private well owners to hook up to the municipal system.

To Mr. Huber's knowledge, most trailer park communities in the Louisville area use municipal water. The local health department may have more detailed information.

Areas in Jefferson County not served by LWC include the SE and SW portions of the county. Both areas are largely rural. Mr. Huber estimates there are 5,000 people in SE Jefferson County that do not have access to municipal water.

LOUISVILLE WATER CO.

DISTRIBUTION SYSTEM

REFERENCE # 25



LEGEND

12" and Larger Mains

8" and 10" Mains

6" Mains

4" and Smaller

Valves

Closed Valves

Pressure Reducing Valve (Pressure Planes Separation)

Pressure Reducing Station

Gauge Station


LIVONIA DR
DRIVE
COLUMBINE
SUNSET
CHERRY
DRIVE
ROAD
TERRY
HIPLEY
LIVONIA FOREST STANDPIPE
500,000 GAL
EL ELEV. 775
CARDINAL HILL
BOOSTER STATION
AND PUMP
IROQUOIS PARK
FINLEY MILL STANDPIPE
300,000 GAL
EL ELEV 791
Kentucky Petroleum
Waste, Inc.
SHAVINA PUMP
STATION

NUS CORPORATION AND SUBSIDIARIES REFERENCE # 26 **TELECON NOTE**

CONTROL NO.	DATE: April 26, 1990	TIME: 1415
DISTRIBUTION:		
BETWEEN: Charles Schott	OF: Louisville Water Co.	PHONE: 502-569-3600

AND: Wendell C. McLendon, NUS Corporation

Wendell C McLendon

DISCUSSION:

The Louisville Water Company serves approximately 208,500 residential, industrial, and commercial customers. The total population served is approximately 700,000. There are areas within the city of Louisville that use private wells.

Approximately 3,758 residences in Jefferson County obtain water from private wells (485 have access but have not tied on to the municipal water system).

ENDANGERED AND THREATENED SPECIES

REFERENCE # 27

U.S. FISH AND WILDLIFE SERVICE

REGION 4 - ATLANTA

Federally Listed Species by State

KENTUCKY

(E=Endangered; T=Threatened; CH=Critical Habitat determined)

Mammals	General Distribution
Bat, gray (Myotis grisescens) - E	Entire state
Bat, Indiana (Myotis sodalis) - E,CH	Entire state
Bat, Virginia big-eared (Plecotus townsendii virginianus) - E	Eastern, primarily Lee County
Cougar, eastern (Felis concolor cougar) - E	Entire state
Birds	
Eagle, bald (Haliaeetus leucocephalus) - E	Entire state
Falcon, American peregrine (Falco peregrinus anatum) - E	North
Falcon, Arctic peregrine (Falco peregrinus tundrius) - T	Entire state
Tern, least (Sterna antillarum), interior population - E	Mississippi and Ohio Rivers
Warbler, Bachman's (Vermivora bachmanii) - E	West
Warbler, Kirtland's (Dendroica kirtlandii) - E	East
Woodpecker, ivory-billed (Campephilus principalis) - E	West
Woodpecker, red-cockaded (Picoides (=Dendrocopos) borealis) - E	Southeast
Fishes	
Dace, blackside (Phoxinus cumberlandensis) - T	Upper Cumberland River System (Pulaski, Laurel, McCreary, Whitley, Knox, Bell, Harlan, and Letcher Counties
Mollusks	
Mussel, Cumberland bean pearly (Villosa (=Micromya) trabilis) - E	Roundstone Creek, Horselick Creek, Buck Creek; Little S. Fork Cumberland, Rockcastle and Middle Fork Rockcastle Rivers

CURRENT POPULATION REPORTS

Special Studies

Series P-23, No. 156

Estimates of Households, for Counties: July 1,1985



U.S. Department of Commerce
BUREAU OF THE CENSUS

BUREAU OF THE CENSUS
John G. Keane, Director
C.L. Kincannon, Deputy Director
William P. Butz, Associate Director for
Demographic Fields
Roger A. Herriot, Senior Demographic and
Housing Analyst

POPULATION DIVISION
Paula J. Schneider, Chief

SUGGESTED CITATION

U.S. Bureau of the Census, Current Population Reports, Series P-23, No. 156,
Estimates of Households, for Counties: July 1, 1985,
U.S. Government Printing Office, Washington, D.C., 1988.

For sale by Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

le 1. Estimates of Households, for Counties: July 1, 1985—Continued

ash (-) represents zero or rounds to zero. Estimates are consistent with special censuses since 1980. Corrections to 1980 census counts ot included. See text concerning rounding and average population per household)

e and county	Households				Average population per household		Population			
	July 1, 1985 (estimate)	April 1, 1980 (census)	Change, 1980-85		July 1, 1985 (estimate)	April 1, 1980 (census)	July 1, 1985 (estimate)	April 1, 1980 (census)	Change, 1980-85	
			Number	Percent					Number	Percent
tucky—Continued										
r	7,400	6,821	600	9.0	3.14	3.31	23,600	22,752	900	3.9
ton	3,600	3,259	300	9.5	2.75	2.86	9,800	9,321	500	5.5
tenden	3,500	3,466	-	1.3	2.53	2.63	9,000	9,207	-200	-2.4
nberland	2,700	2,671	100	2.3	2.72	2.70	7,500	7,289	200	3.0
iess	32,600	30,208	2,300	7.8	2.65	2.79	87,800	85,949	1,800	2.1
nonson	4,000	3,357	600	19.2	2.79	2.92	11,300	9,962	1,400	13.7
tt	2,200	2,223	-	0.9	3.00	3.11	6,700	6,908	-200	-2.6
ill	5,200	4,896	300	6.7	2.86	2.94	15,000	14,495	600	3.8
ette	83,600	75,440	8,200	10.8	2.40	2.56	212,100	204,165	7,900	3.9
ming	4,600	4,311	200	5.7	2.70	2.83	12,400	12,323	100	0.9
yd	17,200	15,973	1,200	7.8	2.94	3.04	50,800	48,764	2,100	4.2
nklin	17,100	15,681	1,400	9.2	2.48	2.58	43,900	41,830	2,100	4.9
ton	3,100	3,384	-300	-8.2	2.57	2.61	8,100	8,971	-900	-9.7
latin	1,600	1,649	-	-0.1	2.96	2.93	4,900	4,842	-	0.9
rard	4,200	3,940	300	6.6	2.74	2.73	11,600	10,853	700	6.9
ant	4,700	4,422	300	7.0	2.93	2.97	14,100	13,308	800	5.9
ves	12,800	12,775	100	0.4	2.53	2.63	32,900	34,049	-1,100	-3.3
yson	7,600	7,228	300	4.6	2.82	2.86	21,500	20,854	700	3.1
en	4,100	3,982	100	1.8	2.64	2.73	10,900	11,043	-200	-1.6
enup	13,100	12,926	200	1.4	2.90	3.01	38,200	39,132	-900	-2.3
ncock	2,600	2,552	200	8.3	2.89	3.00	8,100	7,742	300	4.1
rdin	27,600	24,610	3,000	12.3	2.79	2.98	92,300	88,917	3,400	3.8
rlan	14,300	13,849	500	3.3	2.94	3.01	42,400	41,889	500	1.1
rrison	5,900	5,461	500	8.4	2.61	2.74	15,700	15,166	500	3.3
rt	5,900	5,435	500	9.2	2.75	2.83	16,400	15,402	1,000	6.3
nderson	15,800	14,688	1,100	7.3	2.66	2.75	42,500	40,849	1,600	4.0
nry	4,900	4,564	400	7.8	2.69	2.77	13,300	12,740	600	4.7
ickman	2,200	2,229	-	-1.3	2.56	2.67	5,700	6,065	-300	-5.3
opkins	17,500	16,552	900	5.7	2.62	2.74	46,700	46,174	500	1.1
ackson	4,200	4,029	100	3.6	2.99	2.97	12,500	11,996	684,638 500	3.9
efferson	264,000	250,569	13,400	5.4	2.55	2.69	683,600	~~685,004~~	-1,400	-0.2
essamine	9,900	8,413	1,500	17.8	2.77	2.95	28,660	26,146	2,400	9.4
ohnson	8,800	8,196	600	7.5	2.88	2.94	25,700	24,432	1,300	5.2
enton	50,500	48,062	2,400	5.1	2.68	2.82	137,000	137,058	-100	-
nott	5,700	5,461	200	4.2	3.17	3.23	18,400	17,940	500	2.6
nox	10,300	9,946	400	4.1	2.89	3.01	30,200	30,239	-	-0.1
aRue	4,500	4,268	200	4.5	2.77	2.78	12,400	11,922	500	4.3
aurel	14,300	12,817	1,500	11.6	2.89	3.02	41,800	38,982	2,800	7.2
aw rence	4,900	4,662	200	4.1	3.01	3.01	14,700	14,121	600	4.2
Lee	2,800	2,632	200	6.4	2.82	2.91	8,000	7,754	200	3.1
Leslie	4,900	4,569	400	7.8	3.10	3.25	15,300	14,882	400	3.0
Letcher	10,000	10,007	-	-0.1	3.01	3.06	30,200	30,687	-500	-1.5
Lewis	4,800	4,669	100	2.2	2.97	3.09	14,300	14,545	-300	-1.7
Lincoln	6,800	6,521	200	3.6	2.83	2.91	19,200	19,053	100	0.7
Livingston	3,600	3,418	200	6.2	2.48	2.67	9,100	9,219	-100	-1.3
Logan	9,400	8,548	900	10.1	2.72	2.80	25,800	24,138	1,700	7.0
Lyon	2,200	2,211	-	0.1	2.47	2.51	6,400	6,490	-100	-0.8
McCracken	24,100	23,459	600	2.6	2.49	2.58	60,800	61,310	-500	-0.8
McCreary	5,400	4,853	500	10.3	3.01	3.16	16,500	15,634	900	5.5
McLean	3,700	3,671	100	1.8	2.63	2.72	9,900	10,090	-100	-1.4
Madison	18,400	16,809	1,600	9.2	2.57	2.73	54,500	53,352	1,200	2.2
Magoffin	4,600	4,151	400	10.2	3.10	3.24	14,300	13,515	700	5.5
Marion	5,900	5,599	300	6.0	2.95	3.14	17,800	17,910	-100	-0.5
Marshall	9,900	9,427	500	5.1	2.57	2.68	25,900	25,637	200	0.9
Martin	4,300	4,182	100	3.4	3.30	3.33	14,300	13,925	400	2.6
Mason	6,300	6,361	-	-0.4	2.69	2.77	17,200	17,765	-600	-3.2

COVERAG

STATE	COUNTY	STATE NAME	COUNTY NAME
18	43	Indiana	Floyd Co
21	29	Kentucky	Bullitt Co
21	111	Kentucky	Jefferson Co

CENTER POINT AT STATE : 21 Kentucky
COUNTY : 111 Jefferson Co

Press RETURN key to continue...

REGION OF THE COUNTRY

Zipcode found: 40221 at a distance of 3.1 Km

STATE	CITY NAME	COMMUNITY	FIPSCODE	LATITUDE	LONGITUDE
KY	LOUISVILLE	STANDIFORD	21111	38.1767	85.7400

Press RETURN key to continue ...

CENSUS DATA

KENTUCKY PETROLEUM PRODUCTS
LATITUDE 38: 8:57 LONGITUDE 85:44: 8 1980 POPULATION

KM	0.00-.400	.400-.810	.810-1.60	1.60-3.20	3.20-4.80	4.80-6.40	SECTOR TOTALS
S 1	0	0	0	1104	1429	10919	13452
S 2	0	0	0	4802	7405	8076	20283
S 3	0	0	0	632	7225	11709	19566
S 4	0	0	0	4626	6378	1746	12750
S 5	0	0	0	0	1713	1636	3349
S 6	0	0	0	2919	1855	5406	10180
S 7	0	0	0	3534	4410	1720	9664
S 8	0	0	0	2556	12355	18355	33266
RING TOTALS	0	0	0	20173	42770	59567	122510

Press RETURN key to continue ...

STAR STATION

INDEX NUMBER	STATION NAME	LATITUDE DEGREE	LONGITUDE DEGREE	PERIOD OF RECORD	STABILITY CLASSES	DISTANCE (km)
93821	LOUISVILLE/STANDIFOR	38.1833	85.7333			6 3.80
13807	FT KNOX/GODMAN KY	37.9000	85.9667			6 34.29
93820	LEXINGTON/BLUE GRASS	38.0333	84.6000			6100.12
93814	COVINGTON/GTR CINN K	39.0667	84.6667			6137.84
93808	BOWLING GREEN/CITY-C	36.9667	86.4333			6145.03
93817	EVANSVILLE/DRESS IN	38.0500	87.5333			6157.55
93819	INDIANAPOLIS/WEIR CO	39.7333	86.2833			6182.24

Press RETURN key to continue ...

U.S. SOIL DATA

STATE : KENTUCKY

LATITUDE : 38: 8:57 LONGITUDE : 85:44: 8
THE STATION IS INSIDE H.U. 5140102

GROUND WATER ZONE	:	7			
RUNOFF SOIL TYPE	:	3			
EROSION	:	4.7060E-03			CM/MONTH
DEPTH TO GROUND WATER BETWEEN	:	0.0000E+00	AND	1.0000E+02	
FIELD CAPACITY FOR TOP SOIL	:	8.0000E-02			
EFFECTIVE POROSITY BETWEEN	:	1.0000E-02	AND	1.0000E-01	
SEEPAGE TO GROUNDWATER BETWEEN	:	2.7800E+02	AND	2.7800E+03	CM/MONTH
DISTANCE TO DRINKING WELL	:	2.5000E+04			CM

Press RETURN key to continue ...

U.S. CITY

STATE	PLACE NAME	FIPSCODE	LATITUDE	LONGITUDE
KY	FAIRDALE	21111	38.1050	85.7600

Press RETURN key to continue ...

MENU: Geodata Handling Data List procedures

1. Site level retrieval of data (SITERET)
2. Access Census Data (CENSUS)
3. Determine County Coverage (COVERAGE)
4. Geographic Data Management (GEODM)
5. HUCODE/SOIL locator (HUCODE)
6. Convert to Lat/Long (LATLON)
7. Lookup/Examine Star Station Data (STAR)
8. Find US cities (USCITY)
9. Find Soil Survey Status of Counties (SSURVEY)

Enter an option number or a procedure name (in parentheses)

```
or a command: HELP, HELP option, BACK, CLEAR, EXIT, TUTOR
GEMS>

Enter an option number or a procedure name (in parentheses)
or a command: HELP, HELP option, BACK, CLEAR, EXIT, TUTOR
GEMS>

Enter an option number or a procedure name (in parentheses)
or a command: HELP, HELP option, BACK, CLEAR, EXIT, TUTOR
GEMS> EXIT

Type YES to confirm the EXIT command; type NO to restart GEMS
GEMS> YES
$
$ LOGOUT
 WRT           logged out at 28-SEP-1990 14:42:08.70
 Itemized resource charges, for this session, follow:

NODE: VAXTM1
ACCT: NTIS                              START TIME:     28-SEP-1990 14:37:53.54
PROJ: NTISNUCN                          FINISH TIME:    28-SEP-1990 14:42:08.70
USER: WRT                               BILLING PERIOD:900901
UIC:  [000750,000112]                   WEEKDAY:        FRIDAY
BAUD:                                   TERMINAL PORT: TXA6

DESCRIPTION OF CHARGE                    QUANTITY                EXPENDITURE
-------------------------------------------------------------------------------

  ALL CHARGE LEVELS
    300  baud             (Seconds)          255                      0.6910
    CPU TIME              (Seconds)            6                      0.4300
                                                                     ----------
    TOTAL FOR THIS SESSION                                        $      1.1210
NODE 3157  HOST 1038: DROPPED BY HOST
please log in: X

password:
```

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION IV
345 COURTLAND STREET, N.E.
ATLANTA, GEORGIA 30365

2657

4WD-WPB
SEP 6 1991

Mr. Carl Millanti
Uncontrolled Sites Branch
Kentucky Department for
Environmental Protection
18 Reilly Road
Frankfort, Kentucky 40601

Dear Mr. Millanti:

This letter serves to inform you of EPA's decision regarding the disposition of sites under investigation in Kentucky. The following is a list of sites which were investigated and their respective dispositions:

1. Sun Oil Company - Camp Breckinridge
   EPA ID No. KYD991276403
   SSI Phase 1 Report - FIT Lead - Concur with recommendation for NFRAP due to lack of targets.

2. Sandgap Dump
   EPA ID No. KYD980501332
   SSI Phase 1 Report - FIT Lead - Concur with recommendation for NFRAP due to lack of targets.

3. Tartar Farm
   EPA ID No. KYD985066471
   PA Report - State Lead - Do not concur with State recommendation for NFRAP; additional environmental sampling is necessary to fully evaluate effect of earlier removal action. Monitoring well sampling continues to detect low levels of volatile organic compounds in the groundwater.

4. Kentucky Petroleum Products
   EPA ID No. KYD061564001
   SSI Phase 1 Report - FIT Lead - Concur with recommendation for NFRAP due to lack of targets.

5. Bramer's Landfill
   EPA ID No. KYD980728851
   SSI Phase 2 Report - FIT Lead - Concur with recommendation for NFRAP due to lack of targets and small amount of contamination.

I have also enclosed a copy of the respective reports for your files. If you should have any questions, please feel free to contact me at (404) 347-5065.

Sincerely yours,

Craig A. Benedikt
Environmental Scientist

cc: Ramona Klein

Enclosure

CB:cb:DOC MILLANTI:DISK BENEDIKT #3:09/05/91:X5065

4WD-SAS 4WD-SAS

BENEDIKT DEIHL

KYD061564001
Kentucky Petroleum Prods
4019 Blanton Rd
Louisville KY
Jeff Cuty
in Wastelan

POTENTIAL HAZARDOUS WASTE SITE
IDENTIFICATION AND PRELIMINARY ASSESSMENT

EPA

REGION: IV

SITE NUMBER (to be assigned by HQ): KY0000000220 30

NOTE: This form is completed for each potential hazardous waste site to help set priorities for site inspection. The information submitted on this form is based on available records and may be updated on subsequent forms as a result of additional inquiries and on-site inspections.

GENERAL INSTRUCTIONS: Complete Sections I and III through X as completely as possible before Section II (Preliminary Assessment). File this form in the Regional Hazardous Waste Log File and submit a copy to: U.S. Environmental Protection Agency; Site Tracking System; Hazardous Waste Enforcement Task Force (EN-335); 401 M St., SW; Washington, DC 20460.

I. SITE IDENTIFICATION

A. SITE NAME: Kentucky Petroleum Products Co.

B. STREET (or other identifier): 4019 Blanton Lane

C. CITY: Louisville

D. STATE: KY

E. ZIP CODE: 40216

F. COUNTY NAME: Jefferson

G. OWNER/OPERATOR (If known)

1. NAME: Same

2. TELEPHONE NUMBER: (502)447-1802

H. TYPE OF OWNERSHIP

☐ 1. FEDERAL ☐ 2. STATE ☐ 3. COUNTY ☐ 4. MUNICIPAL ☒ 5. PRIVATE ☐ 6. UNKNOWN

I. SITE DESCRIPTION: This is a facility which reclaims waste oil, separates out sludge and water, and sellsoil to a reprocessor. Facility consists of about 15 tanksand a oil water separater.

J. HOW IDENTIFIED (i.e., citizen's complaints, OSHA citations, etc.): Eckhardt Report

K. DATE IDENTIFIED (mo., day, & yr.):

L. PRINCIPAL STATE CONTACT

1. NAME: Pat Haight

2. TELEPHONE NUMBER: (502)564-6716

II. PRELIMINARY ASSESSMENT (complete this section last)

A. APPARENT SERIOUSNESS OF PROBLEM

☐ 1. HIGH ☐ 2. MEDIUM ☒ 3. LOW ☐ 4. NONE ☐ 5. UNKNOWN

B. RECOMMENDATION

☒ 1. NO ACTION NEEDED (no hazard)

☐ 2. IMMEDIATE SITE INSPECTION NEEDED
a. TENTATIVELY SCHEDULED FOR:
b. WILL BE PERFORMED BY:

☐ 3. SITE INSPECTION NEEDED
a. TENTATIVELY SCHEDULED FOR:
b. WILL BE PERFORMED BY:

☐ 4. SITE INSPECTION NEEDED (low priority)

C. PREPARER INFORMATION

1. NAME: Carl Horneman

2. TELEPHONE NUMBER: (502)588-4254

3. DATE (mo., day, & yr.): 2-27-80

III. SITE INFORMATION

A. SITE STATUS

☒ 1. ACTIVE (Those industrial or municipal sites which are being used for waste treatment, storage, or disposal on a continuing basis, even if intermittently.)

☐ 2. INACTIVE (Those sites which no longer receive wastes.)

☐ 3. OTHER (specify): (Those sites that include such incidents like "midnight dumping" where no regular or continuing use of the site for waste disposal has occurred.)

B. IS GENERATOR ON SITE?

☐ 1. NO ☒ 2. YES (specify generator's four-digit SIC Code):

C. AREA OF SITE (in acres) (problem): 1 acre

D. IF APPARENT SERIOUSNESS OF SITE IS HIGH, SPECIFY COORDINATES

1. LATITUDE (deg.-min.-sec.):

2. LONGITUDE (deg.-min.-sec.):

E. ARE THERE BUILDINGS ON THE SITE? (if in problem area)

☐ 1. NO ☒ 2. YES (specify): Pump house

T2070-2 (10-79)

Continue On Reverse

IV. CHARACTERIZATION OF SITE ACTIVITY

Indicate the major site activity(ies) and details relating to each activity by marking 'X' in the appropriate boxes.

X	A. TRANSPORTER	X	B. STORER	X	C. TREATER	X	D. DISPOSER
	1. RAIL		1. PILE		1. FILTRATION		1. LANDFILL
	2. SHIP		2. SURFACE IMPOUNDMENT		2. INCINERATION		2. LANDFARM
	3. BARGE		3. DRUMS		3. VOLUME REDUCTION		3. OPEN DUMP
X	4. TRUCK		4. TANK, ABOVE GROUND	X	4. RECYCLING/RECOVERY		4. SURFACE IMPOUNDMENT
	5. PIPELINE		5. TANK, BELOW GROUND		5. CHEM./PHYS. TREATMENT		5. MIDNIGHT DUMPING
	6. OTHER (specify):		6. OTHER (specify):		6. BIOLOGICAL TREATMENT		6. INCINERATION
					7. WASTE OIL REPROCESSING		7. UNDERGROUND INJECTION
					8. SOLVENT RECOVERY		8. OTHER (specify):
					9. OTHER (specify):		

E. SPECIFY DETAILS OF SITE ACTIVITIES AS NEEDED

V. WASTE RELATED INFORMATION

A. WASTE TYPE

[ ] 1. UNKNOWN [XX] 2. LIQUID [ ] 3. SOLID [ ] 4. SLUDGE [ ] 5. GAS

B. WASTE CHARACTERISTICS

[ ] 1. UNKNOWN [ ] 2. CORROSIVE [ ] 3. IGNITABLE [ ] 4. RADIOACTIVE [ ] 5. HIGHLY VOLATILE
[ ] 6. TOXIC [ ] 7. REACTIVE [ ] 8. INERT [XX] 9. FLAMMABLE

[ ] 10. OTHER (specify):

C. WASTE CATEGORIES

1. Are records of wastes available? Specify items such as manifests, inventories, etc. below.

No

2. Estimate the amount (specify unit of measure) of waste by category; mark 'X' to indicate which wastes are present.

a. SLUDGE	b. OIL	c. SOLVENTS	d. CHEMICALS	e. SOLIDS	f. OTHER
AMOUNT	AMOUNT	AMOUNT	AMOUNT	AMOUNT	AMOUNT
UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE
X (1) PAINT, PIGMENTS	X (1) OILY WASTES	X (1) HALOGENATED SOLVENTS	X (1) ACIDS	X (1) FLYASH	X (1) LABORATORY PHARMACEUT.
(2) METALS SLUDGES	(2) OTHER (specify):	(2) NON-HALOGNTD. SOLVENTS	(2) PICKLING LIQUORS	(2) ASBESTOS	(2) HOSPITAL
(3) POTW		(3) OTHER (specify):	(3) CAUSTICS	(3) MILLING/ MINE TAILINGS	(3) RADIOACTIVE
(4) ALUMINUM SLUDGE			(4) PESTICIDES	(4) FERROUS SMLTG. WASTES	(4) MUNICIPAL
(5) OTHER (specify):			(5) DYES/INKS	(5) NON-FERROUS SMLTG. WASTES	(5) OTHER (specify):
			(6) CYANIDE	(6) OTHER (specify):	
			(7) PHENOLS		
			(8) HALOGENS		
			(9) PCB		
			(10) METALS		
			(11) OTHER (specify)		

No quantity figures were obtained.

Continue On Page 3

Continued From Page 2

V. WASTE RELATED INFORMATION (continued)

3. LIST SUBSTANCES OF GREATEST CONCERN WHICH MAY BE ON THE SITE (place in descending order of hazard)

None

4. ADDITIONAL COMMENTS OR NARRATIVE DESCRIPTION OF SITUATION KNOWN OR REPORTED TO EXIST AT THE SITE.

VI. HAZARD DESCRIPTION

A. TYPE OF HAZARD	B. POTENTIAL HAZARD (mark 'X')	C. ALLEGED INCIDENT (mark 'X')	D. DATE OF INCIDENT (mo., day, yr.)	E. REMARKS
1. NO HAZARD				
2. HUMAN HEALTH				
3. NON-WORKER INJURY/EXPOSURE				
4. WORKER INJURY				
5. CONTAMINATION OF WATER SUPPLY				
6. CONTAMINATION OF FOOD CHAIN				
7. CONTAMINATION OF GROUND WATER				
8. CONTAMINATION OF SURFACE WATER	X			Steps are being taken to prevent possibility of spills (dike).
9. DAMAGE TO FLORA/FAUNA				
10. FISH KILL				
11. CONTAMINATION OF AIR				
12. NOTICEABLE ODORS				
13. CONTAMINATION OF SOIL				
14. PROPERTY DAMAGE				
15. FIRE OR EXPLOSION				
16. SPILLS/LEAKING CONTAINERS/ RUNOFF/STANDING LIQUIDS				
17. SEWER, STORM DRAIN PROBLEMS				
18. EROSION PROBLEMS				
19. INADEQUATE SECURITY				
20. INCOMPATIBLE WASTES				
21. MIDNIGHT DUMPING				
22. OTHER (specify):				

Continue On Reverse

VII. PERMIT INFORMATION

A. INDICATE ALL APPLICABLE PERMITS HELD BY THE SITE.

☐ 1. NPDES PERMIT ☐ 2. SPCC PLAN ☐ 3. STATE PERMIT (specify) _____
☐ 4. AIR PERMITS ☐ 5. LOCAL PERMIT ☐ 6. RCRA TRANSPORTER
☐ 7. RCRA STORER ☐ 8. RCRA TREATER ☐ 9. RCRA DISPOSER

☐ 10. OTHER (specify): _____

B. IN COMPLIANCE?

☒ 1. YES ☐ 2. NO ☐ 3. UNKNOWN

4. WITH RESPECT TO (list regulation name & number): _____

VIII. PAST REGULATORY ACTIONS

☒ A. NONE ☐ B. YES (summarize below)

IX. INSPECTION ACTIVITY (past or on-going)

☐ A. NONE ☒ B. YES (complete items 1,2,3, & 4 below)

1. TYPE OF ACTIVITY	2. DATE OF PAST ACTION (mo., day, & yr.)	3. PERFORMED BY: (EPA/State)	4. DESCRIPTION
Inspection	2-27-80	State	Permit application for storage facility and CWA spec plan being prepared.

X. REMEDIAL ACTIVITY (past or on-going)

☒ A. NONE ☐ B. YES (complete items 1, 2, 3, & 4 below)

1. TYPE OF ACTIVITY	2. DATE OF PAST ACTION (mo., day, & yr.)	3. PERFORMED BY: (EPA/State)	4. DESCRIPTION

NOTE: Based on the information in Sections III through X, fill out the Preliminary Assessment (Section II) information on the first page of this form.

EPA

POTENTIAL HAZARDOUS WASTE SITE
SITE INSPECTION REPORT

REGION	SITE NUMBER (to be assigned by Hq)
IV	KY000000220

GENERAL INSTRUCTIONS: Complete Sections I and III through XV of this form as completely as possible. Then use the information on this form to develop a Tentative Disposition *(Section II)*. File this form in its entirety in the regional Hazardous Waste Log File. Be sure to include all appropriate Supplemental Reports in the file. Submit a copy of the forms to: U.S. Environmental Protection Agency; Site Tracking System; Hazardous Waste Enforcement Tack Force *(EN-335)*; 401 M St., SW; Washington, DC 20460.

I. SITE IDENTIFICATION

A. SITE NAME: KY Petroleum Prod.
B. STREET (or other identifier): 4019 Blanton Lane
C. CITY: Louisville
D. STATE: KY
E. ZIP CODE: 40216
F. COUNTY NAME: Jefferson

G. SITE OPERATOR INFORMATION
1. NAME: Leo Shircliff - Operator
2. TELEPHONE NUMBER:
3. STREET:
4. CITY:
5. STATE:
6. ZIP CODE:

H. REALTY OWNER INFORMATION *(if different from operator of site)*
1. NAME:
2. TELEPHONE NUMBER:
3. CITY:
4. STATE:
5. ZIP CODE:

I. SITE DESCRIPTION: Waste oil recycler - Above ground storage w/ containment

J. TYPE OF OWNERSHIP
☐ 1. FEDERAL ☐ 2. STATE ☐ 3. COUNTY ☐ 4. MUNICIPAL ☒ 5. PRIVATE

II. TENTATIVE DISPOSITION *(complete this section last)*

A. ESTIMATE DATE OF TENTATIVE DISPOSITION *(mo., day, & yr.)*: 11/17/80
B. APPARENT SERIOUSNESS OF PROBLEM
☐ 1. HIGH ☐ 2. MEDIUM ☐ 3. LOW ☒ 4. NONE

C. PREPARER INFORMATION
1. NAME: A. Shane Hitchcock
2. TELEPHONE NUMBER: 404/881-2234
3. DATE *(mo., day, & yr.)*: 11/18/80

III. INSPECTION INFORMATION

A. PRINCIPAL INSPECTOR INFORMATION
1. NAME: A. Shane Hitchcock
2. TITLE: Env. Scientist
3. ORGANIZATION: US- EPA
4. TELEPHONE NO. *(area code & no.)*: 404/881-2234

B. INSPECTION PARTICIPANTS

1. NAME	2. ORGANIZATION	3. TELEPHONE NO.
Bob Koentop	KY- DNREP - D. of HMWM	502/588-4254

C. SITE REPRESENTATIVES INTERVIEWED *(corporate officials, workers, residents)*

1. NAME	2. TITLE & TELEPHONE NO.	3. ADDRESS

Continued From Front

II. INSPECTION INFORMATION *(continued)*

D. GENERATOR INFORMATION *(sources of waste)*

1. NAME	2. TELEPHONE NO.	3. ADDRESS	4. WASTE TYPE GENERATED

E. TRANSPORTER/HAULER INFORMATION

1. NAME	2. TELEPHONE NO.	3. ADDRESS	4. WASTE TYPE TRANSPORTED

F. IF WASTE IS PROCESSED ON SITE AND ALSO SHIPPED TO OTHER SITES, IDENTIFY OFF-SITE FACILITIES USED FOR DISPOSAL.

1. NAME	2. TELEPHONE NO.	3. ADDRESS

G. DATE OF INSPECTION *(mo., day, & yr.)*	H. TIME OF INSPECTION	I. ACCESS GAINED BY: *(credentials must be shown in all cases)*
11/17/80		☐ 1. PERMISSION ☐ 2. WARRANT

J. WEATHER *(describe)*

IV. SAMPLING INFORMATION

A. Mark 'X' for the types of samples taken and indicate where they have been sent e.g., regional lab, other EPA lab, contractor, etc. and estimate when the results will be available.

1. SAMPLE TYPE	2. SAMPLE TAKEN *(mark 'X')*	3. SAMPLE SENT TO:	4. DATE RESULTS AVAILABLE
a. GROUNDWATER			
b. SURFACE WATER			
c. WASTE			
d. AIR			
e. RUNOFF			
f. SPILL			
g. SOIL			
h. VEGETATION			
i. OTHER *(specify)*			

B. FIELD MEASUREMENTS TAKEN *(e.g., radioactivity, explosivity, PH, etc.)*

1. TYPE	2. LOCATION OF MEASUREMENTS	3. RESULTS

Continued From Page 2

IV. SAMPLING INFORMATION *(continued)*

C. PHOTOS

1. TYPE OF PHOTOS
☐ a. GROUND ☐ b. AERIAL

2. PHOTOS IN CUSTODY OF:

D. SITE MAPPED?

☐ YES. SPECIFY LOCATION OF MAPS:

E. COORDINATES

1. LATITUDE *(deg.-min.-sec.)*

2. LONGITUDE *(deg.-min.-sec.)*

V. SITE INFORMATION

A. SITE STATUS

☒ 1. ACTIVE *(Those inductrial or municipal sites which are being used for waste treatment, storage, or disposal on a continuing basis, even if infrequently.)*

☐ 2. INACTIVE *(Those sites which no longer receive wastes.)*

☐ 3. OTHER *(specify):* _____
(Those sites that include such incidents like "midnight dumping" where no regular or continuing use of the site for waste disposal has occurred.)

B. IS GENERATOR ON SITE?

☒ 1. NO ☐ 2. YES *(specify generator's four-digit SIC Code):* _____

C. AREA OF SITE *(in acres)*

~ 5 acres

D. ARE THERE BUILDINGS ON THE SITE?

☒ 1. NO ☐ 2. YES *(specify):*

VI. CHARACTERIZATION OF SITE ACTIVITY

Indicate the major site activity*(ies)* and details relating to each activity by marking 'X' in the appropriate boxes.

'X'	A. TRANSPORTER	'X'	B. STORER	'X'	C. TREATER	'X'	D. DISPOSER
	1. RAIL		1. PILE		1. FILTRATION		1. LANDFILL
	2. SHIP		2. SURFACE IMPOUNDMENT		2. INCINERATION		2. LANDFARM
	3. BARGE		3. DRUMS		3. VOLUME REDUCTION		3. OPEN DUMP
	4. TRUCK		4. TANK, ABOVE GROUND	X	4. RECYCLING/RECOVERY		4. SURFACE IMPOUNDMENT
	5. PIPELINE		5. TANK, BELOW GROUND		5. CHEM./PHYS./TREATMENT		5. MIDNIGHT DUMPING
	6. OTHER *(specify):*		6. OTHER *(specify):*		6. BIOLOGICAL TREATMENT		6. INCINERATION
					7. WASTE OIL REPROCESSING		7. UNDERGROUND INJECTION
					8. SOLVENT RECOVERY		8. OTHER *(specify):*
					9. OTHER *(specify):*		

E. SUPPLEMENTAL REPORTS: If the site falls within any of the categories listed below, Supplemental Reports must be completed. Indicate which Supplemental Reports you have filled out and attached to this for..

☐ 1. STORAGE ☐ 2. INCINERATION ☐ 3. LANDFILL ☐ 4. SURFACE IMPOUNDMENT ☐ 5. DEEP WELL

☐ 6. CHEM/BIO/PHYS TREATMENT ☐ 7. LANDFARM ☐ 8. OPEN DUMP ☐ 9. TRANSPORTER ☐ 10. RECYCLOR/RECLAIMER

VII. WASTE RELATED INFORMATION

A. WASTE TYPE

☒ 1. LIQUID ☐ 2. SOLID ☐ 3. SLUDGE ☐ 4. GAS

B. WASTE CHARACTERISTICS

☐ 1. CORROSIVE ☐ 2. IGNITABLE ☐ 3. RADIOACTIVE ☐ 4. HIGHLY VOLATILE

☐ 5. TOXIC ☐ 6. REACTIVE ☐ 7. INERT ☐ 8. FLAMMABLE

☐ 9. OTHER *(specify):*

C. WASTE CATEGORIES

1. Are records of wastes available? Specify items such as manifests, inventories, etc. below.

Waste Oil

Continued From Front

VII. WASTE RELATED INFORMATION *(continued)*

2. Estimate the amount *(specify unit of measure)* of waste by category; mark 'X' to indicate which wastes are present.

a. SLUDGE	b. OIL	c. SOLVENTS	d. CHEMICALS	e. SOLIDS	f. OTHER
AMOUNT	AMOUNT	AMOUNT	AMOUNT	AMOUNT	AMOUNT
UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE
X (1) PAINT, PIGMENTS	X (1) OILY WASTES	X (1) HALOGENATED SOLVENTS	X (1) ACIDS	X (1) FLYASH	X (1) LABORATORY, PHARMACEUT.
(2) METALS SLUDGES	(2) OTHER *(specify)*:	(2) NON-HALOGNTD. SOLVENTS	(2) PICKLING LIQUORS	(2) ASBESTOS	(2) HOSPITAL
(3) POTW		(3) OTHER *(specify)*:	(3) CAUSTICS	(3) MILLING/MINE TAILINGS	(3) RADIOACTIVE
(4) ALUMINUM SLUDGE			(4) PESTICIDES	(4) FERROUS SMELTING WASTES	(4) MUNICIPAL
(5) OTHER *(specify)*:			(5) DYES/INKS	(5) NON-FERROUS SMLTG. WASTES	(5) OTHER *(specify)*:
			(6) CYANIDE	(6) OTHER *(specify)*:	
			(7) PHENOLS		
			(8) HALOGENS		
			(9) PCB		
			(10) METALS		
			(11) OTHER *(specify)*:		

D. LIST SUBSTANCES OF GREATEST CONCERN WHICH ARE ON THE SITE *(place in descending order of hazard)*

1. SUBSTANCE	2. FORM *(mark 'X')*			3. TOXICITY *(mark 'X')*				4. CAS NUMBER	5. AMOUNT	6. UNIT
	a. SOLID	b. LIQ.	c. VAPOR	a. HIGH	b. MED.	c. LOW	d. NONE			

VIII. HAZARD DESCRIPTION

FIELD EVALUATION HAZARD DESCRIPTION: Place an 'X' in the box to indicate that the listed hazard exists. Describe the hazard in the space provided.

☐ A. HUMAN HEALTH HAZARDS

Continue On Page 5

Continued From Page 4

VIII. HAZARD DESCRIPTION *(continued)*

☐ B. NON-WORKER INJURY/EXPOSURE

☐ C. WORKER INJURY/EXPOSURE

☐ D. CONTAMINATION OF WATER SUPPLY

☐ E. CONTAMINATION OF FOOD CHAIN

☐ F. CONTAMINATION OF GROUND WATER

☐ G. CONTAMINATION OF SURFACE WATER

Continued From Front

VIII. HAZARD DESCRIPTION *(continued)*

☐ H. DAMAGE TO FLORA/FAUNA

☐ I. FISH KILL

☐ J. CONTAMINATION OF AIR

☐ K. NOTICEABLE ODORS

☒ L. CONTAMINATION OF SOIL

This is a waste oil recycler that buys and sells waste oil. this facility is used as a transfer station. Soil is contaminated w/ oil in the immediate vicinity of the tanks but the ~~contam~~ contamination is confined to the area with the containment structures.

☐ M. PROPERTY DAMAGE

Continued From Page 6

VIII. HAZARD DESCRIPTION *(continued)*

☐ N. FIRE OR EXPLOSION

☐ O. SPILLS/LEAKING CONTAINERS/RUNOFF/STANDING LIQUID

☐ P. SEWER, STORM DRAIN PROBLEMS

☐ Q. EROSION PROBLEMS

☐ R. INADEQUATE SECURITY

☐ S. INCOMPATIBLE WASTES

VIII. HAZARD DESCRIPTION *(continued)*

☐ T. MIDNIGHT DUMPING

☐ U. OTHER *(specify)*:

IX. POPULATION DIRECTLY AFFECTED BY SITE

A. LOCATION OF POPULATION	B. APPROX. NO. OF PEOPLE AFFECTED	C. APPROX. NO. OF PEOPLE AFFECTED WITHIN UNIT AREA	D. APPROX. NO. OF BUILDINGS AFFECTED	E. DISTANCE TO SITE *(specify units)*
1. IN RESIDENTIAL AREAS				
2. IN COMMERCIAL OR INDUSTRIAL AREAS				
3. IN PUBLICLY TRAVELLED AREAS				
4. PUBLIC USE AREAS *(parks, schools, etc.)*				

X. WATER AND HYDROLOGICAL DATA

A. DEPTH TO GROUNDWATER *(specify unit)*	B. DIRECTION OF FLOW	C. GROUNDWATER USE IN VICINITY
D. POTENTIAL YIELD OF AQUIFER	E. DISTANCE TO DRINKING WATER SUPPLY *(specify unit of measure)*	F. DIRECTION TO DRINKING WATER SUPPLY

G. TYPE OF DRINKING WATER SUPPLY

☐ 1. NON-COMMUNITY < 15 CONNECTIONS* ☐ 2. COMMUNITY *(specify town)*: > 15 CONNECTIONS _____

☐ 3. SURFACE WATER ☐ 4. WELL

Continue On Page 9

Continued From Page 8

X. WATER AND HYDROLOGICAL DATA *(continued)*

H. LIST ALL DRINKING WATER WELLS WITHIN A 1/4 MILE RADIUS OF SITE

1. WELL	2. DEPTH *(specify unit)*	3. LOCATION *(proximity to population/buildings)*	4. NON-COMMUNITY *(mark 'X')*	5. COMMUNITY *(mark 'X')*

I. RECEIVING WATER

1. NAME

☐ 2. SEWERS ☐ 3. STREAMS/RIVERS

☐ 4. LAKES/RESERVOIRS ☐ 5. OTHER *(specify)*:

6. SPECIFY USE AND CLASSIFICATION OF RECEIVING WATERS

XI. SOIL AND VEGITATION DATA

LOCATION OF SITE IS IN:

☐ A. KNOWN FAULT ZONE ☐ B. KARST ZONE ☐ C. 100 YEAR FLOOD PLAIN ☐ D. WETLAND

☐ E. A REGULATED FLOODWAY ☐ F. CRITICAL HABITAT ☐ G. RECHARGE ZONE OR SOLE SOURCE AQUIFER

XII. TYPE OF GEOLOGICAL MATERIAL OBSERVED

Mark 'X' to indicate the type(s) of geological material observed and specify where necessary, the component parts.

'X'	A. OVERBURDEN	'X'	B. BEDROCK *(specify below)*	'X'	C. OTHER *(specify below)*
	1. SAND				
	2. CLAY				
	3. GRAVEL				

XIII. SOIL PERMEABILITY

☐ A. UNKNOWN ☐ B. VERY HIGH *(100,000 to 1000 cm/sec.)* ☐ C. HIGH *(1000 to 10 cm/sec.)*

☐ D. MODERATE *(10 to .1 cm/sec.)* ☐ E. LOW *(.1 to .001 cm/sec.)* ☐ F. VERY LOW *(.001 to .00001 cm/sec.)*

G. RECHARGE AREA

☐ 1. YES ☐ 2. NO 3. COMMENTS:

H. DISCHARGE AREA

☐ 1. YES ☐ 2. NO 3. COMMENTS:

I. SLOPE

1. ESTIMATE % OF SLOPE

2. SPECIFY DIRECTION OF SLOPE, CONDITION OF SLOPE, ETC.

J. OTHER GEOLOGICAL DATA

Continue On Reverse

Continued From Front

XIV. PERMIT INFORMATION

List all applicable permits held by the site and provide the related information.

A. PERMIT TYPE *(e.g., RCRA, State, NPDES, etc.)*	B. ISSUING AGENCY	C. PERMIT NUMBER	D. DATE ISSUED *(mo., day, & yr.)*	E. EXPIRATION DATE *(mo., day, & yr.)*	F. IN COMPLIANCE *(mark 'X')*		
					1. YES	2. NO	3. UNKNOWN

XV. PAST REGULATORY OR ENFORCEMENT ACTIONS

☐ NONE ☐ YES *(summarize in this space)*

NOTE: Based on the information in Sections III through XV, fill out the Tentative Disposition *(Section II)* information on the first page of this form.

M.2 - SITE MAINTENANCE FORM

EPA ID : KYD061564001

SITE NAME: KENTUCKY PETROLEUM PRODUCTS SOURCE: S

STREET : 4019 BLANTON LN CONG DIST: 03

CITY : LOUISVILLE ZIP: 40216

CNTY NAME: JEFFERSON CNTY CODE : 111

LATITUDE : 38/11/36.0 LONGITUDE : 085/48/30.0

LL-SOURCE: R LL-ACCURACY:

SMSA : 4520 HYDRO UNIT: 05140101

INVENTORY IND: Y REMEDIAL IND: Y REMOVAL IND: N FED FAC IND: N

NPL IND: N NPL LISTING DATE: NPL DELISTING DATE:

SITE/SPILL IDS:

RPM NAME: RPM PHONE: - -

SITE CLASSIFICATION: SITE APPROACH:

DIOXIN TIER: REG FLD1: REG FLD2:

RESP TERM: PENDING ( ) NO FURTHER ACTION ( )

ENF DISP: NO VIABLE RESP PARTY ( ) VOLUNTARY RESPONSE ( )
ENFORCED RESPONSE ( ) COST RECOVERY ( )

SITE DESCRIPTION:

* ACTION: _

* _____ _

* _____ __

* _____ _____-____

* _____ ___

* __/__/__._ ___/__/__._

* _ _

* ____ _____

* _ _ _ _

* _ __/__ __/__

* __ __ __ __ __

* - -

* __ ___

* ____ _____ _

* PENDING (_) NO FURTHER ACTION (_)

* _ _
* _ _

* _____

* _____

* _____

* _____

M.2 - PROGRAM MAINTENANCE FORM

* ACTION: _ *

SITE: KENTUCKY PETROLEUM PRODUCTS

EPA ID: KYD061564001 PROGRAM CODE: H01 PROGRAM TYPE: * _ *

PROGRAM QUALIFIER: ALIAS LINK : * ___ __ *

PROGRAM NAME: SITE EVALUATION * _____ *

DESCRIPTION:

* _____ *

* _____ *

* _____ *

* _____ *

M.2 - EVENT MAINTENANCE FORM

* ACTION: _ *

SITE: KENTUCKY PETROLEUM PRODUCTS
PROGRAM: SITE EVALUATION

EPA ID: KYD061564001 PROGRAM CODE: H01 EVENT TYPE: DS1

FMS CODE: EVENT QUALIFIER : EVENT LEAD: E * _ ___ _ *

EVENT NAME: DISCOVERY STATUS: * _____ _ *

DESCRIPTION:

* _____ *
* _____ *
* _____ *
* _____ *

ORIGINAL	CURRENT	ACTUAL			
START:	START:	START:	* / /	/ /	/ / *
COMP :	COMP :	COMP : 11/01/79	* __/__/__	__/__/__	__/__/__ *

HQ COMMENT:

* _____ *

RG COMMENT:

* _____ *

COOP AGR #	AMENDMENT #	STATUS	STATE %				
			0	* _____	_____	__	___ *

M.2 - EVENT MAINTENANCE FORM

* ACTION: _ *

SITE: KENTUCKY PETROLEUM PRODUCTS
PROGRAM: SITE EVALUATION

EPA ID: KYD061564001 PROGRAM CODE: H01 EVENT TYPE: PA1

FMS CODE: EVENT QUALIFIER : EVENT LEAD: S * _ ___ _ *

EVENT NAME: PRELIMINARY ASSESSMENT STATUS: * _____ _ *

DESCRIPTION:

* _____ *
* _____ *
* _____ *
* _____ *

ORIGINAL	CURRENT	ACTUAL			
START:	START:	START: 04/01/84	* / /	/ /	/ / *
COMP :	COMP :	COMP : 08/01/84	*__/__/__	__/__/__	__/__/__ *

HQ COMMENT:

* _____ *

RG COMMENT:

* _____ *

COOP AGR #	AMENDMENT #	STATUS	STATE %				
			0	* _____	_____	__	___ *

M.2 - EVENT MAINTENANCE FORM

* ACTION: _ *

SITE: KENTUCKY PETROLEUM PRODUCTS
PROGRAM: SITE EVALUATION

EPA ID: KYD061564001 PROGRAM CODE: H01 EVENT TYPE: SI1

FMS CODE: EVENT QUALIFIER : EVENT LEAD: E * _ ___ _ *

EVENT NAME: SITE INSPECTION STATUS: * _____ _ *

DESCRIPTION:

* _____ *
* _____ *
* _____ *
* _____ *

ORIGINAL	CURRENT	ACTUAL			
START:	START:	START: 11/01/80	* / /	/ /	/ / *
COMP :	COMP :	COMP : 11/01/80	* __/__/__	__/__/__	__/__/__ *

HQ COMMENT:

* _____ *

RG COMMENT:

* _____ *

COOP AGR #	AMENDMENT #	STATUS	STATE %				
			0	* _____	_____	_	___ *

M.2 - COMMENT MAINTENANCE FORM

SITE: KENTUCKY PETROLEUM PRODUCTS

EPA ID: KYD061564001

COM NO	COMMENT	ACTION	
001	LOW PRIORITY.	_	

EPA

POTENTIAL HAZARDOUS WASTE SITE
TENTATIVE DISPOSITION

REGION	SITE NUMBER
IV	KYD 061 569 001

File this form in the regional Hazardous Waste Log File and submit a copy to: U.S. Environmental Protection Agency; Site Tracking System, Hazardous Waste Enforcement Task Force (EN-335), 401 M St., SW, Washington, DC 20460.

I. SITE IDENTIFICATION

A. SITE NAME	B. STREET		
Kentucky Petroleum Products	4019 Blanton Lane		
C. CITY	**D. STATE**	**E. ZIP CODE**	
Louisville (Jefferson Co.)	KY	40216	

II. TENTATIVE DISPOSITION

Indicate the recommended action(s) and agency(ies) that should be involved by marking 'X' in the appropriate boxes.

RECOMMENDATION	MARK 'X'	ACTION AGENCY: EPA	STATE	LOCAL	PRIVATE
A. NO ACTION NEEDED -- NO HAZARD					
B. INVESTIGATIVE ACTION(S) NEEDED (If yes, complete Section III.)	X	X			
C. REMEDIAL ACTION NEEDED (If yes, complete Section IV.)					
D. ENFORCEMENT ACTION NEEDED (If yes, specify in Part E whether the case will be primarily managed by the EPA or the State and what type of enforcement action is anticipated.)					

E. RATIONALE FOR DISPOSITION

Some waste oil has spilled around some storage tanks

F. INDICATE THE ESTIMATED DATE OF FINAL DISPOSITION (mo., day, & yr.)	G. IF A CASE DEVELOPMENT PLAN IS NECESSARY, INDICATE THE ESTIMATED DATE ON WHICH THE PLAN WILL BE DEVELOPED (mo., day, & yr.)

H. PREPARER INFORMATION

1. NAME	2. TELEPHONE NUMBER	3. DATE (mo., day, & yr.)
Elizabeth Seely	(404) 881-2234	12-7-84

III. INVESTIGATIVE ACTIVITY NEEDED

A. IDENTIFY ADDITIONAL INFORMATION NEEDED TO ACHIEVE A FINAL DISPOSITION.

Low priority for SI.

~Non State

B. PROPOSED INVESTIGATIVE ACTIVITY (Detailed Information)

1. METHOD FOR OBTAINING NEEDED ADDITIONAL INFO.	2. SCHEDULED DATE OF ACTION (mo, day, & yr)	3. TO BE PERFORMED BY (EPA, Contractor, State, etc.)	4. ESTIMATED MANHOURS	5. REMARKS
a. TYPE OF SITE INSPECTION (1)				
(2)				
(3)				
b. TYPE OF MONITORING (1)				
(2)				
c. TYPE OF SAMPLING (1)				
(2)				

Continue On Reverse

EPA

POTENTIAL HAZARDOUS WASTE SITE
TENTATIVE DISPOSITION

REGION: IV | SITE NUMBER: KYD 061 364 001

File this form in the regional Hazardous Waste Log File and submit a copy to: U.S. Environmental Protection Agency; Site Tracking System, Hazardous Waste Enforcement Task Force (EN-335), 401 M St., SW, Washington, DC 20460.

I. SITE IDENTIFICATION

A. SITE NAME	B. STREET	
Kentucky Petroleum Products	4019 Blanton Lane	
C. CITY	D. STATE	E. ZIP CODE
Louisville (Jefferson Co.)	KY	40216

II. TENTATIVE DISPOSITION

Indicate the recommended action(s) and agency(ies) that should be involved by marking 'X' in the appropriate boxes.

RECOMMENDATION	MARK 'X'	ACTION AGENCY: EPA	STATE	LOCAL	PRIVATE
A. NO ACTION NEEDED -- NO HAZARD					
B. INVESTIGATIVE ACTION(S) NEEDED (If yes, complete Section III.)	X	X			
C. REMEDIAL ACTION NEEDED (If yes, complete Section IV.)					
D. ENFORCEMENT ACTION NEEDED (If yes, specify in Part E whether the case will be primarily managed by the EPA or the State and what type of enforcement action is anticipated.)					

E. RATIONALE FOR DISPOSITION

Some waste oil has spilled around some storage tanks

F. INDICATE THE ESTIMATED DATE OF FINAL DISPOSITION (mo., day, & yr.)	G. IF A CASE DEVELOPMENT PLAN IS NECESSARY, INDICATE THE ESTIMATED DATE ON WHICH THE PLAN WILL BE DEVELOPED (mo., day, & yr.)

H. PREPARER INFORMATION

1. NAME	2. TELEPHONE NUMBER	3. DATE (mo., day, & yr.)
Elizabeth Seely	(404) 881-2234	12-7-84

III. INVESTIGATIVE ACTIVITY NEEDED

A. IDENTIFY ADDITIONAL INFORMATION NEEDED TO ACHIEVE A FINAL DISPOSITION.

Low priority for SI.

B. PROPOSED INVESTIGATIVE ACTIVITY (Detailed Information)

1. METHOD FOR OBTAINING NEEDED ADDITIONAL INFO.	2. SCHEDULED DATE OF ACTION (mo, day, & yr)	3. TO BE PERFORMED BY (EPA, Contractor, State, etc.)	4. ESTIMATED MANHOURS	5. REMARKS
a. TYPE OF SITE INSPECTION				
(1)				
(2)				
(3)				
b. TYPE OF MONITORING				
(1)				
(2)				
c. TYPE OF SAMPLING				
(1)				
(2)				

Continue On Reverse

Continued From Front

III. INVESTIGATIVE ACTIVITY NEEDED and PART B - PROPOSED INVESTIGATIVE ACTIVITY *(Continued)*

d. TYPE OF LAB ANALYSIS (1)				
(2)				
e. OTHER *(specify)* (1)				
(2)				

C. ELABORATE ON ANY OF THE INFORMATION PROVIDED IN PART B *(on front & above)*, AS NEEDED TO IDENTIFY ADDITIONAL INVESTIGATIVE WORK.

D. ESTIMATED MANHOURS BY ACTION AGENCY

1. ACTION AGENCY	2. TOTAL ESTIMATED MANHOURS FOR INVESTIGATIVE ACTIVITIES	1. ACTION AGENCY	2. TOTAL ESTIMATED MANHOURS FOR INVESTIGATIVE ACTIVITIES
a. EPA		b. STATE	
c. EPA CONTRACTOR		d. OTHER *(specify)*	

IV. REMEDIAL ACTIONS

A. SHORT TERM EMERGENCY STRATEGY *(On Site & Off-Site)* List all emergency actions needed to bring site under immediate control, e.g., restrict access, provide alternate water supply, etc. See instructions for a list of Key Words for each of the actions to be used in the space below.

1. ACTION	2. EST. START DATE *(mo, day, & yr)*	3. EST. END DATE *(mo, day, & yr)*	4. ACTION AGENCY *(EPA, State, Private Party)*	5. ESTIMATED COST	6. SPECIFY 311 OR OTHER ACTION; INDICATE THE MAGNITUDE OF THE WORK REQUIRED
				$	
				$	
				$	
				$	
				$	
				$	

B. LONG TERM STRATEGY *(On Site & Off-Site)* List all long term solutions, e.g., excavation, removal, ground water monitoring wells, etc. See instructions for a list of Key Words for each of the actions to be used in the spaces below.

1. ACTION	2. EST. START DATE *(mo, day, & yr)*	3. EST. END DATE *(mo, day, & yr)*	4. ACTION AGENCY *(EPA, State Private Party)*	5. ESTIMATED COST	6. SPECIFY 311 OR OTHER ACTION; INDICATE THE MAGNITUDE OF THE WORK REQUIRED
				$	
				$	
				$	
				$	
				$	
				$	

C. ESTIMATED MANHOURS AND COST BY ACTION AGENCY

1. ACTION AGENCY	2. TOTAL EST. MANHOURS FOR REMEDIAL ACTIVITIES	3. TOTAL EST. COST FOR REMEDIAL ACTIVITIES	1. ACTION AGENCY	2. TOTAL EST. MANHOURS FOR REMEDIAL ACTIVITIES	3. TOTAL EST. COST FOR REMEDIAL ACTIVITIES
a. EPA			b. STATE		
c. PRIVATE PARTIES			d. OTHER *(specify)*		

MEMORANDUM

TO: Barry Burrus, Chief
Uncontrolled Sites Section

FROM: Jim Jarman, Geologist
Uncontrolled Sites Section

DATE: March 27, 1984

SUBJECT: Preliminary Assessment Report for Kentucky Petroleum Products - Jefferson County

Kentucky Petroleum Products is a waste oil recycler that operates several tank trucks which collect waste oil and delivers it to a small storage facility (about 15 tanks). The waste oil is stored and later sold to various companies that either refine it into petroleum products, place it in a waste oil fuel program, or burn it as a waste oil fuel. The firm is now known as Kentucky Petroleum Wastes, Inc.

Presently, the site is being handled by the Enforcement Branch of the Kentucky Division of Waste Management. Numerous violations have been documented by field personnel. A preliminary assessment and site inspection completed in 1980 did not designate any action to be taken. Tank waste oil samples taken in February 1984 indicate high levels of trichloroethylene to be present.

After reviewing the information within the division and talking with enforcement personnel, I am recommending this site be given a low priority ranking for a site inspection. The presence of trichloroethylene in these storage tanks could present an environmental problem if the contents are released.

JJ:da

cc: John Brooks
Millie Archer
EPA-Atlanta
File

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 1 - SITE INFORMATION AND ASSESSMENT

EPA

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D061564001

II. SITE NAME AND LOCATION

01 SITE NAME (Legal, common, or descriptive name of site)	02 STREET, ROUTE NO., OR SPECIFIC LOCATION IDENTIFIER
Kentucky Petroleum Products	4019 Blanton Lane

03 CITY	04 STATE	05 ZIP CODE	06 COUNTY	07 COUNTY CODE	08 CONG DIST
Louisville	KY	40216	Jefferson	056	

09 COORDINATES LATITUDE	LONGITUDE
38°08'50".0	085°44'15".0

10 DIRECTIONS TO SITE (Starting from nearest public road)
Facility Location is intersection Knopp avenue & Grade Lane - storage tanks

III. RESPONSIBLE PARTIES

01 OWNER (If known)	02 STREET (Business, mailing, residential)
Kentucky Petroleum Products	4019 Blanton Lane

03 CITY	04 STATE	05 ZIP CODE	06 TELEPHONE NUMBER
Louisville	KY	40216	(502) 447-1802

07 OPERATOR (If known and different from owner)	08 STREET (Business, mailing, residential)
SAME	

09 CITY	10 STATE	11 ZIP CODE	12 TELEPHONE NUMBER
			( )

13 TYPE OF OWNERSHIP (Check one)
X A. PRIVATE ☐ B. FEDERAL: _____ (Agency name) ☐ C. STATE ☐ D. COUNTY ☐ E. MUNICIPAL
☐ F. OTHER: _____ (Specify) ☐ G. UNKNOWN

14 OWNER/OPERATOR NOTIFICATION ON FILE (Check all that apply)
☐ A. RCRA 3001 DATE RECEIVED: ___/___/___ (MONTH DAY YEAR) ☐ B. UNCONTROLLED WASTE SITE (CERCLA 103 c) DATE RECEIVED: ___/___/___ (MONTH DAY YEAR) X C. NONE

IV. CHARACTERIZATION OF POTENTIAL HAZARD

01 ON SITE INSPECTION
X YES DATE 02 / 29 / 84 (MONTH DAY YEAR)
☐ NO

BY (Check all that apply)
☐ A. EPA ☐ B. EPA CONTRACTOR ☐ C. STATE ☐ D. OTHER CONTRACTOR
☐ E. LOCAL HEALTH OFFICIAL ☐ F. OTHER: _____ (Specify)
CONTRACTOR NAME(S): _____

02 SITE STATUS (Check one)	03 YEARS OF OPERATION
X A. ACTIVE ☐ B. INACTIVE ☐ C. UNKNOWN	BEGINNING YEAR ____ ENDING YEAR ____ X UNKNOWN

04 DESCRIPTION OF SUBSTANCES POSSIBLY PRESENT, KNOWN, OR ALLEGED
Waste oil & Trichloroethylene mixed with water.

05 DESCRIPTION OF POTENTIAL HAZARD TO ENVIRONMENT AND/OR POPULATION
- Spills - Floral & faunal destruction; Groundwater contamination

V. PRIORITY ASSESSMENT

01 PRIORITY FOR INSPECTION (Check one. If high or medium is checked, complete Part 2 - Waste Information and Part 3 - Description of Hazardous Conditions and Incidents)
☐ A. HIGH (Inspection required promptly) ☐ B. MEDIUM (Inspection required) X C. LOW (Inspect on time available basis) ☐ D. NONE (No further action needed, complete current disposition form)

VI. INFORMATION AVAILABLE FROM

01 CONTACT	02 OF (Agency/Organization)	03 TELEPHONE NUMBER
Millie ARCHER	KYNREPC - Louisville Field Office	(502) 588 4254

04 PERSON RESPONSIBLE FOR ASSESSMENT	05 AGENCY	06 ORGANIZATION	07 TELEPHONE NUMBER	08 DATE
Jim Jarman	KYNREPC	Div. Waste Mgt.	(502) 564-6716	03 / 27 / 84 (MONTH DAY YEAR)

EPA FORM 2070-12 (7-81)

EPA

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 2 - WASTE INFORMATION

I. IDENTIFICATION

01 STATE	02 SITE NUMBER
KY	D006156400 1

II. WASTE STATES, QUANTITIES, AND CHARACTERISTICS

01 PHYSICAL STATES (Check all that apply)

- ☐ A. SOLID
- ☐ B. POWDER, FINES
- ☐ C. SLUDGE
- ☐ D. OTHER N/A (Specify)
- ☐ E. SLURRY
- ☐ F. LIQUID
- ☐ G. GAS

02 WASTE QUANTITY AT SITE

(Measures of waste quantities must be independent)

- TONS
- CUBIC YARDS N/A
- NO. OF DRUMS

03 WASTE CHARACTERISTICS (Check all that apply)

- ☐ A. TOXIC
- ☐ B. CORROSIVE
- ☐ C. RADIOACTIVE
- ☐ D. PERSISTENT
- ☐ E. SOLUBLE
- ☐ F. INFECTIOUS
- ☐ G. FLAMMABLE
- ☐ H. IGNITABLE
- ☐ I. HIGHLY VOLATILE
- ☐ J. EXPLOSIVE
- ☐ K. REACTIVE
- ☐ L. INCOMPATIBLE
- ☒ M. NOT APPLICABLE

III. WASTE TYPE

CATEGORY	SUBSTANCE NAME	01 GROSS AMOUNT	02 UNIT OF MEASURE	03 COMMENTS
SLU	SLUDGE			
OLW	OILY WASTE			
SOL	SOLVENTS			
PSD	PESTICIDES			
OCC	OTHER ORGANIC CHEMICALS			
IOC	INORGANIC CHEMICALS			
ACD	ACIDS			
BAS	BASES			
MES	HEAVY METALS			

IV. HAZARDOUS SUBSTANCES (See Appendix for most frequently cited CAS Numbers)

01 CATEGORY	02 SUBSTANCE NAME	03 CAS NUMBER	04 STORAGE/DISPOSAL METHOD	05 CONCENTRATION	06 MEASURE OF CONCENTRATION

V. FEEDSTOCKS (See Appendix for CAS Numbers)

CATEGORY	01 FEEDSTOCK NAME	02 CAS NUMBER	CATEGORY	01 FEEDSTOCK NAME	02 CAS NUMBER
FDS			FDS		
FDS			FDS		
FDS			FDS		
FDS			FDS		

VI. SOURCES OF INFORMATION (Cite specific references, e.g., state files, sample analysis, reports)

KYNREPC files
Enforcement Branch files

EPA

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

I. IDENTIFICATION	
01 STATE	02 SITE NUMBER
KY	D061564001

II. HAZARDOUS CONDITIONS AND INCIDENTS

01 ☐ A. GROUNDWATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ B. SURFACE WATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ C. CONTAMINATION OF AIR — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ D. FIRE/EXPLOSIVE CONDITIONS — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ E. DIRECT CONTACT — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ F. CONTAMINATION OF SOIL — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 AREA POTENTIALLY AFFECTED: _____ (Acres) 04 NARRATIVE DESCRIPTION

01 ☐ G. DRINKING WATER CONTAMINATION — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ H. WORKER EXPOSURE/INJURY — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 WORKERS POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ I. POPULATION EXPOSURE/INJURY — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

EPA

POTENTIAL HAZARDOUS WASTE SITE
PRELIMINARY ASSESSMENT
PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

I. IDENTIFICATION
01 STATE: KY | 02 SITE NUMBER: KYD061564001

II. HAZARDOUS CONDITIONS AND INCIDENTS (Continued)

01 ☐ J. DAMAGE TO FLORA — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ K. DAMAGE TO FAUNA — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION (Include name(s) of species)

01 ☐ L. CONTAMINATION OF FOOD CHAIN — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ M. UNSTABLE CONTAINMENT OF WASTES (Spills/runoff/standing liquids/leaking drums) — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED: _____ 04 NARRATIVE DESCRIPTION

01 ☐ N. DAMAGE TO OFFSITE PROPERTY — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ O. CONTAMINATION OF SEWERS, STORM DRAINS, WWTPs — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

01 ☐ P. ILLEGAL/UNAUTHORIZED DUMPING — 02 ☐ OBSERVED (DATE: _____) ☐ POTENTIAL ☐ ALLEGED
04 NARRATIVE DESCRIPTION

05 DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL, OR ALLEGED HAZARDS

III. TOTAL POPULATION POTENTIALLY AFFECTED: _____

IV. COMMENTS

This facility is now Regulated By RCRA AND is now UNDER Enforcement preceedings in the Division's Enforcement Branch.
Site Has 15(+) Tanks with waste in them- Tanks are rusting & spills are evident according to pictures in Division files. Sample analysis of 3/13/84 shows high concentrations of Tri-chloroethylene in tank samples. The spillage area would be good sampling Locations for future inspections.

V. SOURCES OF INFORMATION (Cite specific references, e. g., state files, sample analyses, reports)

KYAREPC FILES
Louisville field Personael - Enforcement files.

EPA FORM 2070-12 (7-81)



(VALLEY STATION) 3860 III SE

Mapped by the Army Map Service and the Geological Survey
Edited and Published by the Geological Survey

Control by USGS, NOS/NOAA, USCE, and the City of Louisville

Topography by photogrammetric methods from aerial photographs taken 1947. Field checked 1950. Revised from aerial photographs taken 1978. Field checked 1979. Map edited 1982

Polyconic projection. 10,000-foot grid ticks based on Kentucky coordinate system, north zone
1000-meter Universal Transverse Mercator grid, zone 16
1927 North American Datum
To place on predicted North American Datum 1983 move the projection lines 4 meters south and 3 meters west as shown by dashed corner ticks

Red tint indicates areas in which only landmark buildings are shown

MN GN
1½° 27 MILS 0°49' 15 MILS

UTM GRID AND 1982 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE

1 ½
1000 0 1000 2000
1 5

CONTOUR INT
DOTTED LINES REPRE
NATIONAL GEODETIC V

THIS MAP COMPLIES WITH NATI
FOR SALE BY U. S. GEOLOGICAL
KENTUCKY GEOLOGICAL SURV
AND KENTUCKY DEPARTMENT OF CO
A FOLDER DESCRIBING TOPOGRAPHIC MAPS

EPA

POTENTIAL HAZARDOUS WASTE SITE
IDENTIFICATION AND PRELIMINARY ASSESSMENT

REGION:

SITE NUMBER (to be assigned by EPA): 39

NOTE: This form is completed for each potential hazardous waste site to help set priorities for site inspection. The information submitted on this form is based on available records and may be updated on subsequent forms as a result of additional inquiries and on-site inspections.

GENERAL INSTRUCTIONS: Complete Sections I and III through X as completely as possible before Section II (Preliminary Assessment). File this form in the Regional Hazardous Waste Log File and submit a copy to: U.S. Environmental Protection Agency; Site Tracking System; Hazardous Waste Enforcement Task Force (EN-335); 401 M St., SW; Washington, DC 20460.

I. SITE IDENTIFICATION

A. SITE NAME: Kentucky Petroleum Products Co.

B. STREET (or other identifier): 4019 Blanton Lane

C. CITY: Louisville

D. STATE: KY

E. ZIP CODE: 40216

F. COUNTY NAME: Jefferson

G. OWNER/OPERATOR (If known)

1. NAME: Same

2. TELEPHONE NUMBER: (502) 447-1802

H. TYPE OF OWNERSHIP

☐ 1. FEDERAL ☐ 2. STATE ☐ 3. COUNTY ☐ 4. MUNICIPAL ☒ 5. PRIVATE ☐ 6. UNKNOWN

I. SITE DESCRIPTION: This is a facility which reclaims waste oil, separates out sludge and water, and sellsoil to a reprocessor. Facility consists of about 15 tanksand a oil water separater.

J. HOW IDENTIFIED (i.e., citizen's complaints, OSHA citations, etc.): Eckhardt Report

K. DATE IDENTIFIED (mo., day, & yr.):

L. PRINCIPAL STATE CONTACT

1. NAME: Pat Haight

2. TELEPHONE NUMBER: (502) 564-6716

II. PRELIMINARY ASSESSMENT (complete this section last)

A. APPARENT SERIOUSNESS OF PROBLEM

☐ 1. HIGH ☐ 2. MEDIUM ☒ 3. LOW ☐ 4. NONE ☐ 5. UNKNOWN

B. RECOMMENDATION

☒ 1. NO ACTION NEEDED (no hazard)

☐ 2. IMMEDIATE SITE INSPECTION NEEDED
a. TENTATIVELY SCHEDULED FOR:
b. WILL BE PERFORMED BY:

☐ 3. SITE INSPECTION NEEDED
a. TENTATIVELY SCHEDULED FOR:
b. WILL BE PERFORMED BY:

☐ 4. SITE INSPECTION NEEDED (low priority)

C. PREPARER INFORMATION

1. NAME: Carl Horneman

2. TELEPHONE NUMBER: (502) 588-4254

3. DATE (mo., day, & yr.): 2-27-80

III. SITE INFORMATION

A. SITE STATUS

☒ 1. ACTIVE (Those industrial or municipal sites which are being used for waste treatment, storage, or disposal on a continuing basis, even if intermittently.)

☐ 2. INACTIVE (Those sites which no longer receive wastes.)

☐ 3. OTHER (specify): (Those sites that include such incidents like "midnight dumping" where no regular or continuing use of the site for waste disposal has occurred.)

B. IS GENERATOR ON SITE?

☐ 1. NO ☒ 2. YES (specify generator's four-digit SIC Code):

C. AREA OF SITE (in acres) (problem)

1 acre

D. IF APPARENT SERIOUSNESS OF SITE IS HIGH, SPECIFY COORDINATES

1. LATITUDE (deg.-min.-sec.):

2. LONGITUDE (deg.-min.-sec.):

E. ARE THERE BUILDINGS ON THE SITE? (in problem area)

☐ 1. NO ☒ 2. YES (specify): Pump house

Continue On Reverse

Continued from front

IV. CHARACTERIZATION OF SITE ACTIVITY

Indicate the major site activity(ies) and describe(s) relating to each activity by marking 'X' in the appropriate boxes.

A. TRANSPORTER	B. STORER	C. TREATER	D. DISPOSER
[ ] 1. RAIL	[ ] 1. PILE	[ ] 1. FILTRATION	[ ] 1. LANDFILL
[ ] 2. SHIP	[ ] 2. SURFACE IMPOUNDMENT	[ ] 2. INCINERATION	[ ] 2. LANDFARM
[ ] 3. BARGE	[ ] 3. DRUMS	[ ] 3. VOLUME REDUCTION	[ ] 3. OPEN DUMP
[X] 4. TRUCK	[ ] 4. TANK, ABOVE GROUND	[X] 4. RECYCLING/RECOVERY	[ ] 4. SURFACE IMPOUNDMENT
[ ] 5. PIPELINE	[ ] 5. TANK, BELOW GROUND	[ ] 5. CHEM./PHYS. TREATMENT	[ ] 5. MIDNIGHT DUMPING
[ ] 6. OTHER (specify):	[ ] 6. OTHER (specify)	[ ] 6. BIOLOGICAL TREATMENT	[ ] 6. INCINERATION
		[ ] 7. WASTE OIL REPROCESSING	[ ] 7. UNDERGROUND INJECTION
		[ ] 8. SOLVENT RECOVERY	[ ] 8. OTHER (specify):
		[ ] 9. OTHER (specify):	

E. SPECIFY DETAILS OF SITE ACTIVITIES AS NEEDED

V. WASTE RELATED INFORMATION

A. WASTE TYPE

[ ] 1 UNKNOWN [XX] 2 LIQUID [ ] 3. SOLID [ ] 4. SLUDGE [ ] 5. GAS

B. WASTE CHARACTERISTICS

[ ] 1. UNKNOWN [ ] 2. CORROSIVE [ ] 3. IGNITABLE [ ] 4 RADIOACTIVE [ ] 5 HIGHLY VOLATILE
[ ] 6 TOXIC [ ] 7 REACTIVE [ ] 8 INERT [XX] 9. FLAMMABLE

[ ] 10. OTHER (specify):

C. WASTE CATEGORIES

1. Are records of wastes available? Specify items such as manifests, inventories, etc. below.

No

2. Estimate the amount (specify unit of measure) of waste by category; mark 'X' to indicate which wastes are present.

a. SLUDGE	b. OIL	c. SOLVENTS	d. CHEMICALS	e. SOLIDS	f. OTHER
AMOUNT	AMOUNT	AMOUNT	AMOUNT	AMOUNT	AMOUNT
UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE	UNIT OF MEASURE
[X] (1) PAINT, PIGMENTS	[X] (1) OILY WASTES	[X] (1) HALOGENATED SOLVENTS	[X] (1) ACIDS	[X] (1) FLYASH	[X] (1) LABORATORY PHARMACEUT.
[ ] (2) METALS SLUDGES	[ ] (2) OTHER (specify):	[ ] (2) NON-HALOGNTD. SOLVENTS	[ ] (2) PICKLING LIQUORS	[ ] (2) ASBESTOS	[ ] (2) HOSPITAL
[ ] (3) POTW		[ ] (3) OTHER (specify):	[ ] (3) CAUSTICS	[ ] (3) MILLING/ MINE TAILINGS	[ ] (3) RADIOACTIVE
[ ] (4) ALUMINUM SLUDGE			[ ] (4) PESTICIDES	[ ] (4) FERROUS SMLTG. WASTES	[ ] (4) MUNICIPAL
[ ] (5) OTHER (specify):			[ ] (5) DYES/INKS	[ ] (5) NON-FERROUS SMLTG. WASTES	[ ] (5) OTHER (specify):
			[ ] (6) CYANIDE	[ ] (6) OTHER (specify):	
			[ ] (7) PHENOLS		
			[ ] (8) HALOGENS		
			[ ] (9) PCB		
			[ ] (10) METALS		
			[ ] (11) OTHER (specify)		

No quantity figures were obtained.

Continue On Page 3

Continued From Page 2

V. WASTE RELATED INFORMATION (continued)

LIST SUBSTANCES OF GREATEST CON[illegible] WHICH MAY BE ON THE SITE (place in descend[illegible]order of hazard).

None

4. ADDITIONAL COMMENTS OR NARRATIVE DESCRIPTION OF SITUATION KNOWN OR REPORTED TO EXIST AT THE SITE.

VI. HAZARD DESCRIPTION

A. TYPE OF HAZARD	B. POTENTIAL HAZARD (mark 'X')	C. ALLEGED INCIDENT (mark 'X')	D. DATE OF INCIDENT (mo., day, yr.)	E. REMARKS
1. NO HAZARD				
2. HUMAN HEALTH				
3. NON-WORKER INJURY/EXPOSURE				
4. WORKER INJURY				
5. CONTAMINATION OF WATER SUPPLY				
6. CONTAMINATION OF FOOD CHAIN				
7. CONTAMINATION OF GROUND WATER				
8. CONTAMINATION OF SURFACE WATER	X			Steps are being taken to prevent possibility of spills (dike).
9. DAMAGE TO FLORA/FAUNA				
10. FISH KILL				
11. CONTAMINATION OF AIR				
12. NOTICEABLE ODORS				
13. CONTAMINATION OF SOIL				
14. PROPERTY DAMAGE				
15. FIRE OR EXPLOSION				
16. SPILLS/LEAKING CONTAINERS/ RUNOFF/STANDING LIQUIDS				
17. SEWER, STORM DRAIN PROBLEMS				
18. EROSION PROBLEMS				
19. INADEQUATE SECURITY				
20. INCOMPATIBLE WASTES				
21. MIDNIGHT DUMPING				
22. OTHER (specify):				

Continue On Reverse

VII. PERMIT INFORMATION

A. INDICATE ALL APPLICABLE PERMITS HELD BY THE SITE.

☐ 1. NPDES PERMIT ☐ 2. SPCC PLAN ☐ 3. STATE PERMIT (specify): _____
☐ 4. AIR PERMITS ☐ 5. LOCAL PERMIT ☐ 6. RCRA TRANSPORTER
☐ 7. RCRA STORER ☐ 8. RCRA TREATER ☐ 9. RCRA DISPOSER

☐ 10. OTHER (specify): _____

B. IN COMPLIANCE?

☒ 1. YES ☐ 2. NO ☐ 3. UNKNOWN

4. WITH RESPECT TO (list regulation name & number): _____

VIII. PAST REGULATORY ACTIONS

☒ A. NONE ☐ B. YES (summarize below)

IX. INSPECTION ACTIVITY (past or on-going)

☐ A. NONE ☒ B. YES (complete items 1,2,3, & 4 below)

1. TYPE OF ACTIVITY	2. DATE OF PAST ACTION (mo., day, & yr.)	3. PERFORMED BY: (EPA/State)	4. DESCRIPTION
Inspection	2-27-80	State	Permit application for storage facility and CWA spec plan being prepared.

X. REMEDIAL ACTIVITY (past or on-going)

☒ A. NONE ☐ B. YES (complete items 1, 2, 3, & 4 below)

1. TYPE OF ACTIVITY	2. DATE OF PAST ACTION (mo., day, & yr.)	3. PERFORMED BY: (EPA/State)	4. DESCRIPTION

NOTE: Based on the information in Sections III through X, fill out the Preliminary Assessment (Section II) information on the first page of this form.